Cloudera Runtime 7.1.9

Apache Hadoop YARN Reference

Date published: 2020-07-28 Date modified: 2023-09-07



https://docs.cloudera.com/

Legal Notice

© Cloudera Inc. 2024. All rights reserved.

The documentation is and contains Cloudera proprietary information protected by copyright and other intellectual property rights. No license under copyright or any other intellectual property right is granted herein.

Unless otherwise noted, scripts and sample code are licensed under the Apache License, Version 2.0.

Copyright information for Cloudera software may be found within the documentation accompanying each component in a particular release.

Cloudera software includes software from various open source or other third party projects, and may be released under the Apache Software License 2.0 ("ASLv2"), the Affero General Public License version 3 (AGPLv3), or other license terms. Other software included may be released under the terms of alternative open source licenses. Please review the license and notice files accompanying the software for additional licensing information.

Please visit the Cloudera software product page for more information on Cloudera software. For more information on Cloudera support services, please visit either the Support or Sales page. Feel free to contact us directly to discuss your specific needs.

Cloudera reserves the right to change any products at any time, and without notice. Cloudera assumes no responsibility nor liability arising from the use of products, except as expressly agreed to in writing by Cloudera.

Cloudera, Cloudera Altus, HUE, Impala, Cloudera Impala, and other Cloudera marks are registered or unregistered trademarks in the United States and other countries. All other trademarks are the property of their respective owners.

Disclaimer: EXCEPT AS EXPRESSLY PROVIDED IN A WRITTEN AGREEMENT WITH CLOUDERA, CLOUDERA DOES NOT MAKE NOR GIVE ANY REPRESENTATION, WARRANTY, NOR COVENANT OF ANY KIND, WHETHER EXPRESS OR IMPLIED, IN CONNECTION WITH CLOUDERA TECHNOLOGY OR RELATED SUPPORT PROVIDED IN CONNECTION THEREWITH. CLOUDERA DOES NOT WARRANT THAT CLOUDERA PRODUCTS NOR SOFTWARE WILL OPERATE UNINTERRUPTED NOR THAT IT WILL BE FREE FROM DEFECTS NOR ERRORS, THAT IT WILL PROTECT YOUR DATA FROM LOSS, CORRUPTION NOR UNAVAILABILITY, NOR THAT IT WILL MEET ALL OF CUSTOMER'S BUSINESS REQUIREMENTS. WITHOUT LIMITING THE FOREGOING, AND TO THE MAXIMUM EXTENT PERMITTED BY APPLICABLE LAW, CLOUDERA EXPRESSLY DISCLAIMS ANY AND ALL IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO IMPLIED WARRANTIES OF MERCHANTABILITY, QUALITY, NON-INFRINGEMENT, TITLE, AND FITNESS FOR A PARTICULAR PURPOSE AND ANY REPRESENTATION, WARRANTY, OR COVENANT BASED ON COURSE OF DEALING OR USAGE IN TRADE.

Contents

| Tuning Apache Hadoop YARN | |
|--|----|
| YARN tuning overview | |
| Step 1: Worker host configuration | |
| Step 2: Worker host planning | |
| Step 3: Cluster size | 9 |
| Steps 4 and 5: Verify settings | 9 |
| Step 6: Verify container settings on cluster | 9 |
| Step 6A: Cluster container capacity | |
| Step 6B: Container parameters checking | |
| Step 7: MapReduce configuration | |
| Step 7A: MapReduce settings checking | |
| Set properties in Cloudera Manager | |
| Configure memory settings | |
| YARN Configuration Properties | 13 |
| | |
| Use the YARN REST APIs to manage applications | |
| Use the YARN REST APIs to manage applications | |
| Use the YARN REST APIs to manage applications | |
| Use the YARN REST APIs to manage applications Comparison of Fair Scheduler with Capacity Scheduler Why one scheduler? | |
| Use the YARN REST APIs to manage applications Comparison of Fair Scheduler with Capacity Scheduler Why one scheduler? Scheduler performance improvements | |
| Use the YARN REST APIs to manage applications Comparison of Fair Scheduler with Capacity Scheduler Why one scheduler? Scheduler performance improvements Feature comparison | |
| Use the YARN REST APIs to manage applications Comparison of Fair Scheduler with Capacity Scheduler Why one scheduler? Scheduler performance improvements Feature comparison Migration from Fair Scheduler to Capacity Scheduler | |
| Use the YARN REST APIs to manage applications Comparison of Fair Scheduler with Capacity Scheduler Why one scheduler? Scheduler performance improvements Feature comparison Migration from Fair Scheduler to Capacity Scheduler Configuring and using Queue Manager REST API | |
| Use the YARN REST APIs to manage applications Comparison of Fair Scheduler with Capacity Scheduler Why one scheduler? Scheduler performance improvements Feature comparison Migration from Fair Scheduler to Capacity Scheduler Configuring and using Queue Manager REST API Limitations | |
| Use the YARN REST APIs to manage applications Comparison of Fair Scheduler with Capacity Scheduler Why one scheduler? Scheduler performance improvements Feature comparison Migration from Fair Scheduler to Capacity Scheduler Configuring and using Queue Manager REST API Limitations Using the REST API | |
| Use the YARN REST APIs to manage applications | |
| Use the YARN REST APIs to manage applications | |
| Use the YARN REST APIs to manage applications | |
| Use the YARN REST APIs to manage applications | |
| Use the YARN REST APIs to manage applications | |
| Use the YARN REST APIs to manage applications | |

Tuning Apache Hadoop YARN

YARN tuning overview

Abstract description of a YARN cluster and the goals of YARN tuning.

This topic applies to YARN clusters only, and describes how to tune and optimize YARN for your cluster.



Note: Download the Cloudera YARN tuning spreadsheet to help calculate YARN configurations. For a short video overview, see Tuning YARN Applications.

This overview provides an abstract description of a YARN cluster and the goals of YARN tuning.









YARN tuning has three phases. The phases correspond to the tabs in the YARN tuning spreadsheet.

- 1. Cluster configuration, where you configure your hosts.
- 2. YARN configuration, where you quantify memory and vcores.
- **3.** MapReduce configuration, where you allocate minimum and maximum resources for specific map and reduce tasks.

YARN and MapReduce have many configurable properties. The YARN tuning spreadsheet lists the essential subset of these properties that are most likely to improve performance for common MapReduce applications.

Step 1: Worker host configuration

Define the configuration for a single worker host computer in your cluster

Step 1 is to define the configuration for a single worker host computer in your cluster.

| STEP 1: Worker Host | Configura | ation | | | |
|---|---|------------------------------|---------------------------------|----------------------|--|
| Enter your likely machine confi uncertain what machines you p will suit what you expect to bu | guration in the plan on buying y. | e input boxe , put in som | es below. If ye ne minimum v | ou are alues that | |
| Host Components | Quantity | Size | Total | Description | / Notes |
| RAM | 256G | | 256G | Node memory | in Gigabytes |
| CPU | 4 | | 48 | Number of CPI | U's and the number of HW cores per CPU. The calculation of vcores below includes HyperThreading support. |
| HyperThreading CPU | yes 👻 | | | Does the CPU | support HyperThreading? |
| HDD (Hard Disk Drive) | 24 | 31 | 72G | Number of Har | rd Drives and size per drive in JBOD Configuration |
| | | | | | |

As with any system, the more memory and CPU resources available, the faster the cluster can process large amounts of data. A machine with 4 CPUs with HyperThreading, each with 6 cores, provides 48 vcores per host.

3 TB hard drives in a 2-unit server installation with 12 available slots in JBOD (Just a Bunch Of Disks) configuration is a reasonable balance of performance and pricing at the time the spreadsheet was created. The cost of storage decreases over time, so you might consider 4 TB disks. Larger disks are expensive and not required for all use cases.

Two 1-Gigabit Ethernet ports provide sufficient throughput at the time the spreadsheet was published, but 10-Gigabit Ethernet ports are an option where price is of less concern than speed.

Step 2: Worker host planning

Allocate resources on each worker machine,

| STEP 2: Worker Host | t Planning | | | |
|---|---|------------------------------|-------------------------------|---|
| Now that you have your base below to allocate resources, m components that run on the h | Host configurat nainly CPU and ost. | ion from Ste memory, to 1 | p 1, use the the various s | e table software |
| | | | Memory | |
| Service | Category | CPU (cores) | (MB) | Notes |
| Operating System | Overhead | 1 | 8192 | 2 Most operating systems use 4-8GB minimum. |
| Other services | Overhead | 0 | | 0 Enter the required cores or memory for non CDH services not part of the OS. |
| Cloudera Manager agent | Overhead | 1 | 1024 | 4 Allocate 1GB and 1 vcore for Cloudera Manager agents, which track resource usage on a host. |
| HDFS DataNode | CDH | 1 | 1024 | 4 Allocation for the HDFS DataNode heap: default 1GB and 1 vcore. |
| ARN NodeManager | CDH | 1 | 1024 | 4 Allocation for the YARN NodeManager heap: default 1GB and 1 vcore |
| mpala daemon | CDH | 0 | 0 | 0 (Optional Service) Suggestion: Allocate at least 16GB memory when using Impala. |
| Hbase RegionServer | CDH | 0 | 0 | 0 (Optional Service) Suggestion: Allocate no more than 12-16GB memory when using HBase Region Servers. |
| Solr Server | CDH | 0 | 0 | 0 (Optional Service) Suggestion: Minimum 1GB for Solr server. More might be necessary depending on index sizes. |
| Kudu Server | CDH | 0 | 0 | O(Optional Service) Suggestion: Minimum 1GB for Kudu Tablet server. More might be necessary depending on data |
| Available Container Resources | | 44 | 250880 | |
| Container resources | | | | |
| Physical Cores to Veores Multiplier | | 1 | | Set this ratio based on the expected number of consurrent threads in a container per thread core. Default is 1 |
| VAPN Available Vcores | | 1 | | This value will be used in STEP 4 for VAPN Configuration |
| VAPN Available Momony | | 44 | 250990 | This value will be used in STEP 4 for FARV configuration |
| ranin Available Mentory | | | 250880 | I mis value will be used in STEP 4 for TAKIN Computation |

Start with at least 8 GB for your operating system, and 1 GB for Cloudera Manager. If services outside of Cloudera Runtime require additional resources, add those numbers under Other Services.

The HDFS DataNode uses a minimum of 1 core and about 1 GB of memory. The same requirements apply to the YARN NodeManager.

The spreadsheet lists several optional services:

- Impala daemon requires at least 16 GB for the daemon.
- HBase Region Servers requires 12-16 GB of memory.
- Solr server requires a minimum of 1 GB of memory.
- Kudu Tablet server requires a minimum of 1 GB of memory.

Any remaining resources are available for YARN applications (Spark and MapReduce). In this example, 44 CPU cores are available. Set the multiplier for vcores you want on each physical core to calculate the total available vcores.

Step 3: Cluster size

Having defined the specifications for each host in your cluster, enter the number of worker hosts needed to support your business case.

To see the benefits of parallel computing, set the number of hosts to a minimum of 10.

STEP 3: Cluster Size Enter the number of nodes you have (or expect to have) in the cluster Quantity Number of Worker Hosts in the cluster

Steps 4 and 5: Verify settings

Verify the memory and vcore settings.

Step 4 pulls forward the memory and vcore numbers from step 2. Step 5 shows the total memory and vcores for the cluster.

| STEP 4: YARN Configuration on Cluster | r | | |
|---|---------------|-----------------|---|
| These are the first set of configuration values for your clu | ister. You c | an set | |
| these values in YARN->Configuration | | | |
| | | | |
| YARN NodeManager Configuration Properties | Value | Note | |
| yarn.nodemanager.resource.cpu-vcores | 44 | Copied from ST | EP 2 "Available Resources" |
| yarn.nodemanager.resource.memory-mb | 250880 | Copied from ST | EP 2 "Available Resources" |
| | | | |
| STEP 5: Verify YARN Settings on Cluste | er | | |
| Go to the Resource Manager Web UI (usually | | | |
| http:// <resourcemanagerip>:8088/ and verify the "Mem</resourcemanagerip> | nory Total" a | and | |
| "Vcores Total" matches the values above. If your machin | Ie has no ba | d nodes. | |
| then the numbers should match exactly. | | | |
| Resource Manager Property to Check | Value | Note | |
| Expected Value for "Vcores Total" | 440 | Calculated from | n STEP 2 "YARN Available Vcores" and STEP 3 |
| Expected Value for "Memory Total" (in GB) | 2450 | Calculated from | n STEP 2 "YARN Available Memory" and STEP 3 |
| | | | |

Step 6: Verify container settings on cluster

You can change the values that impact the size of your containers.

The minimum number of vcores should be 1. When additional vcores are required, adding 1 at a time should result in the most efficient allocation. Set the maximum number of vcore reservations to the size of the node.

Set the minimum and maximum reservations for memory. The increment should be the smallest amount that can impact performance. Here, the minimum is approximately 1 GB, the maximum is approximately 8 GB, and the increment is 512 MB.

| STEP 6: Verify Container Settings on C | | | |
|--|-------------|--|---|
| In order to have YARN jobs run cleanly, you need to confi properties. | | | |
| YARN Container Configuration Properties (Vcores) | Value | Description | |
| yarn.scheduler.minimum-allocation-vcores | 1 | Minimum vcor | e reservation for a container |
| yarn.scheduler.maximum-allocation-vcores | 44 | Maximum vco | re reservation for a container |
| yarn.scheduler.increment-allocation-vcores | 1 | Vcore allocation | ons must be a multiple of this value |
| | | | |
| YARN Container Configuration Properties (Memory) | Value | Description | |
| yarn.scheduler.minimum-allocation-mb | Minimum mer | nory reservation for a container in MegaByte | |
| yarn.scheduler.maximum-allocation-mb | 250880 | Maximum mer | mory reservation for a container in MegaByte |
| yarn.scheduler.increment-allocation-mb | 512 | Memory alloca | ations must be a multiple of this value in MegaByte |

Step 6A: Cluster container capacity

Validate the minimum and maximum number of containers in your cluster, based on the numbers you entered

Step 6A: Cluster Container Capacity

This section will tell you the capacity of your cluster (in terms of containers).

| Cluster Container Estimates | Minimum | Maximum | |
|--|---------|---------|--|
| Max possible number of containers, based on memory configu | | 2450 | |
| Max possible number of containers, based on vcore configurat | | 440 | |
| Container number based on 2 containers per disk spindles | | 480 | |
| Min possible number of containers, based on memory configu | ration | 10 | |
| Min possible number of containers, based on vcore configurat | ion | 10 | |
| | | | |

Step 6B: Container parameters checking

See whether you have over-allocated resources.

| STEP 6B: Container Sanity Checking | | |
|---|-------------|---|
| This section will do some basic checking of your contai against the hosts. | ner paramet | ters in STEP 6 |
| | Check | |
| Sanity Check | Status | Description |
| Scheduler maximum vcores must be larger than minimum | GOOD | yarn.scheduler.maximum-allocation-vcores >= yarn.scheduler.minimum-allocation-vcores |
| Scheduler maximum allocation MB must be larger than minimum | GOOD | yarn.scheduler.maximum-allocation-mb >= yarn.scheduler.minimum-allocation-mb |
| Scheduler minimum vcores must be greater than or equal to 0 | GOOD | yarn.scheduler.minimum-allocation-vcores >= 0 |
| Scheduler maximum vcores must be greater than or equal to 1 | GOOD | yarn.scheduler.maximum-allocation-vcores >= 1 |
| Host vcores must be larger than scheduler minimum vcores | GOOD | yarn.nodemanager.resource.cpu-vcores >= yarn.scheduler.minimum-allocation-vcores |
| Host vcores must be larger than scheduler maximum vcores | GOOD | yarn.nodemanager.resource.cpu-vcores >= yarn.scheduler.maximum-allocation-vcores |
| Host allocation MB must be larger than scheduler minimum | GOOD | yarn.nodemanager.resource.memory-mb >= yarn.scheduler.maximum-allocation-mb |
| Host allocation MB must be larger than scheduler maximum vcores | GOOD | yarn.nodemanager.resource.memory-mb >= yarn.scheduler.minimum-allocation-mb |
| Small container limit | GOOD | If yarn.scheduler.minimum-allocation-mb is less than 1GB, containers will likely get killed by YARN due to OutOfMem |

Step 7: MapReduce configuration

You can increase the memory allocation for the ApplicationMaster, map tasks, and reduce tasks.

The minimum vcore allocation for any task is always 1. The Spill/Sort memory allocation of 400 should be sufficient, and should be (rarely) increased if you determine that frequent spills to disk are hurting job performance.

The common MapReduce parameters mapreduce.map.java.opts, mapreduce.reduce.java.opts, and yarn.app.mapredu ce.am.command-opts are configured for you automatically based on the *Heap to Container Size Ratio*.

STEP 7: MapReduce Configuration

For CDH 5.5 and later we recommend that only the heap or the container size is specified for map and reduce tasks. The value that is not specified will be calculated based on the setting mapreduce.job.heap.memory-mb.ratio. This calculation follows Cloudera Manager and calculates the heap size based on the ratio and the container size.

| Application Master Configuration properties | Valu | le | Description | |
|---|---------|------|----------------|------------------------------------|
| yarn.app.mapreduce.am.resource.cpu-vcores | | 1 | AM container | vcore reservation |
| yarn.app.mapreduce.am.resource.mb | | 1024 | AM container | memory reservation in MegaByte |
| yarn.app.mapreduce.am.command-opts | -Xmx | 800 | AM Java heap | size in MegaByte |
| Task auto heap sizing | | | | |
| Use task auto heap sizing | yes | - | | |
| mapreduce.job.heap.memory-mb.ratio | | 0.8 | Ratio between | the container size and task heap s |
| Map Task Configuration properties | | | | |
| mapreduce.map.cpu.vcores | | 1 | Map task vcor | e reservation |
| mapreduce.map.memory.mb | | 1024 | Map task mem | nory reservation in MegaByte |
| mapreduce.map.java.opts i | ignored | 800 | Map task Java | heap size in MegaByte |
| mapreduce.task.io.sort.mb | | 400 | Spill/Sort mem | nory reservation |
| ReduceTask Configuration properties | | | | |
| mapreduce.reduce.cpu.vcores | | 1 | Reduce task vo | core reservation |
| mapreduce.reduce.memory.mb | | 1024 | Reduce task m | emory reservation in MegaByte |
| mapreduce.reduce.java.opts i | ignored | 800 | Reduce Task Ja | ava heap size in MegaByte |

Step 7A: MapReduce settings checking

Verify at a glance that all of your minimum and maximum resource allocations are within the parameters you set.

| STEP 7A: MapReduce Sanity Checking | g | |
|---|-----------------|---|
| Sanity check ManReduce settings against container mit | _ nimum/maxi | imum |
| properties | | |
| properties. | | |
| Application Master Sanity Checks | Value | Description |
| AM vcore request must fit within scheduler limits | GOOD | varn.scheduler.minimum-allocation-vcores <= varn.app.mapreduce.am.resource.cpu-vcores <= varn-scheduler.maximum-allocation-vcores |
| AM memory request must fit within scheduler limits | GOOD | yarn.scheduler.minimum-allocation-mb <= yarn.app.mapreduce.am.resource.cpu-vcores <= yarn.scheduler.maximum-allocation-mb |
| Container size must large enough for java heap and overhead | GOOD | Java Heap should be between 75% and 90% of the container size: too low wastes resources, to high could lead to OOM |
| | | |
| Ratio should be between 0.75 and 0.9 | GOOD | Java Heap should be between 75% and 90% of the container size: too low wastes resources, to high could lead to OOM |
| | | |
| Map Task Sanity Checks | Value | Description |
| Map task vcore request must fit within scheduler limits | GOOD | yarn.scheduler.minimum-allocation-vcores <= mapreduce.map.cpu.vcores <= yarn-scheduler.maximum-allocation-vcores |
| Map task memory request must fit within scheduler limits | GOOD | yarn.scheduler.minimum-allocation-mb <= mapreduce.map.memory.mb <= yarn.scheduler.maximum-allocation-mb |
| Container size must large enough for java heap and overhead | N/A | Java Heap should be between 75% and 90% of the container size: too low wastes resources, to high could lead to OOM |
| Spill/Sort memory should not use whole map task heap | GOOD | Make sure that Spill/Sort memory reservation uses between 40% and 60% of the heap of a map task. |
| | | |
| Reduce Task Sanity Checks | Value | Description |
| Reduce task vcore request must fit within scheduler limits | GOOD | yarn.scheduler.minimum-allocation-vcores <= mapreduce.reduce.cpu.vcores <= yarn-scheduler.maximum-allocation-vcores |
| Reduce task memory request must fit within scheduler limits | GOOD | yarn.scheduler.minimum-allocation-mb <= mapreduce.reduce.memory.mb <= yarn.scheduler.maximum-allocation-mb |
| Container size must large enough for java heap and overhead | N/A | Java Heap should be between 75% and 90% of the container size: too low wastes resources, to high could lead to OOM |

Set properties in Cloudera Manager

When you are satisfied with the cluster configuration estimates, use the values in the spreadsheet to set the corresponding properties in Cloudera Manager

| Step | YARN/MapReduce Property | Cloudera Manager Equivalent |
|------|--|---------------------------------------|
| 4 | yarn.nodemanager.resource.cpu-vcores | Container Virtual CPU Cores |
| 4 | yarn.nodemanager.resource.memory-mb | Container Memory |
| 6 | yarn.scheduler.minimum-allocation-vcores | Container Virtual CPU Cores Minimum |
| 6 | yarn.scheduler.maximum-allocation-vcores | Container Virtual CPU Cores Maximum |
| 6 | yarn.scheduler.increment-allocation-vcores | Container Virtual CPU Cores Increment |
| 6 | yarn.scheduler.minimum-allocation-mb | Container Memory Minimum |
| 6 | yarn.scheduler.maximum-allocation-mb | Container Memory Maximum |
| 6 | yarn.scheduler.increment-allocation-mb | Container Memory Increment |
| 7 | yarn.app.mapreduce.am.resource.cpu-vcores | ApplicationMaster Virtual CPU Cores |
| 7 | yarn.app.mapreduce.am.resource.mb | ApplicationMaster Memory |
| 7 | mapreduce.map.cpu.vcores | Map Task CPU Virtual Cores |
| 7 | mapreduce.map.memory.mb | Map Task Memory |
| 7 | mapreduce.reduce.cpu.vcores | Reduce Task CPU Virtual Cores |
| 7 | mapreduce.reduce.memory.mb | Reduce Task Memory |
| 7 | mapreduce.task.io.sort.mb | I/O Sort Memory |

Table 1: Cloudera Manager Property Correspondence

Configure memory settings

The memory configuration for YARN and MapReduce memory is important to get the best performance from your cluster.

Several different settings are involved. The table below shows the default settings, as well as the settings that Cloudera recommends, for each configuration option.

| Table 2: | YARN | and N | | Memory | Confid | uration |
|----------|------|-------|------------|-----------|--------|----------|
| | | and n | napricuuce | Michiel y | Count | Julation |

| Cloudera Manager Property Name | Cloudera Runtime Property Name | Default Configuration | Cloudera Tuning Guidelines |
|-----------------------------------|--|---------------------------------|--|
| Container Memory Minimum | yarn.scheduler.minimum-allocatio n-mb | 1 GB | 0 |
| Container Memory Maximum | yarn.scheduler.maximum-alloc ation-mb | 64 GB | amount of memory on largest host |
| Container Memory Increment | yarn.scheduler.increment-allocat ion-mb | 512 MB | Use a fairly large value, such as 128 MB |
| Container Memory | yarn.nodemanager.resource.me mory-mb | 8 GB | 8 GB |
| Map Task Memory | mapreduce.map.memory.mb | 1 GB | 1 GB |
| Reduce Task Memory | mapreduce.reduce.memory.mb | 1 GB | 1 GB |
| Map Task Java Opts Base | mapreduce.map.java.opts | -Djava.net.preferIPv4Stack=true | -Djava.net.preferIPv4Stack=true - Xmx768m |
| Reduce Task Java Opts Base | mapreduce.reduce.java.opts | -Djava.net.preferIPv4Stack=true | -Djava.net.preferIPv4Stack=true - Xmx768m |
| ApplicationMaster Memory | yarn.app.mapreduce.am.resour ce.mb | 1 GB | 1 GB |

| Cloudera Manager Property Name | Cloudera Runtime Property Name | Default Configuration | Cloudera Tuning Guidelines |
|-----------------------------------|---------------------------------------|---------------------------------|--|
| ApplicationMaster Java Opts Base | yarn.app.mapreduce.am.comman d-opt | -Djava.net.preferIPv4Stack=true | -Djava.net.preferIPv4Stack=true - Xmx768m |

YARN Configuration Properties

This table provides information about the parameters listed in the yarn-site.xml file.

| adoop.registry.zk.quorumc2185-node3.coelab.root.hwx.site:2181,c2185- node1.coelab.root.hwx.site:2181,c2185- node2.coelab.root.hwx.site:2181urn.acl.enabletrueurn.admin.aclyarn,hive,hdfs,mapredurn.am.liveness-monitor.expiry-interval-ms600000urn.application.classpath\$HADOOP_CLIENT_CONF_DIR,\$HADOOP_COMMON_HOME/ *,\$HADOOP_COMMON_HOME/lib/*,\$HADOOP_HDFS_HOME/ *,\$HADOOP_HDFS_HOME/lib/*,\$HADOOP_YARN_HOME/*, \$HADOOP_YARN_HOME/lib/*urn.authorization-providerorg.apache.ranger.authorization.yarn.authorizer.RangerYarnAuthorizerurn.client.failover-sleep-base-ms2000 |
|---|
| arn.acl.enabletruearn.admin.aclyarn,hive,hdfs,mapredarn.am.liveness-monitor.expiry-interval-ms600000arn.application.classpath\$HADOOP_CLIENT_CONF_DIR,\$HADOOP_COMMON_HOME/ *,\$HADOOP_COMMON_HOME/lib/*,\$HADOOP_HDFS_HOME/ *,\$HADOOP_HDFS_HOME/lib/*,\$HADOOP_YARN_HOME/ *,\$HADOOP_YARN_HOME/lib/*,\$HADOOP_YARN_HOME/ *,\$HADOOP_YARN_HOME/lib/*arn.authorization-providerorg.apache.ranger.authorization.yarn.authorizer.RangerYarnAuthorizerarn.client.failover-sleep-base-ms100 |
| arn.admin.aclyarn,hive,hdfs,mapredarn.admin.acl600000arn.am.liveness-monitor.expiry-interval-ms600000arn.application.classpath\$HADOOP_CLIENT_CONF_DIR,\$HADOOP_COMMON_HOME/ *,\$HADOOP_COMMON_HOME/lib/*,\$HADOOP_HDFS_HOME/ *,\$HADOOP_HDFS_HOME/lib/*,\$HADOOP_YARN_HOME/*, \$HADOOP_YARN_HOME/lib/*,\$HADOOP_YARN_HOME/*, \$HADOOP_YARN_HOME/lib/*,\$HADOOP_YARN_HOME/*, \$HADOOP_YARN_HOME/lib/*arn.authorization-providerorg.apache.ranger.authorization.yarn.authorizer.RangerYarnAuthorizerurn.client.failover-sleep-base-ms100urn.client.failover-sleep-max-ms2000 |
| arn.am.liveness-monitor.expiry-interval-ms600000arn.application.classpath\$HADOOP_CLIENT_CONF_DIR,\$HADOOP_COMMON_HOME/ *,\$HADOOP_COMMON_HOME/lib/*,\$HADOOP_HDFS_HOME/ *,\$HADOOP_HDFS_HOME/lib/*,\$HADOOP_YARN_HOME/*, \$HADOOP_YARN_HOME/lib/*arn.authorization-providerorg.apache.ranger.authorization.yarn.authorizer.RangerYarnAuthorizerurn.client.failover-sleep-base-ms100urn.client.failover-sleep-max-ms2000 |
| arn.application.classpath\$HADOOP_CLIENT_CONF_DIR,\$HADOOP_COMMON_HOME/ *,\$HADOOP_COMMON_HOME/lib/*,\$HADOOP_HDFS_HOME/ *,\$HADOOP_HDFS_HOME/lib/*,\$HADOOP_YARN_HOME/! *,\$HADOOP_YARN_HOME/lib/*arn.authorization-providerorg.apache.ranger.authorization.yarn.authorizer.RangerYarnAuthorizerurn.client.failover-sleep-base-ms100urn.client.failover-sleep-max-ms2000 |
| arn.authorization-provider org.apache.ranger.authorization.yarn.authorizer.RangerYarnAuthorizer arn.client.failover-sleep-base-ms 2000 |
| arn.client.failover-sleep-base-ms 100 urn.client.failover-sleep-max-ms 2000 |
| un.client.failover-sleep-max-ms 2000 |
| |
| arn.cluster.scaling.recommendation.enable true |
| arn.http.policy HTTPS_ONLY |
| arn.http.rmwebapp.custom.unwrapped.dao.classes com.cloudera.cloud.yarn.resourcemanager.webapp.dao.ClusterScalingInfo,com.cloudera.c |
| arn.log-aggregation-enable true |
| arn.log-aggregation-status.time-out.ms 600000 |
| arn.log-aggregation.TFile.remote-app-log-dir-suffix |
| arn.log-aggregation.file-controller.IFile.class org.apache.hadoop.yarn.logaggregation.filecontroller.ifile.LogAggregationIndexedFileCo |
| arn.log-aggregation.file-controller.TFile.class org.apache.hadoop.yarn.logaggregation.filecontroller.tfile.LogAggregationTFileControlle |
| arn.log-aggregation.file-formats IFile,TFile |
| arn.log-aggregation.retain-seconds 604800 |
| arn.nm.liveness-monitor.expiry-interval-ms 600000 |
| arn.node-labels.enabled true |
| arn.node-labels.fs-store.root-dir /yarn/node-labels |
| arn.resourcemanager.address.rm1546335021 coelab.int.cldr.work:8032 |
| arn.resourcemanager.address.rm1546335074 coelab.int.cldr.work:8032 |
| arn.resourcemanager.admin.address.rm1546335021 coelab.int.cldr.work:8033 |
| arn.resourcemanager.admin.address.rm1546335074 coelab.int.cldr.work:8033 |
| arn.resourcemanager.admin.client.thread-count 1 |
| arn.resourcemanager.am.max-attempts 2 |
| arn.resourcemanager.am.placement-preference-with-node-attributes ORDER NODES IN NodeInstanceType WITH worker > compute |
| arn.resourcemanager.amliveliness-monitor.interval-ms 1000 |

| Parameter | Value | |
|--|--|-------------------|
| varn.resourcemanager.autoscaling.plugin-type | coarse | |
| varn.resourcemanager.client.thread-count | 50 | |
| varn.resourcemanager.cluster-id | varnRM | - |
| yarn.resourcemanager.container.liveness-monitor.interval-ms | 600000 | |
| varn.resourcemanager.ha.automatic-failover.embedded | true | |
| varn.resourcemanager.ha.automatic-failover.enabled | true | |
| varn.resourcemanager.ha.enabled | true | - |
| yarn.resourcemanager.ha.id | rm1546335074 | |
| varn.resourcemanager.ha.rm-ids | rm1546335074.rm1546335021 | |
| varn.resourcemanager.kevtab | varn.kevtab | |
| varn.resourcemanager.max-completed-applications | 10000 | - |
| varn.resourcemanager.nm.liveness-monitor.interval-ms | 1000 | |
| varn resourcemanager nodes exclude-nath | {{CMF_CONF_DIR}}/nodes_exclude_txt | |
| varn resourcemanager nodes include-path | {{CMF_CONF_DIR}}/nodes_allow txt | |
| varn resourcemanager non-am placement-preference-with-pode-attri | ORDER NODES IN NodeInstanceType WITH compute > worker | |
| butes | | |
| yarn.resourcemanager.placement-constraints.handler | scheduler | |
| yarn.resourcemanager.principal | yarn/_HOST@YARN-Y4C.L2OV-M7VS.INT.CLDR.WORK | |
| yarn.resourcemanager.proxy-user-privileges.enabled | true | |
| yarn.resourcemanager.recovery.enabled | true | |
| yarn.resourcemanager.resource-tracker.address.rm1546335021 | coelab.cldr.work:8031 | |
| yarn.resourcemanager.resource-tracker.address.rm1546335074 | coelab.int.cldr.work:8031 | |
| yarn.resourcemanager.resource-tracker.client.thread-count | 50 | |
| yarn.resourcemanager.scheduler.address.rm1546335021 | coelab.cldr.work:8030 | |
| yarn.resourcemanager.scheduler.address.rm1546335074 | coelab.int.cldr.work:8030 | |
| yarn.resourcemanager.scheduler.class | org.apache.hadoop.yarn.server.resourcemanager.scheduler.capacity.Cap | acityScheduler |
| yarn.resourcemanager.scheduler.client.thread-count | 50 | |
| yarn.resourcemanager.scheduler.monitor.enable | true | |
| yarn.resourcemanager.scheduler.monitor.policies | org.apache.hadoop.yarn.server.resourcemanager.monitor.capacity.Propo | rtionalCapacityPr |
| yarn.resourcemanager.store.class | org.apache.hadoop.yarn.server.resourcemanager.recovery.ZKRMStateSt | tore |
| yarn.resourcemanager.webapp.address.rm1546335021 | yarn-zfv9wy-master1.yarn-y4c.l2ov-m7vs.int.cldr.work:8088 | |
| yarn.resourcemanager.webapp.address.rm1546335074 | yarn-zfv9wy-master0.yarn-y4c.l2ov-m7vs.int.cldr.work:8088 | |
| yarn.resourcemanager.webapp.cross-origin.enabled | true | |
| yarn.resourcemanager.webapp.https.address.rm1546335021 | coelab.cldr.work:8090 | |
| yarn.resourcemanager.webapp.https.address.rm1546335074 | coelab.int.cldr.work:8090 | |
| yarn.resourcemanager.webapp.spnego-keytab-file | yarn.keytab | 1 |
| yarn.resourcemanager.webapp.spnego-principal | HTTP/_HOST@YARN-Y4C.L2OV-M7VS.INT.CLDR.WORK | 1 |
| yarn.resourcemanager.work-preserving-recovery.enabled | true | |
| yarn.resourcemanager.zk-acl | sasl:yarn:cdrwa | 1 |

| Parameter | Value | |
|---|--|-----------------|
| yarn.resourcemanager.zk-address | coelab.int.cldr.work:2181,coelab.int.cldr.work:2181,coelab- master0.yarn-y4c.l2cldr.work:2181 | |
| yarn.resourcemanager.zk-timeout-ms | 60000 | |
| yarn.scheduler.capacity.multi-node-placement-enabled | true | |
| yarn.scheduler.capacity.multi-node-sorting.policy | instancetype-based | |
| yarn.scheduler.capacity.multi-node-sorting.policy.instancetype-based .class | com.cloudera.cloud.yarn.resourcemanager.scheduler.NodeInstanceType | BinPackingPolic |
| yarn.scheduler.capacity.multi-node-sorting.policy.names | instancetype-based | |
| yarn.scheduler.capacity.resource-calculator | org.apache.hadoop.yarn.util.resource.DefaultResourceCalculator | |
| yarn.scheduler.configuration.store.class | zk | |
| yarn.scheduler.increment-allocation-mb | 512 | |
| yarn.scheduler.increment-allocation-vcores | 1 | |
| yarn.scheduler.maximum-allocation-mb | 450560 | |
| yarn.scheduler.maximum-allocation-vcores | 32 | |
| yarn.scheduler.minimum-allocation-mb | 11264 | |
| yarn.scheduler.minimum-allocation-vcores | 1 | |
| yarn.service.classpath | \$HADOOP_CLIENT_CONF_DIR | |
| yarn.service.framework.path | /user/yarn/services/service-framework/7.2.13/service-dep.tar.gz | |
| yarn.webapp.api-service.enable | true | |
| yarn.webapp.custom.webservice.class | com.cloudera.cloud.yarn.resourcemanager.webapp.YarnOnCloudWebSe | rvices |
| yarn.webapp.filter-entity-list-by-user | true | |
| yarn.webapp.ui2.enable | true | |

For information about the YARN configuration properties supported by Cloudera Manager, see *Cloudera Manager* documentation.

Use the YARN REST APIs to manage applications

You can use the YARN REST APIs to submit, monitor, and stop applications.



Important: In a non-secure cluster, you must append a request with ?user.name=<user>.

Example: Get application data

• Without ?user.name=<user>:

```
curl http://localhost:19888/jobhistory/job/job_1516861688424_0001
Access denied: User null does not have permission to view job job_
1516861688424_0001
```

• With ?user.name=<user>:

```
curl http://localhost:19888/jobhistory/job/job_1516861688424_0001?user.name=hrt_1
{"job":{"submitTime":1516863297896,"startTime":1516863310110,"finishTime":1516863330610,
"id":"job_1516861688424_0001","name":"Sleepjob","gueue":"default","user":"hrt_1",
"state":"SUCCEEDED","mapsTotal":1,"mapsCompleted":1,"reducesTotal":1,"reducesCompleted":1,
"uberized":false,"diagnostics":"","avgMapTime":10387,"avgReduceTime":536,"avgShuffleTime":4727,
"avgMergeTime":27,"failedReduceAttempts":0,"killedReduceAttempts":0,"successfulReduceAttempts":1,"failedMapAttempts":0,"killedMapAttempts":1,"acls":[{"name":"mapreduce.job.acl-modify-job","value":" "}]}
```

Get an Application ID

You can use the New Application API to get an application ID, which can then be used to submit an application. For example:

```
curl -v -X POST 'http://localhost:8088/ws/v1/cluster/apps/new-application'
```

The response returns the application ID, and also includes the maximum resource capabilities available on the cluster. For example:

```
{
application-id: application_1409421698529_0012",
"maximum-resource-capability":{"memory":"8192","vCores":"32"}
}
```

Set Up an Application .json File

Before you submit an application, you must set up a .json file with the parameters required by the application. This is analogous to creating your own ApplicationMaster. The application .json file contains all of the fields you are required to submit in order to launch the application.

The following is an example of an application .json file:

```
{
    "application-id": "application_1404203615263_0001",
    "application-name":"test",
    "am-container-spec":
       "local-resources":
          "entry":
         [
            {
                "key": "AppMaster.jar",
                "value":
                ł
                   "resource": "hdfs://hdfs-namenode:9000/user/testuser/Dis
tributedShell/demo-app/AppMaster.jar",
                   "type":"FILE",
                   "visibility": "APPLICATION",
                   "size": "43004",
                   "timestamp": "1405452071209"
                }
            }
          1
       },
       "commands":
       {
          "command":"{{JAVA_HOME}}/bin/java -Xmx10m org.apache.hadoop.yar
n.applications.distributedshell.ApplicationMaster --container_memory 10 --co
ntainer_vcores 1 --num_containers 1 --priority 0 1><LOG_DIR>/AppMaster.stdou
t 2><LOG_DIR>/AppMaster.stderr"
       },
       "environment":
          "entry":
          [
                 "key": "DISTRIBUTEDSHELLSCRIPTTIMESTAMP",
                 "value": "1405459400754"
```

```
},
{
                "key": "CLASSPATH",
                "value": "{{CLASSPATH}}<CPS>./*<CPS>{{HADOOP_CONF_DIR}}<C</pre>
PS>{{HADOOP_COMMON_HOME}}/share/hadoop/common/*<CPS>{{HADOOP_COMMON_HOME}}/s
hare/hadoop/common/lib/*<CPS>{{HADOOP_HDFS_HOME}}/share/hadoop/hdfs/*<CPS>{{
HADOOP_HDFS_HOME}}/share/hadoop/hdfs/lib/*<CPS>{{HADOOP_YARN_HOME}}/share/ha
doop/yarn/*<CPS>{{HADOOP_YARN_HOME}}/share/hadoop/yarn/lib/*<CPS>./log4j.pro
perties"
              }
{
                "key": "DISTRIBUTEDSHELLSCRIPTLEN",
                "value": "6"
                 "key": "DISTRIBUTEDSHELLSCRIPTLOCATION",
                 "value": "hdfs://hdfs-namenode:9000/user/testuser/demo-app/
shellCommands"
             }
          1
       }
    },
    "unmanaged-AM":"false",
    "max-app-attempts":"2",
    "resource":
    ł
       "memory":"1024",
       "vCores":"1"
    },
    "application-type":"YARN",
    "keep-containers-across-application-attempts":"false"
  }
```

Submit an Application

You can use the Submit Application API to submit applications. For example:

```
curl -v -X POST -d @example-submit-app.json -H "Content-type: application/js
on"'http://localhost:8088/ws/v1/cluster/apps'
```

After you submit an application the response includes the following field:

HTTP/1.1 202 Accepted

The response also includes the Location field, which you can use to get the status of the application (app ID). The following is an example of a returned Location code:

```
Location: http://localhost:8088/ws/v1/cluster/apps/application_1409421698529 _0012
```

Monitor an Application

You can use the Application State API to query the application state. To return only the state of a running application, use the following command format:

```
curl 'http://localhost:8088/ws/v1/cluster/apps/application_1409421698529_001
2/state'
```

You can also use the value of the Location field (returned in the application submission response) to check the application status. For example:

```
curl -v 'http://localhost:8088/ws/v1/cluster/apps/application_1409421698529_
0012'
```

You can use the following command format to check the logs:

```
yarn logs -appOwner 'dr.who' -applicationId application_1409421698529_0012 |
less
```

Kill an Application

You can also use the Application State API to end an application by using a PUT operation to set the application state to KILLED. For example:

```
curl -v -X PUT -H 'Accept: application/json' -H 'Content-Type: application/j
son' -d '{"state": "KILLED"}' 'http://localhost:8088/ws/v1/cluster/apps/appl
ication_1409421698529_0012/state'
```

Comparison of Fair Scheduler with Capacity Scheduler

This section provides information about choosing Capacity Scheduler, its benefits, and performance improvements along with features comparison between Fair Scheduler and Capacity Scheduler.

Why one scheduler?

Cloudera Data Platform (CDP) only supports the Capacity Scheduler in the YARN clusters.

Prior to the launch of CDP, Cloudera customers used one of the two schedulers (Fair Scheduler and Capacity Scheduler) depending on which product they were using (CDH or HDP respectively).

The choice to converge to one scheduler in CDP was a hard one but ultimately rooted in our intention to reduce complexity for our customers and at the same time help focus our future investments. Over the years, both the schedulers have evolved greatly, to the point that Fair Scheduler borrowed almost all of the features from Capacity Scheduler and vice-versa. Given this, we ultimately decided to put our weight behind Capacity Scheduler for all your YARN clusters.

Those clusters that currently use the Fair scheduler must migrate to the Capacity Scheduler when moving to CDP. Cloudera provides tools, documentation, and related help for such migrations.

Benefits of Using Capacity Scheduler

The following are some of the benefits when using Capacity Scheduler:

- Integration with Ranger
- Node partitioning/labeling
- Improvements to schedule on cloud-native environments, such as better bin-packing, autoscaling support, and so on.
- Scheduling throughput improvements
 - Global Scheduling Framework
 - Lookup of multiple nodes at one time

Fore more details about Scheduling throughput improvements, see Scheduler Performance Improvements.

• Affinity/anti-affinity: run application X only on those nodes which run application Y and the other way around. Do not run application X and application Y on the same node.

For information about the currently supported features, see Supported Features.

Scheduler performance improvements

Provides information about Global scheduling feature and its test results.

Improvements brought by Global Scheduling Improvements (YARN-5139)

Before the changes of global scheduling, the YARN scheduler was under a monolithic lock, which was underperforming. Global scheduling largely improved the internal locking structure and the thread-model of how the YARN scheduler works. The scheduler can now decouple placement decisions and change the internal data structure. This can also enable to lookup multiple nodes at a time, which is used by auto-scaling and bin-packing policies on cloud. For more information, see the design and implementation notes.

Based on the simulation, the test result of using Global Scheduling feature shows:



This is a simulated environment which has 20000 nodes and 47000 running applications. For more information about these tests, see the performance report.

Performance test from YARN community

Microsoft published Hydra: a federated resource manager for data-center scale analytics (Carlo, et al) report which highlights the scalability (Deployed YARN to more than 250k nodes, which includes five large federated cluster, each of them having 50k nodes) and scheduling performance (each cluster's scheduler can make more than 40k container allocation per second) by using Capacity Scheduler. This is the largest known YARN deployment in the world.

We also saw performance numbers from other companies in the community in line with what we have tested using simulators (thousands of container allocations per second for a cluster that has thousands of nodes).

Disclaimer: The performance number discussed above is related to the size of the cluster, workloads running on the cluster, queue structure, healthiness (such as node manager, disk, and network), container churns, and so on. This typically needs fine-tuning efforts for the scheduler and other cluster parameters to reach the ideal performance. This is NOT a guaranteed number which can be achieved just by using CDP.

Feature comparison

The features of both schedulers have become similar over time. The current feature list and differences between the two schedulers is listed in the tables.

Supported Features

| Feature List | | Capacity Scheduler | Fair Scheduler | Comments |
|-----------------------|--|--------------------|----------------|---|
| Queues | Hierarchical Queues | yes | yes | |
| | Elastic Queue Capacity for better resource sharing | yes | yes | |
| | Percentage Based Resource Configuration in Queues | yes | yes | Percentages and absolute resources settings cannot be used simultaneous. |
| | Auto Queue Creation | yes | yes | |
| | User Mapping (user/group to queue mapping) | yes | yes | |
| | CLI/REST API support to manage queues | yes | yes | |
| | Move applications between queues | yes | yes | |
| | Dynamic Queue creation/ deletion/modification | yes | yes | |
| | Reservation support in queues | yes | yes | |
| Authorization | Authorization control (ACLs in Queues for submit/manage/admin) | yes | yes | |
| | Third party ACL control (Ranger) | yes | yes | |
| Application Placement | Node Labels support | yes | no | |
| | Hive placement integration | yes | yes | |
| | Node Attributes support | yes | no | |
| | Placement constraints support | yes | no | Supported constraints are limited in the current implementation. |
| | Node Locality | yes | yes | |
| | Locality Delay control | yes | yes | |
| | User limit quota management | yes | yes | |
| | AM resource quota management | yes | yes | |
| | Queue Priority | yes | no | Indirectly managed through queue weights. |
| | Maximum and Minimum allocation limit per container unit | yes | yes | |
| Scheduling | Asynchronous scheduling support | yes | yes | Implementation differs between the schedulers and should not be treated as equivalent. |

| | Multiple resource types support (CPU, Memory, GPU, and so on) | yes | yes | |
|------------------------|---|-----|-----|---|
| | Queue Ordering Policies (Fair, FIFO, and so on) | yes | yes | |
| | Multiple container assignments per heartbeat | yes | yes | |
| Preemption | Inter Queue preemption support | yes | yes | |
| | Intra Queue preemption support | yes | yes | |
| | Reservation based preemption | yes | yes | |
| | Queue Priority based preemption | yes | no | Queue weights are taken into account when preempting decisions are made. |
| Application Support | First class Concept of application | yes | yes | |
| | Application priority | yes | yes | |
| | Application timeout | yes | yes | |
| | Moving Application across queues | yes | yes | |
| | High Availability stateful application recovery | yes | yes | |

Roadmap Features

| Feature List | | Capacity Scheduler | Fair Scheduler | Comments |
|-----------------------|--|--------------------|----------------|---|
| Queues | Absolute Resource Configuration in Queues | yes | yes | Percentages and absolute resources settings cannot be usedsimultaneously. |
| Application Placement | Maximum number of applications | no | yes | Indirectly managed through AM resource quotas. |
| Scheduling | Application Size Based Fairness | no | yes | |

Migration from Fair Scheduler to Capacity Scheduler

Starting from the CDP CDP Private Cloud Base 7.1 release, Cloudera provides the fs2cs conversion utility, which is a CLI application and is a part of the YARN CLI command. This utility helps to migrate from Fair Scheduler to Capacity Scheduler.

For information about using the fs2cs conversion utility, the scheduler conversion process, and manual configurations, see Migrating Fair Scheduler to Capacity Scheduler.

Configuring and using Queue Manager REST API

You can use the Queue Manager REST APIs to automate the Queue Manager operations using the HTTP endpoints.

Limitations

These Queue Manager REST APIs are recommended to be used only for administrative purposes, and are not supported in heavily concurrent use cases.

Using the REST API

The Queue Manager REST server exposes endpoints that provide the start, stop, add, delete, change queue capacity, and change queue properties operations. For a given endpoint, the HTTP verb controls the type of operation.

Prerequisites

You must first authenticate and obtain the cookies to send a request.

- Authenticate and obtain cookie
 - Log in to Cloudera Manager and get the cookie to send a request. This generates a session cookie that must be provided with every request. If you are using an HTTP client such as Postman, you can copy the cookie value from your browser and add it as a header to your requests. You can also authenticate and obtain the cookie using the command line using cURL, as follows:

```
curl -i -k -v -c cookies.txt -u admin:admin
http://ccm_host>:7180/api/v41/clusters
```

• This command saves the resulting cookie in cookies.txt. You can use the cookie to make the requests. Run the following command to make the initial validation request.

```
curl -v -k -b cookies.txt -u <username>:<password> -H 'Content-Type: app
lication/json' -X POST -H 'referer:
http://<cm_host>:7180/cmf/clusters/Cluster%201/queue-manager/'
http://<cm_host>:7180/cmf/clusters/Cluster%201/queue-manager-api/api/
v1/environments/dev/clusters/Cluster%201/resources/scheduler/partitions/
default/queues/root.default -d '<request_body>'
```

• Secure cluster (SSL and Kerberos enabled)

If you are using a cluster secured with SSL and Kerberos, obtain the required certificates.

1. Create a directory on your machine to copy the certificates from the Queue Manager node. The following command creates the apiCerts directory.

mkdir apiCerts

2. SSH to your Queue Manager node to obtain the WebApp folder information.

cd /var/run/cloudera-scm-agent/process/

3. Copy the certificates from the Queue Manager node to the "apiCerts" directory.

```
scp -i <your_keypair>
root@<qm_host>:/var/run/cloudera-scm-agent/process/{12}-queuemanager-Q
UEUEMANAGER_WEBAPP/cm-auto-host_cert_chain.pem apiCerts/
```

4. Copy the following certificates from the Queue Manager node.

```
scp -i <your_keypair>
root@<qm_host>:/var/run/cloudera-scm-agent/process/12-queuemanager-QU
EUEMANAGER_WEBAPP/cm-auto-global_cacerts.pem apiCerts/
```

```
scp -i <your_keypair>
root@<qm_host>:/var/run/cloudera-scm-agent/process/12-queuemanager-QU
EUEMANAGER_WEBAPP/cm-auto-host_cert_chain.pem apiCerts/
scp -i <your_keypair>
root@<qm_host>:/var/run/cloudera-scm-agent/process/12-queuemanager-QUEUE
MANAGER_WEBAPP/cm-auto-host_key.pem apiCerts/
scp -i <your_keypair>
```

```
root@<qm_host>:/var/run/cloudera-scm-agent/process/12-queuemanager-QUE
UEMANAGER_WEBAPP/cm-auto-host_key.pw apiCerts/
```

5. Decrypt the certificate so that you can use it later in the cURL call.

```
openssl rsa -passin file:cm-auto-host_key.pw -in cm-auto-host_key.pem -o
ut
cm-auto-host_key_decrypted.pem
chmod 644 cm-auto-host_key_decrypted.pem
```

6. Save the cookie for the API calls.

```
curl --key cm-auto-host_key_decrypted.pem --cert cm-auto-host_cert_chain
.pem --cacert cm-auto-global_cacerts.pem -v -c cookies_ssl.txt -u admin:
admin https://<cm_host>:7183/api/v41/clusters
```

7. Make the initial validation request.

```
curl --key cm-auto-host_key_decrypted.pem --cert cm-auto-host_cert_chain
.pem --cacert cm-auto-global_cacerts.pem -v -b cookies_ssl.txt -u admin:
admin -H 'Content-Type: application/json' -X POST -H 'referer: https://<
cm_host>:7183/cmf/clusters/Cluster%201/queue-manager/' https://<cm_host>
:7183/cmf/clusters/Cluster%201/queue-manager-api/api/v1/environments/dev
/clusters/Cluster%201/resources/scheduler/partitions/default/queues/root
.default\?validate=true\&startsafemode=60 -d '<request_body>
```

• Initialization

Before using Queue Manager, you must initialize the back-end with information about the cluster. This is usually done using a POST request from the UI with information obtained from the Cloudera Manager, which you can find in various places in the Cloudera Manager UI.

The information can also be found in session storage after navigating to the Queue Manager UI. Refer your browser documentation for information about viewing session storage. For example, to view session storage in Chrome, see View Session Storage.

```
POST http://<cm_host>:7180/cmf/clusters/Cluster%201/queue-manager-api/api/
v1/environments/dev/clusters
```

```
"provisioner": "CLOUDERA_MANAGER",
"provisionerUrl": "<cm_host>:<port (7180 or if secure cluster, 7183)>",
"clusters": [
    {
        "rmUrl": <resource manager URL(s)>,
        "clusterId": <cluster id>,
        "yarnServiceName": <service name>,
        "rmRoleConfigGroup": <resource manager group name>
    }
}
```

}

Sample request

You can use a comma separated list to add multiple URLs of the Resource Manager.



Note: You must initialize the Queue Manager backend with information about the cluster whenever the Queue Manager service is restarted.

Start Queue

Run the following to start a queue.

Request URL

```
PUT
http://<cm_host>:7180/cmf/clusters/<Cluster-id>/queue-manager-api/api/v1/env
ironments/support/clusters/<Cluster-id>/resources/scheduler/partitions/defau
lt/queues/<path-to-the-queue>
```

Request Body

```
{
   "properties": [{ "name": "state", "value": "RUNNING" }],
   "message": "Started <path-to-the-queue>"
}
```

Note: In the Queue Manager UI, hover on the queue name to know the path of the queue.

Example Request

```
curl -v -X PUT -b cookie.txt --key cm-auto-host_key_decrypted.pem --cert cm-
auto-host_cert_chain.pem --cacert cm-auto-global_cacerts.pem -H "Referer: ht
tps://<cm_host>:7183/cmf/clusters/Cluster%201/queue-manager/"
```

```
my-cluster-1.my-cluster.root.hwx.site:7180/cmf/clusters/Cluster201/queue-man
ager-api/api/v1/environments/support/clusters/Cluster201/resources/scheduler
/partitions/default/queues/root.samplequeue -d @request.json
```

The above example starts the samplequeue queue placed under the root queue.



Note: You must save the Request Body content as a .json file before using this command. In the above example, the Request Body content is saved as the *request.json* file.

| Parameter | Description |
|-------------------|---------------------------------------|
| cm_host | Cloudera Manager host address |
| Cluster-id | Name of the cluster |
| path-to-the-queue | Path to the queue with the queue name |

Stop Queue

Run the following to stop a queue.

Request URL

```
PUT
http://<cm_host>:7180/cmf/clusters/<Cluster-id>/queue-manager-api/api/v1/en
vironments/support/clusters/<Cluster-id>/resources/scheduler/partitions/defa
ult/queues/<path-to-the-queue>
```

Request Body

```
{
    "properties": [{ "name": "state", "value": "STOPPED" }],
    "message": "Stopped <path-to-the-queue>"
}
```

Note: In the Queue Manager UI, hover on the queue name to know the path of the queue.

Example Request

```
curl -v -X PUT -b cookie.txt --key cm-auto-host_key_decrypted.pem --cert cm-
auto-host_cert_chain.pem --cacert cm-auto-global_cacerts.pem -H "Referer: ht
tps://<cm_host>:7183/cmf/clusters/Cluster%201/queue-manager/"
```

```
my-cluster-1.my-cluster.root.hwx.site:7180/cmf/clusters/Cluster201/queue-man
ager-api/api/v1/environments/support/clusters/Cluster201/resources/scheduler
/partitions/default/queues/root.samplequeue -d @request.json
```

The above example stops the samplequeue queue placed under the root queue.



Note: You must save the Request Body content as a .json file before using this command. In the above example, the Request Body content is saved as the *request.json* file.

| Parameter | Description |
|-------------------|---------------------------------------|
| cm_host | Cloudera Manager host address |
| Cluster-id | Name of the cluster |
| path-to-the-queue | Path to the queue with the queue name |

Add Queue

Run the following to add a queue.

Request URL

```
PUT
http://<cm_host>:7180/cmf/clusters/<Cluster-id>/queue-manager-api/api/v1/en
vironments/support/clusters/<Cluster-id>/resources/scheduler/partitions/defa
ult/queues/<path-to-the-queue>
```

Request Body

```
{
  "queuePath": "{queue-path}",
  "queueName": "{queue-name}",
  "capacity": "{queue-capacity}",
  "maximum-capacity": "{queue-maximum-capacity}",
  "siblingCapacities": [
    {
        "queuePath": "{sibling-queue-path}",
        "queueName": "{sibling-queue-name}",
        "capacity": "{sibling-queue-capacity}",
        "maximum-capacity": "{sibling-queue-maximum-capacity}",
        "maximum-capacity": "{sibling-queue-maximum-capacity}",
        "maximum-capacity": "{sibling-queue-name}",
        "gueueName": "{sibling-queue-maximum-capacity}",
        "maximum-capacity": "{sibling-queue-maximum-capacity}",
        "maximum-capacity": "{sibling-queue-maximum-capacity}",
        "maximum-capacity": "{sibling-queue-maximum-capacity}",
        "maximum-capacity": "{sibling-queue-maximum-capacity}",
        "maximum-capacity": "{sibling-queue-maximum-capacity}",
        "maximum-capacity": "{sibling-queue-maximum-capacity}",
        "
        "maximum-capacity": "{sibling-queue-maximum-capacity}",
        "maximum-capacity": "{sibling-queue-maximum-capacity}",
        "maximum-capacity": "{sibling-queue-maximum-capacity}",
        "
        "message": "Added {queue-name}"
    }
}
```

Note: The siblingCapacities parameter is required only if you are adding a sibling to an existing leaf queue. You must ensure that the total capacity of the sibling queues and the new queue must be equal to 100% of the parent queue in the Relative mode. The total allocated capacity of the sibling queues and the new queue must be less than or equal to the capacity of the parent in the Absolute mode. For information about resource allocation, see "change link" Resource allocation overview.

| Parameter | Description |
|-------------------|-------------------------------|
| cm_host | Cloudera Manager host address |
| Cluster-id | Name of the cluster |
| queuePath | Path to the queue |
| queueName | Name of the queue |
| capacity | Capacity of the queue |
| maximum-capacity | Maximum capacity of the queue |
| siblingCapacities | Capacity of the sibling queue |

Example Request

curl -v -X PUT -b cookie.txt --key cm-auto-host_key_decrypted.pem --cert cmauto-host_cert_chain.pem --cacert cm-auto-global_cacerts.pem -H "Referer: ht tps://<cm_host>:7183/cmf/clusters/Cluster%201/queue-manager/"

my-cluster-1.my-cluster.root.hwx.site:7180/cmf/clusters/Cluster201/queue-man
ager-api/api/v1/environments/support/clusters/Cluster201/resources/scheduler
/partitions/default/queues/root.samplequeue -d @request.json



Note: You must save the Request Body content as a .json file before using this command. In the above example, the Request Body content is saved as the *request.json* file.

Change Queue Capacities

Run the following to change the queue properties.

Request URL

```
PUT
http://<cm_host>:7180/cmf/clusters/<Cluster-id>/queue-manager-api/api/v1/en
vironments/support/clusters/<Cluster-id>/resources/scheduler/partitions/defa
ult/queues/<path-to-the-queue>
```

Request Body

```
{
  "properties": [
     "name": "capacity", "value": "0" },
      "name": "maximum-capacity", "value": "100" }
      "accessible-node-labels.<name-of-the-partition>.capacity":"<queue-
capacity>",
      "accessible-node-labels.<name-of-the-partition>.maximum-capacity":"
100",
      "accessible-node-labels.<name-of-the-partition>.capacity":"<queue-
capacity>",
      "accessible-node-labels.<name-of-the-partition>.maximum-capacity":"
100"
  ],
  "siblingCapacities": [
    ł
      "queuePath": "root.default",
      "queueName": "default",
      "capacity": "100",
      "maximum-capacity": "100"
      "accessible-node-labels.<name-of-the-partition>.capacity":"<queue-
capacity>",
      "accessible-node-labels.<name-of-the-partition>.maximum-capacity":"
100",
      "accessible-node-labels.<name-of-the-partition>.capacity":"<queue-
capacity>",
      "accessible-node-labels.<name-of-the-partition>.maximum-capacity":"
100"
 ],
  "message": "Changed child capacities for root"
}
```



Important:

- You can specify the capacity for a particular partition using the accessible-node-labels.<name-of-thepartition>.capacity option. The total capacity of all the queues in a given partition must be equal to 100% of the parent queue in the Relative mode. The total allocated capacity of all the queues and the must be less than or equal to the capacity of the parent in the Absolute mode.
- YARN Queue Manager does not support mixed allocation of resources. That is, some queues allocated using percentages and some queues using absolute units. Hence, you must not update the capacities in mixed mode at different levels. You must set the capacities at all levels in the same mode and that mode must match with the current Queue Manager mode.

For information about Partitions, see Configuring Partitions. For information about changing queue capacities, see Configure cluster capacity with queues.

| Parameter | Description |
|-----------|-------------|
|-----------|-------------|

| cm_host | Cloudera Manager host address |
|-----------------------|-------------------------------|
| Cluster-id | Name of the cluster |
| queuePath | Path to the queue |
| queueName | Name of the queue |
| capacity | Capacity of the queue |
| maximum-capacity | Maximum capacity of the queue |
| name-of-the-partition | Name of the partition |

Example Request

```
curl -v -X PUT -b cookie.txt --key cm-auto-host_key_decrypted.pem --cert cm-
auto-host_cert_chain.pem --cacert cm-auto-global_cacerts.pem -H "Referer: ht
tps://<cm_host>:7183/cmf/clusters/Cluster%201/queue-manager/"
```

```
my-cluster-1.my-cluster.root.hwx.site:7180/cmf/clusters/Cluster201/queue-man
ager-api/api/v1/environments/support/clusters/Cluster201/resources/scheduler
/partitions/default/queues/root.samplequeue -d @request.json
```



Note: You must save the Request Body content as a .json file before using this command. In the above example, the Request Body content is saved as the *request.json* file.

Change Queue Properties

You can configure numerous queue properties that can be included in the properties array, each with its own range of valid values.

For information about the YARN properties, see Managing and Allocating Cluster Resources using Capacity Scheduler.

Request URL

PUT

```
http://<cm_host>:7180/cmf/clusters/<Cluster-id>/queue-manager-api/api/vl/en
vironments/support/clusters/<Cluster-id>/resources/scheduler/partitions/defa
ult/queues/<path-to-the-queue>
```

Request Body

```
"properties": [{ "name": "{name-of-the-property}", "value": "{value}" }],
"message": "Changed properties of {path-of-the-queue}"
}
```

| Parameter | Description |
|----------------------|-------------------------------|
| cm_host | Cloudera Manager host address |
| Cluster-id | Name of the cluster |
| path-of-the-queue | Path to the queue |
| name-of-the-property | Name of the property |
| value | Value of the YARN property |

Example Request Body

```
{
```

"message": "Changed properties of root.samplequeue"

"properties": [{ "name": "maximum-applications", "value": "1" }],



Note: You can change the queue capacity and configure queue capacity using the same request body.

Example Request

```
curl -v -X PUT -b cookie.txt --key cm-auto-host_key_decrypted.pem --cert cm-
auto-host_cert_chain.pem --cacert cm-auto-global_cacerts.pem -H "Referer: ht
tps://<cm_host>:7183/cmf/clusters/Cluster%201/queue-manager/"
```

```
my-cluster-1.my-cluster.root.hwx.site:7180/cmf/clusters/Cluster201/queue-man
ager-api/api/v1/environments/support/clusters/Cluster201/resources/scheduler
/partitions/default/queues/root.samplequeue -d @request.json
```



Note: You must save the Request Body content as a .json file before using this command. In the above example, the Request Body content is saved as the *request.json* file.

Delete Queue

You must set the capacity of the queue to zero before you delete a queue.

For information about changing queue capacity using the API, see Change Queue Capacities.

The delete queue requests cannot have a body, but the version message can be passed as a query string parameter as shown in the Request URL.

Request URL

```
DELETE
```

```
http://<cm_host>:7180/cmf/clusters/<Cluster-id>/queue-manager-api/api/vl/en
vironments/support/clusters/<Cluster-id>/resources/scheduler/partitions/defa
ult/queues/<path-to-the-queue>
```

| Parameter | Description |
|-------------------|-------------------------------|
| cm_host | Cloudera Manager host address |
| Cluster-id | Name of the cluster |
| path-of-the-queue | Path to the queue |

Example Request

curl -v -X DELETE -b cookie.txt --key cm-auto-host_key_decrypted.pem --cert cm-auto-host_cert_chain.pem --cacert cm-auto-global_cacerts.pem -H "Referer: https://<cm_host>:7183/cmf/clusters/Cluster%201/queue-manager/"

my-cluster-1.my-cluster.root.hwx.site:7180/cmf/clusters/Cluster201/queuemanager-api/api/v1/environments/support/clusters/Cluster201/resources/schedu ler/partitions/default/queues/root.a?message=Deleted%20root.a