

Cloudera Runtime 7.3.2

Streams Replication Manager Reference

Date published: 2019-08-22

Date modified: 2026-03-31

The Cloudera logo is displayed in a bold, orange, sans-serif font. The word "CLOUDERA" is written in all caps, with the letter 'E' featuring a unique design consisting of three horizontal bars.

<https://docs.cloudera.com/>

Legal Notice

© Cloudera Inc. 2026. All rights reserved.

The documentation is and contains Cloudera proprietary information protected by copyright and other intellectual property rights. No license under copyright or any other intellectual property right is granted herein.

Unless otherwise noted, scripts and sample code are licensed under the Apache License, Version 2.0.

Copyright information for Cloudera software may be found within the documentation accompanying each component in a particular release.

Cloudera software includes software from various open source or other third party projects, and may be released under the Apache Software License 2.0 (“ASLv2”), the Affero General Public License version 3 (AGPLv3), or other license terms. Other software included may be released under the terms of alternative open source licenses. Please review the license and notice files accompanying the software for additional licensing information.

Please visit the Cloudera software product page for more information on Cloudera software. For more information on Cloudera support services, please visit either the Support or Sales page. Feel free to contact us directly to discuss your specific needs.

Cloudera reserves the right to change any products at any time, and without notice. Cloudera assumes no responsibility nor liability arising from the use of products, except as expressly agreed to in writing by Cloudera.

Cloudera, Cloudera Altus, HUE, Impala, Cloudera Impala, and other Cloudera marks are registered or unregistered trademarks in the United States and other countries. All other trademarks are the property of their respective owners.

Disclaimer: EXCEPT AS EXPRESSLY PROVIDED IN A WRITTEN AGREEMENT WITH CLOUDERA, CLOUDERA DOES NOT MAKE NOR GIVE ANY REPRESENTATION, WARRANTY, NOR COVENANT OF ANY KIND, WHETHER EXPRESS OR IMPLIED, IN CONNECTION WITH CLOUDERA TECHNOLOGY OR RELATED SUPPORT PROVIDED IN CONNECTION THEREWITH. CLOUDERA DOES NOT WARRANT THAT CLOUDERA PRODUCTS NOR SOFTWARE WILL OPERATE UNINTERRUPTED NOR THAT IT WILL BE FREE FROM DEFECTS NOR ERRORS, THAT IT WILL PROTECT YOUR DATA FROM LOSS, CORRUPTION NOR UNAVAILABILITY, NOR THAT IT WILL MEET ALL OF CUSTOMER’S BUSINESS REQUIREMENTS. WITHOUT LIMITING THE FOREGOING, AND TO THE MAXIMUM EXTENT PERMITTED BY APPLICABLE LAW, CLOUDERA EXPRESSLY DISCLAIMS ANY AND ALL IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO IMPLIED WARRANTIES OF MERCHANTABILITY, QUALITY, NON-INFRINGEMENT, TITLE, AND FITNESS FOR A PARTICULAR PURPOSE AND ANY REPRESENTATION, WARRANTY, OR COVENANT BASED ON COURSE OF DEALING OR USAGE IN TRADE.

Contents

srm-control Options Reference.....	4
Configuration Properties Reference for Properties not Available in Cloudera Manager.....	4
Kafka credentials property reference.....	6
Streams Replication Manager Service data traffic reference.....	8

srm-control Options Reference

A collection of all options and their descriptions for the srm-control command line tool.

Table 1: Topics and groups subcommand properties

Options	Description
-h, --help	Shows the help message.
--source	Specifies the source cluster
--target	Specifies the target cluster
--config	Specifies the Streams Replication Manager configuration file to use.
--add	Specifies topics or groups to add to the allowlist
--remove	Specifies topics or groups to remove from the allowlist
--add-blacklist	Specifies topics or groups to add to the denylist
--remove-blacklist	Specifies topics or groups to remove from the denylist
--list	Lists current allowlist and denylist
--bootstrap-servers	Specifies the bootstraps servers
--producer-props	Specifies producer configuration properties
--consumer-props	Specifies consumer configuration properties
--props	Specifies client configuration properties

Table 2: Offsets subcommand properties

Option	Description
-h, --help	Shows the help message.
--source	Specifies the source cluster
--target	Specifies the target cluster
--config	Specifies the Streams Replication Manager configuration file to use.
--export	Export translated offsets
--group	Specifies the groups translated offsets should be exported for
--bootstrap-servers	Specifies the bootstraps servers
--props	Specifies client configuration properties

Configuration Properties Reference for Properties not Available in Cloudera Manager

A collection of Streams Replication Manager configuration properties not available in Cloudera Manager

The following table lists all Streams Replication Manager specific configuration properties that are not available directly for configuration via Cloudera Manager.

Property	Default Value	Description
checkpoints.topic.replication.factor	3	Replication factor used for internal checkpoints topics.
emit.checkpoints.enabled	true	Enables periodic emission of consumer offset information.
emit.heartbeats.enabled	true	Enables periodic emission of heartbeats.
emit.heartbeats.interval.seconds	5 (seconds)	The interval at which Streams Replication Manager emits heartbeats.
heartbeats.topic.replication.factor	3	Replication factor used for internal heartbeat topics.
offset-syncs.topic.replication.factor	3	Replication factor used for internal offset-syncs topics.
refresh.groups.enabled	true	Enables a periodical check for new consumer groups on source clusters.
refresh.topics.enabled	true	Enables a periodical check for new topics on source clusters.
replication.factor	2	Replication factor used for remote topics.
replication.policy.class	org.apache.kafka.connect.mirror.DefaultReplicationPolicy	Replication policy to use. Use this property to set a custom replication policy. If you want to enable prefixless replication, use the Enable Prefixless Replication property instead. Enable Prefixless Replication is found in Cloudera Manager Streams Replication Manager Configuration. For more information, see <i>Enabling prefixless replication</i> .
sync.topic.configs.enabled	true	Enables the monitoring of the source cluster for configuration changes.
config.properties.exclude	follower\,replication\,throttled\,replicas, leader\,replication\,throttled\,replicas, message\,timestamp\,difference\,max\,ms, message\,timestamp\,type, unclean\,leader\,election\,enable, min\,insync\,replicas	A list of topic configuration properties or regexes that must not be replicated.
use.defaults.from	target	Determines whether the source cluster or the target cluster default values are used when syncing topic configurations that have default values.
replication.records.lag.calc.enabled	true	Controls whether the replication-records-lag metric is calculated. This metric provides information regarding the replication lag based on offsets. The metric is available both on the cluster and the topic level. The calculation of this metric might add latency to replications and impact Streams Replication Manager performance. If you are experiencing performance issues, you can try setting this property to false to disable the calculation of replication-records-lag. Alternatively, you can try fine-tuning how Streams Replication Manager calculates replication-records-lag with the replication.records.lag.calc.period.ms and replication.records.lag.end.offset.timeout.ms properties.

Property	Default Value	Description
replication.records.lag.calc.period.ms	0	Controls how frequently Streams Replication Manager calculates the replication-records-lag metric. The default value of 0 means that the metric is calculated continuously. Cloudera recommends configuring this property to 15000 ms (15 seconds) or higher if you are experiencing issues related to the calculation of replication-records-lag. A calculation frequency of 15 seconds or more results in the metric being available for consumption without any significant impact on Streams Replication Manager performance.
replication.records.lag.end.offset.timeout.ms	6000	Specifies the Kafka end offset timeout value used for calculating the replication-records-lag metric. Setting this property to a lower value than the default 6000 ms (1 minute) might reduce latency in calculating replication-records-lag, however, replication-records-lag calculation might fail. A value higher than the default can help avoid metric calculation failures, but might increase replication latency and lower Streams Replication Manager performance.
srm.internal.topic.exclude.enable	true	Enables automatically adding the internal Streams Replication Manager topic patterns to the replication deny list. If it is set to false, you need to add Streams Replication Manager internal topics to the deny list.
metrics.topic.creation.for.possible.flows.enabled	true	Determines whether the Streams Replication Manager Service creates srm-metrics topics for all possible replication flows eagerly. When set to false, only the Driver creates the topics.

Related Information

[Enabling prefixless replication](#)

Kafka credentials property reference

A Kafka credential allows services and Cloudera tools to securely connect to Kafka clusters that are external to a particular Cloudera Manager instance. Review the Kafka credentials property reference to better understand what options you have when configuring and setting up a Kafka credential.

Name

Description

Specifies the name of the Kafka credential. For Streams Replication Manager, the name you specify here is equivalent to the cluster alias. As a result, this name is used to refer to the cluster that the credential defines when configuring Streams Replication Manager properties and when using the srm-control tool. Cloudera recommends that you specify unique and easily identifiable names.

Bootstrap servers

Description

Specifies the addresses of the Kafka brokers. Add a comma-separated list of host and port pairs. The host can be specified as an IP address or an FQDN.

Example

```
my-kafka-cluster-host-1.com:9093, my-kafka-cluster-host-2.com:9093
```

JAAS secret [1-3]

Description

There are three JAAS Secret properties, numbered 1-3. All three properties can be used to specify sensitive JAAS configuration values. Values set in these properties can be referenced with placeholders in the JAAS configuration you add to the JAAS template property.

JAAS template

Description

Specifies the JAAS configuration that Streams Replication Manager uses when connecting to this cluster. The configuration you add to this property can contain placeholders. These placeholders can be used to hide sensitive information. The property accepts and resolves the following placeholders:

- `##JAAS_SECRET_1##`
Used to refer to the value set in the JAAS Secret 1 property.
- `##JAAS_SECRET_2##`
Used to refer to the value set in the JAAS Secret 2 property.
- `##JAAS_SECRET_3##`
Used to refer to the value set in the JAAS Secret 3 property.

Example

```
org.apache.kafka.common.security.plain.PlainLoginModule required username="##JAAS_SECRET_1##" password="##JAAS_SECRET_2##";
```

In this example `##JAAS_SECRET_1##` and `##JAAS_SECRET_2##` are used to hide sensitive information. The values of the username and password are defined in the JAAS Secret 1 and JAAS Secret 2 properties.

If for example the JAAS Secret 1 and JAAS Secret 2 properties were set to “username” and “password”, the resolved JAAS configuration would be the following:

```
org.apache.kafka.common.security.plain.PlainLoginModule required username="username" password="password";
```

Kerberos Service Name

Description

Specifies the name of the Kafka kerberos principal. Only required if the SASL Mechanism property is set to GSSAPI.

Key Password

Description

Specifies the password used to access the keys stored in the keystore configured in the Keystore Path property.

Keystore Password

Description

Specifies the password used to access the keystore configured in the Keystore Path property.

Keystore Path

Description

Specifies the path to the keystore containing the authorized client’s certificates or keys

Keystore Type

Description

Specifies the type of the keystore configured in the Keystore Path property

SASL Mechanism

Description

Specifies the SASL mechanism used for authentication by the Kafka cluster that the client is connecting to.

Accepted values

- GSSAPI
- PLAIN
- SCRAM-SHA-256
- SCRAM-SHA-512
- OAUTHBEARER

Security Protocol

Description

Specifies the security protocol used by the Kafka cluster that the client is connecting to.

Accepted values

- PLAINTEXT
- SSL
- SASL_PLAINTEXT
- SASL_SSL

Truststore Password

Description

Specifies the password used to access the truststore specified in the Truststore Path property

Truststore Path

Description

Specifies the path to the truststore containing the certificates or keys belonging to the Kafka cluster that the client is connecting to.

Truststore Type

Description

Specifies the type of the truststore configured in the Truststore Path property.

Streams Replication Manager Service data traffic reference

The Streams Replication Manager Service generates data traffic when it collects replication related metrics. Data traffic is generated between the Streams Replication Manager Service and its target Kafka cluster. Additionally, if Remote Querying is set up, data traffic is also generated between different Streams Replication Manager Services that are remote to each other. Review these examples to gain a better understanding of how much data traffic you should expect in your deployment.

Data transferred between the Streams Replication Manager Service and Kafka

The Streams Replication Manager service generates data traffic between itself and its target Kafka cluster. This data traffic is generated as a result of the Streams Replication Manager Service collecting the raw metrics from the target Kafka cluster. In the case of:

- A single replication.
- A single replicated topic with 1000 partitions and 100 messages published per second.
- A single consumer group.

The amount of data traffic generated is approximately 280 kB per second.

Data transferred between Streams Replication Manager Services by Remote Querying

When Remote Querying is enabled, the Streams Replication Manager Service acting as the designated monitoring gateway generates additional data traffic. This data traffic is generated as a result of the gateway communicating with other, remote Streams Replication Manager Services and receiving data on remote replications. In the case of:

- A single replication flow.
- A single replicated topic with 1000 partitions.
- A single consumer group.
- One hour retention time set for the Streams application.

The maximum amount of data traffic generated by Remote Querying (the data returned by other Streams Replication Manager Services) is around 70 kB.