

## Deploying an Edge Flow Manager Cluster

Date published: 2019-04-15

Date modified: 2025-02-28



# Legal Notice

© Cloudera Inc. 2025. All rights reserved.

The documentation is and contains Cloudera proprietary information protected by copyright and other intellectual property rights. No license under copyright or any other intellectual property right is granted herein.

Unless otherwise noted, scripts and sample code are licensed under the Apache License, Version 2.0.

Copyright information for Cloudera software may be found within the documentation accompanying each component in a particular release.

Cloudera software includes software from various open source or other third party projects, and may be released under the Apache Software License 2.0 (“ASLv2”), the Affero General Public License version 3 (AGPLv3), or other license terms. Other software included may be released under the terms of alternative open source licenses. Please review the license and notice files accompanying the software for additional licensing information.

Please visit the Cloudera software product page for more information on Cloudera software. For more information on Cloudera support services, please visit either the Support or Sales page. Feel free to contact us directly to discuss your specific needs.

Cloudera reserves the right to change any products at any time, and without notice. Cloudera assumes no responsibility nor liability arising from the use of products, except as expressly agreed to in writing by Cloudera.

Cloudera, Cloudera Altus, HUE, Impala, Cloudera Impala, and other Cloudera marks are registered or unregistered trademarks in the United States and other countries. All other trademarks are the property of their respective owners.

Disclaimer: EXCEPT AS EXPRESSLY PROVIDED IN A WRITTEN AGREEMENT WITH CLOUDERA, CLOUDERA DOES NOT MAKE NOR GIVE ANY REPRESENTATION, WARRANTY, NOR COVENANT OF ANY KIND, WHETHER EXPRESS OR IMPLIED, IN CONNECTION WITH CLOUDERA TECHNOLOGY OR RELATED SUPPORT PROVIDED IN CONNECTION THEREWITH. CLOUDERA DOES NOT WARRANT THAT CLOUDERA PRODUCTS NOR SOFTWARE WILL OPERATE UNINTERRUPTED NOR THAT IT WILL BE FREE FROM DEFECTS NOR ERRORS, THAT IT WILL PROTECT YOUR DATA FROM LOSS, CORRUPTION NOR UNAVAILABILITY, NOR THAT IT WILL MEET ALL OF CUSTOMER’S BUSINESS REQUIREMENTS. WITHOUT LIMITING THE FOREGOING, AND TO THE MAXIMUM EXTENT PERMITTED BY APPLICABLE LAW, CLOUDERA EXPRESSLY DISCLAIMS ANY AND ALL IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO IMPLIED WARRANTIES OF MERCHANTABILITY, QUALITY, NON-INFRINGEMENT, TITLE, AND FITNESS FOR A PARTICULAR PURPOSE AND ANY REPRESENTATION, WARRANTY, OR COVENANT BASED ON COURSE OF DEALING OR USAGE IN TRADE.

# Contents

<b>Deploying an Edge Flow Manager cluster.....</b>	<b>4</b>
Edge Flow Manager cluster database setup.....	4
Edge Flow Manager cluster configuration.....	4
Edge Flow Manager cluster high availability.....	5

## Deploying an Edge Flow Manager cluster

Learn how to deploy an Edge Flow Manager cluster and the requirements to do so including supported number of nodes, supported databases, load balancer, and MiNiFi agents.

The Edge Flow Manager server component of Cloudera Edge Management supports clustered deployments for horizontal scalability and high availability. An EFM cluster deployment requires the following:

- Three or more Edge Flow Manager nodes
- Two-node clusters are not supported.
- A shared and external Edge Flow Manager database (MySQL, MariaDB, or PostgreSQL)
- An Edge Flow Manager load balancer for Web UI users

You can use any load balancer of your choice, provided it can proxy HTTP(s) traffic and can be configured as described in this document.

- MiNiFi agents that forward client requests to one of the Edge Flow Manager cluster nodes

In addition to communicating with the external, centralized, and shared Edge Flow Manager database, Edge Flow Manager cluster members also communicate with each other to establish ephemeral state, such as distributed locks and caches, within the cluster. Due to this, each Edge Flow Manager node must have network connectivity to every other cluster member.

### Edge Flow Manager cluster database setup

Before you first run or launch the Edge Flow Manager cluster, you must learn how to install and configure MySQL, MariaDB, or PostgreSQL.

For more information, see *Installing Databases*.

You can use an existing external database of a single and standalone Edge Flow Manager instance for the cluster deployment. None of the existing data will be lost.

However, you cannot use an H2 database of a standalone Edge Flow Manager instance and you must start over with an external database. When moving from H2 to MySQL, MariaDB, or PostgreSQL, prior to stopping the standalone instance, export the existing flows from the Edge Flow Manager Flow Designer and import into the cluster to avoid data loss. For more information on exporting and importing flows, see the [REST API Reference](#).

#### Related Information

[Installing databases for Edge Flow Manager](#)

### Edge Flow Manager cluster configuration

Learn how to configure every Edge Flow Manager cluster member to make it part of the same cluster.

You can find the cluster configuration in the `efm.properties` file located in the `conf` directory of the Edge Flow Manager installation. The following is an example cluster configuration:

```
# Web Server Properties
# address: the hostname or ip address of the interface to bind to; to bind
# to all, use 0.0.0.0
efm.server.address=10.0.0.1
efm.server.port=10090
efm.server.servlet.contextPath=/efm
efm.cluster.enabled=true
# Database Properties
efm.db.url=jdbc:mysql://database.example.com:3306/efm
efm.db.driverClass=com.mysql.cj.jdbc.Driver
```

```
efm.db.username=efm
efm.db.password=efmPassword
efm.db.maxConnections=50
efm.db.sqlDebug=false
```



**Note:** Except for the node-specific configurations, such as `efm.server.address` and `efm.cluster.address`, which can be a hostname or IP address, all other configurations must match for all nodes in the cluster. It is especially important that the nodes use the same database URL (`efm.db.url`), and the same list of cluster members (`efm.infinispan.jgroups[tcping.initial_hosts]`). If these values do not match on all cluster nodes, the cluster fails on startup.

## Cluster node discovery

Cluster node discovery allows you to configure multiple node discovery strategies to establish an Edge Flow Manager cluster, tailored to different deployment environments.

You have to define the `efm.infinispan.environment` property with the name of the environment where Edge Flow Manager is deployed. The default value is `tcp`, and the supported values are `tcp`, `tcp-fixed`, and `kubernetes`.

Here are the specifics for each environment setting:

### tcp

TCP discovery uses IP multicast to discover the initial membership, eliminating the need for manual configuration on each node. This is the default setting.

Property required: `efm.infinispan.environment=tcp`

### tcp-fixed

You have to provide a static list of host:port combinations for all nodes.

Properties required:

- `efm.infinispan.environment=tcp-fixed`
- `efm.infinispan.jgroups[tcping.initial_hosts]`

Example value: `localhost[7801],localhost[7802],localhost[7803]`



**Note:** Port numbers have to match the `efm.infinispan.jgroups[bind.port.jgroups.tcp.port]` startup settings where Infinispan is running. The default port is 7800.

### kubernetes

This strategy is designed to automatically discover pods based on namespace and label filtering.

Properties required:

- `efm.infinispan.environment=kubernetes`
- `efm.infinispan.jgroups[kubeping.namespace]`

Example value: `cem-namespace`

- `efm.infinispan.jgroups[kubeping.labels]`

Example value: `app=efm`



**Note:**

Setting up labels and namespaces in Kubernetes is the responsibility of the user.

## Edge Flow Manager cluster high availability

Learn why you are able to operate in an Edge Flow Manager cluster with high availability.

In a clustered mode, Edge Flow Manager is highly available.

Even if individual nodes are stopped the cluster can continue operation. Nodes can stop or fail due to a variety of reasons, such as routine maintenance, loss of network connectivity, or underlying physical server host failure. By default, an Edge Flow Manager cluster can continue operating with up to two nodes down. If the failed nodes are restored, the cluster reforms. Note that any load that was served by a failed node is shifted to other cluster nodes. Hence capacity may fall if all nodes in the cluster were optimally utilized with regards to resources including network, CPU, memory, and disk.