

Cloudera Flow Management 1.1.0

Upgrading Cloudera Flow Management

Date published: 2019-06-26

Date modified: 2020-05-21

The Cloudera logo is displayed in a bold, orange, sans-serif font. The word "CLOUDERA" is written in all caps, with a stylized 'E' that has three horizontal bars.

<https://docs.cloudera.com/>

Legal Notice

© Cloudera Inc. 2024. All rights reserved.

The documentation is and contains Cloudera proprietary information protected by copyright and other intellectual property rights. No license under copyright or any other intellectual property right is granted herein.

Unless otherwise noted, scripts and sample code are licensed under the Apache License, Version 2.0.

Copyright information for Cloudera software may be found within the documentation accompanying each component in a particular release.

Cloudera software includes software from various open source or other third party projects, and may be released under the Apache Software License 2.0 (“ASLv2”), the Affero General Public License version 3 (AGPLv3), or other license terms. Other software included may be released under the terms of alternative open source licenses. Please review the license and notice files accompanying the software for additional licensing information.

Please visit the Cloudera software product page for more information on Cloudera software. For more information on Cloudera support services, please visit either the Support or Sales page. Feel free to contact us directly to discuss your specific needs.

Cloudera reserves the right to change any products at any time, and without notice. Cloudera assumes no responsibility nor liability arising from the use of products, except as expressly agreed to in writing by Cloudera.

Cloudera, Cloudera Altus, HUE, Impala, Cloudera Impala, and other Cloudera marks are registered or unregistered trademarks in the United States and other countries. All other trademarks are the property of their respective owners.

Disclaimer: EXCEPT AS EXPRESSLY PROVIDED IN A WRITTEN AGREEMENT WITH CLOUDERA, CLOUDERA DOES NOT MAKE NOR GIVE ANY REPRESENTATION, WARRANTY, NOR COVENANT OF ANY KIND, WHETHER EXPRESS OR IMPLIED, IN CONNECTION WITH CLOUDERA TECHNOLOGY OR RELATED SUPPORT PROVIDED IN CONNECTION THEREWITH. CLOUDERA DOES NOT WARRANT THAT CLOUDERA PRODUCTS NOR SOFTWARE WILL OPERATE UNINTERRUPTED NOR THAT IT WILL BE FREE FROM DEFECTS NOR ERRORS, THAT IT WILL PROTECT YOUR DATA FROM LOSS, CORRUPTION NOR UNAVAILABILITY, NOR THAT IT WILL MEET ALL OF CUSTOMER’S BUSINESS REQUIREMENTS. WITHOUT LIMITING THE FOREGOING, AND TO THE MAXIMUM EXTENT PERMITTED BY APPLICABLE LAW, CLOUDERA EXPRESSLY DISCLAIMS ANY AND ALL IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO IMPLIED WARRANTIES OF MERCHANTABILITY, QUALITY, NON-INFRINGEMENT, TITLE, AND FITNESS FOR A PARTICULAR PURPOSE AND ANY REPRESENTATION, WARRANTY, OR COVENANT BASED ON COURSE OF DEALING OR USAGE IN TRADE.

Contents

Upgrading from CFM 1.0.1.....	4
Upgrading from CFM 1.0.0.....	4

Upgrading from CFM 1.0.1

To upgrade from CFM 1.0.1 to CFM 1.1.0, you must stop the CFM services, update the CSD files, restart the SCM Server, activate the new CFM parcel, and then restart your CFM services.

Before you begin

Cloudera recommends that you upgrade from CFM version 1.0.1 to 1.1.0.

However, if you must upgrade directly from CFM version 1.0.0 to 1.1.0, see *Upgrading from CFM 1.0.0*.

Procedure

1. Stop NiFi, NiFi Registry, and NIFI CA Service in this order.
2. Delete the old CSD files.
3. Download the new CSD files.

The default CSD location is `/opt/cloudera/csd`, but you can configure that location from Cloudera Manager Administration | Settings | Local Descriptor Repository Path.

Ensure that you maintain the appropriate file ownership and access attributes and SELinux permissions if needed.

4. Download the new CFM parcel and .sha checksum file appropriate for your operating system.

The default parcel location is `/opt/cloudera/parcel-repo/`.

Ensure that you maintain the appropriate file ownership and access attributes and SELinux permissions if needed.

5. Restart the `cloudera-scm-server` service:

```
service cloudera-scm-server restart
```

6. In Cloudera Manager, from the **Parcels** page, distribute and activate the CFM 1.1.0 parcel.
After clicking Activate, the Activate CFM 1.1.0.0 on <cluster-name> pop-up displays. Click Activate Only, and then OK.
7. Restart the NiFi CA Service, NiFi Registry and NiFi, and deploy the client configurations.
8. Optionally, to clean up, remove the 1.0.1.0 parcels from the host.
 - a) From the Parcel menu, go to the CFM 1.0.1.0 parcel.
 - b) Select Remove From Host.
 - c) Select Delete.

Related Information

[Upgrading from CFM 1.0.0](#)

Upgrading from CFM 1.0.0

To upgrade from CFM 1.0.0 to CFM 1.1.0, you must make note of and update some security password values, update the CSD files, restart the SCM Server, deactivate your old parcel and activate the new CFM parcel, and then restart your CFM services.

Before you begin

If you plan to upgrade from CFM version 1.0.0 to 1.1.0, Cloudera recommends that you first upgrade to CFM 1.0.1 and then to CFM 1.1.0. However, if you must upgrade directly from CFM version 1.0.0 to 1.1.0, follow the steps here.

Procedure

1. Stop NiFi, NiFi Registry, and NIFI CA Service in this order.
2. Delete the old CSD files.
3. Download the new CSD files.

The default CSD location is `/opt/cloudera/csd`, but you can configure that location from Cloudera Manager Administration | Settings | Local Descriptor Repository Path.

Ensure that you maintain the appropriate file ownership and access attributes and SELinux permissions if needed.

4. Download the new CFM parcel and .sha checksum file appropriate for your operating system.

The default parcel location is `/opt/cloudera/parcel-repo/`.

Ensure that you maintain the appropriate file ownership and access attributes and SELinux permissions if needed.

5. Get the `nifi.sensitive.props.key` value from one of the NiFi nodes you have installed:

```
cd /var/run/cloudera-scm-agent/process/ \
&& find . -name config.zip \
| grep "NIFI_NODE" \
| cut -c 3- \
| sort -n \
| tail -1 \
| xargs unzip -p \
| grep -A1 "<name>random.nifi.sensitive.props.key" \
| grep -Po "(?<=<value>)[^<]+"
```

6. Remove `flow.xml.gz` from all nodes except the one from which you obtained the `nifi.sensitive.props.key` value. The `var/lib/nifi/` path is the default location for `flow.xml.gz`, but file location is configurable using the `nifi.working.directory` property in the NiFi configuration file.
7. In Cloudera Manager, select the cluster, then select NiFi from drop down, and then select the Configuration tab. Then use the search box to find the Sensitive Properties Key value. Copy the sensitive properties key value that you got from step 5 and paste into this box. The minimum length is 12 digits.
8. Set the following additional NiFi passwords to randomly generated values:
 - `nifi.master.key.password`
 - `nifi.security.truststorePasswd`
 - `nifi.security.keystorePasswd`
 - `nifi.security.keyPasswd`
9. Update the following NiFi Registry configurations with random values for the following fields:
 - `nifi.registry.master.key.password`
 - `nifi.registry.security.truststorePasswd`
 - `nifi.registry.security.keyPasswd`
 - `nifi.registry.security.keystorePasswd`

You must use the same value for `nifi.registry.security.keyPasswd` and `nifi.registry.security.keystorePasswd`.

10. Restart the `cloudera-scm-server` service:

```
service cloudera-scm-server restart
```

11. In Cloudera Manager, from the **Parcels** page, distribute and activate the CFM 1.1.0 parcel. After clicking Activate, the Activate CFM 1.1.0.0 on `<cluster-name>` pop-up displays. Click Activate Only, and then OK.
12. Restart the NiFi CA Service, NiFi Registry and NiFi, and deploy the client configurations.

- 13.** Optionally, to clean up, remove the old parcels from the host.
- a) From the Parcel menu, go to the CFM 1.0.0.0 parcel.
 - b) Select Remove From Host.
 - c) Select Delete.