

Release Notes

Date published: 2024-06-11

Date modified: 2025-07-14



Legal Notice

© Cloudera Inc. 2025. All rights reserved.

The documentation is and contains Cloudera proprietary information protected by copyright and other intellectual property rights. No license under copyright or any other intellectual property right is granted herein.

Unless otherwise noted, scripts and sample code are licensed under the Apache License, Version 2.0.

Copyright information for Cloudera software may be found within the documentation accompanying each component in a particular release.

Cloudera software includes software from various open source or other third party projects, and may be released under the Apache Software License 2.0 (“ASLv2”), the Affero General Public License version 3 (AGPLv3), or other license terms. Other software included may be released under the terms of alternative open source licenses. Please review the license and notice files accompanying the software for additional licensing information.

Please visit the Cloudera software product page for more information on Cloudera software. For more information on Cloudera support services, please visit either the Support or Sales page. Feel free to contact us directly to discuss your specific needs.

Cloudera reserves the right to change any products at any time, and without notice. Cloudera assumes no responsibility nor liability arising from the use of products, except as expressly agreed to in writing by Cloudera.

Cloudera, Cloudera Altus, HUE, Impala, Cloudera Impala, and other Cloudera marks are registered or unregistered trademarks in the United States and other countries. All other trademarks are the property of their respective owners.

Disclaimer: EXCEPT AS EXPRESSLY PROVIDED IN A WRITTEN AGREEMENT WITH CLOUDERA, CLOUDERA DOES NOT MAKE NOR GIVE ANY REPRESENTATION, WARRANTY, NOR COVENANT OF ANY KIND, WHETHER EXPRESS OR IMPLIED, IN CONNECTION WITH CLOUDERA TECHNOLOGY OR RELATED SUPPORT PROVIDED IN CONNECTION THEREWITH. CLOUDERA DOES NOT WARRANT THAT CLOUDERA PRODUCTS NOR SOFTWARE WILL OPERATE UNINTERRUPTED NOR THAT IT WILL BE FREE FROM DEFECTS NOR ERRORS, THAT IT WILL PROTECT YOUR DATA FROM LOSS, CORRUPTION NOR UNAVAILABILITY, NOR THAT IT WILL MEET ALL OF CUSTOMER’S BUSINESS REQUIREMENTS. WITHOUT LIMITING THE FOREGOING, AND TO THE MAXIMUM EXTENT PERMITTED BY APPLICABLE LAW, CLOUDERA EXPRESSLY DISCLAIMS ANY AND ALL IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO IMPLIED WARRANTIES OF MERCHANTABILITY, QUALITY, NON-INFRINGEMENT, TITLE, AND FITNESS FOR A PARTICULAR PURPOSE AND ANY REPRESENTATION, WARRANTY, OR COVENANT BASED ON COURSE OF DEALING OR USAGE IN TRADE.

Contents

- Release notes.....4**
 - What's New.....4
 - Fixed Issues.....5
 - Known Issues.....5
 - Unsupported features.....5
 - Deprecations and removals.....6
- Component versions..... 6**
- System requirements..... 7**
- Kafka Connect plugins.....8**

Release notes

Learn about the new features, improvements, known and fixed issues, limitations, unsupported features, as well as deprecations and removals in this release of Cloudera Streams Messaging - Kubernetes Operator.

What's New

Learn about the new features and notable changes in this release.

Cloudera Surveyor for Apache Kafka

Cloudera Surveyor is a standalone application that allows you to efficiently monitor and manage your Kafka clusters through a graphical user interface. It offers insights into cluster health and performance, enabling you to oversee brokers, topics, and consumer groups. Additionally, it supports essential Kafka management actions, streamlining cluster administration.

Cloudera Surveyor is a new component within the Cloudera ecosystem. Unlike other components in Cloudera Streams Messaging - Kubernetes Operator, which are based on open source projects, Cloudera Surveyor is proprietary software developed by Cloudera.

It is compatible with any Kafka distribution that provides an API compatible with Apache Kafka 2.4.1 or higher. This includes Kafka clusters deployed with the Strimzi Cluster Operator in Cloudera Streams Messaging - Kubernetes Operator, Kafka clusters running in Cloudera on premises and Cloudera on cloud, as well as third-party Kafka distributions.

Learn more:

- [Cloudera Surveyor Overview](#)
- [Installing Cloudera Surveyor](#)
- [Cloudera Surveyor Configuration](#)
- [Cloudera Surveyor Security](#)

Configurable allow list of URLs for OAuth and LDAP authentication

Two new environment variables are introduced for Kafka that enable you to specify an allow list of URLs for OAuth and LDAP authentication mechanisms. This gives you stricter control over which URLs can be accessed by Kafka. The new environment variables are as follows.

- **OAuth** – `org.apache.kafka.sasl.oauthbearer.allowed.urls`
- **LDAP** – `com.cloudera.kafka.ldap.allowed.urls`

If these variables are left empty (default), connection to any URL is allowed. When configured, Kafka is only allowed to connect to the specified URLs. Configure these variables in your `KafkaNodePool` resource using `spec.jvmOptions.javaSystemProperties`.

```
#...
kind: KafkaNodePool
spec:
  jvmOptions:
    javaSystemProperties:
      - name: com.cloudera.kafka.ldap.allowed.urls
        value: http://www.ldap-example-1.com,http://www.ldap-example-2.com
      - name: org.apache.kafka.sasl.oauthbearer.allowed.urls
        value: http://www.oauth-example-1.com,http://www.oauth-example-2.com
```

Fixed Issues

There are no fixed issues in this release.

Known Issues

Learn about the known issues in this release.

CSMDS-334: ZooKeeper pods are running but Kafka pods are not created

Under certain circumstances, ZooKeeper pods might not be able to form a quorum. In a case like this, the creation of the Kafka cluster gets stuck in a state where ZooKeeper pods are running, but Kafka pods are not created.

If you encounter this issue, at least one of the ZooKeeper pods logs a WARN entry similar to the following:

```
2024-02-23 18:45:00,311 WARN Unexpected exception (org.apache.zoo
keeper.server.quorum.QuorumPeer) [QuorumPeer[myid=3](plain=127.
0.0.1:12181)(secure=[0:0:0:0:0:0:0:0]:2181)]
java.lang.InterruptedException: Timeout while waiting for epoch
from quorum
at org.apache.zookeeper.server.quorum.Leader.getEpochToPropose
(Leader.java:1443)
at org.apache.zookeeper.server.quorum.Leader.lead(Leader.java:60
6)
at org.apache.zookeeper.server.quorum.QuorumPeer.run(QuorumPeer.
java:1552)
```

This is caused by a race condition issue in ZooKeeper. ZooKeeper is unable to recover from this state automatically.

Delete the ZooKeeper pods that are unable to form a quorum.

```
kubectrl delete pod [***ZOOKEEPER POD***] -n [***NAMESPACE***]
```

The Strimzi Cluster Operator automatically recreates the ZooKeeper pods that are deleted. The newly created ZooKeeper pods are less likely to encounter the issue.

CSMDS-953: Kafka and ZooKeeper might experience downtime during upgrades

Under certain circumstances, ZooKeeper pods might not be able to form a quorum during an upgrade. This results in both ZooKeeper and Kafka becoming unavailable for several minutes during an upgrade.

After a certain amount of time, failed ZooKeeper pods are automatically recreated by the Strimzi Cluster Operator, and the upgrade succeeds.

If you encounter this issue, at least one of the ZooKeeper pods will log the following error:

```
java.net.BindException: Cannot assign requested address
```

This issue affects ZooKeeper-based deployments only.

Unsupported features

Learn what features are unsupported in this release.

Unsupported Strimzi features

- Kafka MirrorMaker

- Kafka MirrorMaker 2
- Kafka Bridge
- Kafka cluster creation without using `KafkaNodePool` resources

Unsupported Cloudera Surveyor features

- REST API

Calling the REST API directly using any kind of tooling or using it programmatically is unsupported. At this time, the API is evolving and is subject to major, backward incompatible changes.

Deprecations and removals

Learn what is deprecated or removed in this release.

Deprecations

ZooKeeper

ZooKeeper is deprecated. Deploying new or using existing Kafka clusters running in ZooKeeper mode is deprecated. ZooKeeper will be removed in a future release. When deploying new Kafka clusters, deploy them in KRaft mode. Cloudera encourages you to migrate existing clusters to KRaft.

- For cluster deployment instructions, see [Deploying a Kafka cluster](#).
- For migration instructions, see [Migrating Kafka clusters from ZooKeeper to KRaft](#).

Removals

There are no removals in this release.

Component versions

A list of components and their versions shipped in this release of Cloudera Streams Messaging - Kubernetes Operator.

Table 1: Cloudera Streams Messaging - Kubernetes Operator component versions

Component	Version
Cloudera Surveyor for Apache Kafka	0.1.0.1.4.0-b199
Cruise Control	2.5.141.1.4.0-b199
Kafka	3.9.0.1.4.0-b199
Strimzi	0.45.0.1.4.0-b199
ZooKeeper	3.8.1.7.3.1-b197

Supported Kafka versions

Cloudera Streams Messaging - Kubernetes Operator supports the following Kafka versions:

Table 2: Supported Kafka versions

Version	Component/Resource	Kafka Protocol version	Metadata version
3.9.0.1.4 (latest and default)	<ul style="list-style-type: none"> • Kafka – <code>Kafka</code> resources • Kafka Connect – <code>KafkaConnect</code> resources 	3.9	3.9-IV0

Version	Component/Resource	Kafka Protocol version	Metadata version
3.9.0.1.3	<ul style="list-style-type: none"> Kafka – Kafka resources Kafka Connect – KafkaConnect resources 	3.9	3.9-IV0

Kafka versions shipped in Cloudera Streams Messaging - Kubernetes Operator are specific to Cloudera. You specify them in the `spec.version` property of cluster resources like `Kafka` and `KafkaConnect` resources.

The latest version is the current and latest supported version. This version is used by default to deploy clusters if an explicit version is not provided in your resource configuration. This version is also the version recommended by Cloudera. All other versions listed here are Kafka versions shipped in previous releases of Cloudera Streams Messaging - Kubernetes Operator that are also supported.

The Kafka version is made up of two parts. The first three digits specify the Apache Kafka version. The digits following the Apache Kafka version specify the major and minor version of Cloudera Streams Messaging - Kubernetes Operator. When deploying a cluster, you must use the versions listed here. Specifying upstream versions is not supported.

The Kafka protocol and metadata version is relevant for upgrades. Protocol version is relevant for ZooKeeper-based clusters, while metadata version is relevant for KRaft-based clusters. Depending on your specific upgrade path, explicitly setting the protocol or metadata version might be necessary during an upgrade.

System requirements

Cloudera Streams Messaging - Kubernetes Operator requires a Kubernetes cluster environment that meets the following system requirements and prerequisites. Ensure that you meet these requirements, otherwise, you will not be able to install and use Cloudera Streams Messaging - Kubernetes Operator or its components.

- A Kubernetes 1.25 or later cluster (maximum supported version is 1.32).
 - OpenShift 4.12 or later.
 - Any Cloud Native Computing Foundation (CNCF) certified Kubernetes distribution. For more information, see cncf.io.
- Administrative rights on the Kubernetes cluster.
- Access to `kubectl` or `oc`. These command line tools must be configured to connect to your running cluster.
- Access to `helm`.
- Log collection is enabled for the Kubernetes cluster.

Cloudera requires that the logs of Cloudera Streams Messaging - Kubernetes Operator components are stored long term for diagnostic and supportability purposes. Collect logs using the log collector feature of your Kubernetes platform. Cloudera recommends at least one week of retention time for the collected logs.

- A persistent storage class configured on the Kubernetes cluster that satisfies the durability and low-latency requirements for operating Kafka.

The ideal storage class configuration can vary per environment and use-case and is determined by the Kubernetes platform where Cloudera Streams Messaging - Kubernetes Operator is deployed.

Additionally, for Kafka brokers, Cloudera recommends a `StorageClass` that has volume expansion enabled (`allowvolumeexpansion` set to `true`).

- A [Prometheus](#) installation running in the same Kubernetes cluster where you install Cloudera Streams Messaging - Kubernetes Operator is recommended. Prometheus is used for collecting and monitoring Kafka and Strimzi metrics.

Kafka Connect plugins

Learn what Kafka Connect plugins are shipped with and supported in Cloudera Streams Messaging - Kubernetes Operator.

Connectors

Cloudera Streams Messaging - Kubernetes Operator ships and supports all Kafka Connect connectors included in Apache Kafka.

The full list is as follows.

- `org.apache.kafka.connect.mirror.MirrorCheckpointConnector`
- `org.apache.kafka.connect.mirror.MirrorSourceConnector`
- `org.apache.kafka.connect.mirror.MirrorHeartBeatConnector`
- `org.apache.kafka.connect.file.FileStreamSourceConnector`
- `org.apache.kafka.connect.file.FileStreamSinkConnector`



Note:

Although both `FileStreamSourceConnector` and `FileStreamSinkConnector` are shipped with Cloudera Streams Messaging - Kubernetes Operator, neither connector is installed, and you cannot deploy them by default. To deploy instances of these connectors, you must first install them as any other third-party connector. Cloudera also does not recommend that you use these connectors in production.

Single Message Transforms plugins (transformations and predicates)

Single Message Transforms (SMT) plugins (transformations and predicates) are deployed on top of Kafka Connect connectors. They enable you to apply message transformations and filtering on a single message basis. Cloudera Streams Messaging - Kubernetes Operator ships and supports all transformation and predicates plugins included in Apache Kafka as well as the `ConvertFromBytes` and `ConvertToBytes` plugins, which are Cloudera specific plugins.

The full list is as follows.

Transformations

- `com.cloudera.dim.kafka.connect.transforms.ConvertFromBytes`
- `com.cloudera.dim.kafka.connect.transforms.ConvertToBytes`
- `org.apache.kafka.connect.transforms.Cast`
- `org.apache.kafka.connect.transforms.DropHeaders`
- `org.apache.kafka.connect.transforms.ExtractField`
- `org.apache.kafka.connect.transforms.Filter`
- `org.apache.kafka.connect.transforms.Flatten`
- `org.apache.kafka.connect.transforms.HeaderFrom`
- `org.apache.kafka.connect.transforms.HoistField`
- `org.apache.kafka.connect.transforms.InsertField`
- `org.apache.kafka.connect.transforms.InsertHeader`
- `org.apache.kafka.connect.transforms.MaskField`
- `org.apache.kafka.connect.transforms.RegexRouter`
- `org.apache.kafka.connect.transforms.ReplaceField`
- `org.apache.kafka.connect.transforms.SetSchemaMetadata`
- `org.apache.kafka.connect.transforms.TimestampConverter`
- `org.apache.kafka.connect.transforms.TimestampRouter`
- `org.apache.kafka.connect.transforms.ValueToKey`

Predicates

- `org.apache.kafka.connect.transforms.predicates.HasHeaderKey`
- `org.apache.kafka.connect.transforms.predicates.RecordIsTombstone`
- `org.apache.kafka.connect.transforms.predicates.TopicNameMatches`

Converters

Converters can be used to transform Kafka record keys and values between bytes and a specific format. In addition to the `JsonConverter`, there are converters for most often used primitive types as well.

The full list is as follows.

- `org.apache.kafka.connect.json.JsonConverter`
- `org.apache.kafka.connect.converters.ByteArrayConverter`
- `org.apache.kafka.connect.converters.BooleanConverter`
- `org.apache.kafka.connect.converters.DoubleConverter`
- `org.apache.kafka.connect.converters.FloatConverter`
- `org.apache.kafka.connect.converters.IntegerConverter`
- `org.apache.kafka.connect.converters.LongConverter`
- `org.apache.kafka.connect.converters.ShortConverter`
- `org.apache.kafka.connect.storage.StringConverter`

Header converters

Header converters can be used to transform Kafka record headers between bytes and a specific format. Cloudera Streams Messaging - Kubernetes Operator and Kafka includes a single dedicated header converter, which is the `org.apache.kafka.connect.storage.SimpleHeaderConverter`.

The `SimpleHeaderConverter` is the default header converter and is adequate for the majority of use cases. In case your headers are of a specific format, like JSON, you can use any other converter listed in the [Converters](#) on page 9 section as a header converter as well.

Replication policies

A replication policy defines the basic rules of how topics are replicated from source to target clusters when using Kafka Connect-based replication to replicate Kafka data between Kafka clusters.

The full list is as follows.

- `org.apache.kafka.connect.mirror.DefaultReplicationPolicy`
- `org.apache.kafka.connect.mirror.IdentityReplicationPolicy`

Related Information

[Installing Kafka Connect connector plugins](#)

[ConvertFromBytes](#)

[ConvertToBytes](#)

[Transformations | Kafka](#)

[Predicates | Kafka](#)