

Data Catalog

Data Catalog Operations

Date published: 2019-11-14

Date modified: 2023-03-10

CLOUDERA

<https://docs.cloudera.com/>

Legal Notice

© Cloudera Inc. 2024. All rights reserved.

The documentation is and contains Cloudera proprietary information protected by copyright and other intellectual property rights. No license under copyright or any other intellectual property right is granted herein.

Unless otherwise noted, scripts and sample code are licensed under the Apache License, Version 2.0.

Copyright information for Cloudera software may be found within the documentation accompanying each component in a particular release.

Cloudera software includes software from various open source or other third party projects, and may be released under the Apache Software License 2.0 (“ASLv2”), the Affero General Public License version 3 (AGPLv3), or other license terms. Other software included may be released under the terms of alternative open source licenses. Please review the license and notice files accompanying the software for additional licensing information.

Please visit the Cloudera software product page for more information on Cloudera software. For more information on Cloudera support services, please visit either the Support or Sales page. Feel free to contact us directly to discuss your specific needs.

Cloudera reserves the right to change any products at any time, and without notice. Cloudera assumes no responsibility nor liability arising from the use of products, except as expressly agreed to in writing by Cloudera.

Cloudera, Cloudera Altus, HUE, Impala, Cloudera Impala, and other Cloudera marks are registered or unregistered trademarks in the United States and other countries. All other trademarks are the property of their respective owners.

Disclaimer: EXCEPT AS EXPRESSLY PROVIDED IN A WRITTEN AGREEMENT WITH CLOUDERA, CLOUDERA DOES NOT MAKE NOR GIVE ANY REPRESENTATION, WARRANTY, NOR COVENANT OF ANY KIND, WHETHER EXPRESS OR IMPLIED, IN CONNECTION WITH CLOUDERA TECHNOLOGY OR RELATED SUPPORT PROVIDED IN CONNECTION THEREWITH. CLOUDERA DOES NOT WARRANT THAT CLOUDERA PRODUCTS NOR SOFTWARE WILL OPERATE UNINTERRUPTED NOR THAT IT WILL BE FREE FROM DEFECTS NOR ERRORS, THAT IT WILL PROTECT YOUR DATA FROM LOSS, CORRUPTION NOR UNAVAILABILITY, NOR THAT IT WILL MEET ALL OF CUSTOMER’S BUSINESS REQUIREMENTS. WITHOUT LIMITING THE FOREGOING, AND TO THE MAXIMUM EXTENT PERMITTED BY APPLICABLE LAW, CLOUDERA EXPRESSLY DISCLAIMS ANY AND ALL IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO IMPLIED WARRANTIES OF MERCHANTABILITY, QUALITY, NON-INFRINGEMENT, TITLE, AND FITNESS FOR A PARTICULAR PURPOSE AND ANY REPRESENTATION, WARRANTY, OR COVENANT BASED ON COURSE OF DEALING OR USAGE IN TRADE.

Contents

Managing Datasets.....	5
Create Datasets.....	5
Edit Datasets.....	6
Delete Datasets.....	6
 Collaborate with other users.....	 7
 Search for Assets.....	 8
Filters.....	8
Viewing Ranger and Atlas applications.....	8
Prepopulating Asset Owners.....	9
Accessing Data Lakes.....	9
Navigating to tables and databases in Hue.....	10
Prerequisites for accessing Hue tables and databases.....	10
Accessing Hue tables and databases.....	11
Accessing Hue tables and databases from the search page.....	11
Accessing Hue tables and databases from the Asset Details page.....	12
Accessing Hue assets.....	14
Searching for assets across multiple data lakes.....	15
Download CSV option.....	16
Searching for assets using Glossary.....	18
Using Terms in Data Catalog.....	18
Mapping glossary terms.....	19
Searching for assets using glossary terms.....	22
Additional search options for asset types.....	24
Searching for assets in Data Catalog using additional search options.....	25
Accessing Tables based on Ranger policies.....	26
Creating Classification for selected assets.....	27
Adding Classifications / Terms for selected assets.....	28
Additional Entity type selection for searching Assets.....	28
 Viewing Data Asset Details.....	 30
Viewing Data Assets.....	30
View Data Asset Schema.....	32
Navigating from the container asset to the parent asset from Asset Details page.....	32
View Authorization Policies on a Data Asset.....	33
View Data Asset Audit Logs.....	34
Navigation Support for Hive entity within Lineage.....	34
Adding Hive asset to one or more datasets on Asset Details screen.....	35
Viewing Atlas Entity Audits.....	37
 Managing Profilers.....	 39
Data Catalog profiler data testing.....	40
Launch profiler Cluster.....	40
Launching profilers using Command-line.....	42

Deleting profiler cluster.....	46
On-Demand Profilers.....	48
Profiling table data in non-default buckets.....	49
High Availability support for Profiler services.....	49
Tracking Profiler Jobs.....	52
Viewing Profiler Jobs.....	53
Viewing Profiler Configurations.....	53
Edit Profiler Configuration.....	54
Additional Configuration for Cluster Sensitivity Profiler.....	54
Additional Configuration for Hive Column Profiler.....	55
Understanding Cron Expression generator.....	56
Setting Asset filter rules.....	56
Backing up and Restoring Profiler Database.....	59
About the script.....	59
Running the script.....	60
Enable or Disable Profilers.....	62
Profiler Tag Rules.....	62
Tag Management.....	63
Tagging Multiple Assets.....	66
Creating Custom Profiler Rules.....	69
Adding Custom Regular Expressions.....	69
Adding Lookup Files.....	70
Using Behaviors.....	70
Regular expressions.....	71
File based denylist and allowlist checks.....	71
Luhn algorithm.....	71
Using DSL Grammar.....	71

Managing Datasets

You can view, create, edit, and delete Datasets.

On the Data Catalog menu, click Datasets to view all the datasets.

Search for Datasets

On the Datasets page, enter a search string in the search box to view all asset collections with names that contain the search string.

Filter Datasets by Tags

You can filter Datasets and view Dataset with the tags. Select the tag from the drop down list or enter the tag in the filter box. Any Dataset with the filter tag assigned to a column will appear in the filter results.

Related Information

[Understanding asset collections](#)

Create Datasets

You can group data assets into Datasets. This enables you to organize data based on business classifications, purpose, protection requirements, or more. Examples of Datasets are: customer profiles, sales assets, financials, PII, and HR data.

Procedure

1. From the Datasets page, click Add Datasets.
The Add page appears.
2. Enter the following information.

Field Name	Description	Example Values
Name	Enter an appropriate dataset name. This name cannot be duplicated across the system. (Mandatory)	Customer Profiles, Sales Assets, Financials
Description	Describe the purpose or intent of the dataset. (Mandatory)	Contains customer profiles: data assets for US and WW.
Data Lake	Assign the dataset to one Data lake. Choose from a list of available Data lakes. (Mandatory)	dss_bbsh_clust3
Tags	Add tags to your dataset for context and subsequent lookup. Tags enable your to quickly catalog, search and retrieve asset collections as well as share such information with others in the future. (Optional)	se, pii, geo, finance
Public/Private	Select public if you want other users to have access to this dataset. Select private if only you want to have access to this dataset.  Note: You can later change the status of the asset collection. Click the lock icon on the Dataset Details page to change the access state of the dataset.	

3. Click Next.
The Dataset Details page appears for the new dataset.
4. Click Add Assets to add related data assets into your dataset.
The Asset Search page appears.
5. Search for assets using Basic Search.
 - a) Search using the name of the asset by entering the name in the search bar.
 - b) Use filters to search for specific assets based on the attributes of assets. Click Filter to display the filters available.
 - Created Time: From the dropdown list, select the time to refine the search on the basis of when the asset has been created.
 - Owner: Enter the name of the owner to refine the search on the basis of the owners of the assets.
 - DB Name: Enter the name of the database.
 - Tag: Enter the names of the tags.
 - c) Select one more than one filter if needed.
 - d) Click Search to view the assets. The Results appear.
 - e) Click Reset to reset the filters and search again.
 - f) From the list, click to select the assets that you like to add to your dataset.
6. Search for assets using Advanced Search, if needed. Advanced search uses facets of technical and business metadata about the assets, such as those captured in Apache Atlas, to help users define and build collections of interest. Advanced search conditions are a subset of attributes for the Apache Atlas type `hive_table`.
7. Click Done.
The assets are added to the dataset and the Search page is refreshed.
8. Close the Search tab.
The Datasets Details page appears.
9. Click Save.

Edit Datasets

You can edit Datasets by adding or removing assets and changing the access state of the Datasets.

Procedure

1. Click a Dataset in the list to edit it. The Details page of that Dataset appears.
2. On the Assets tab, click Edit to edit the content of this Dataset. The Dataset appears in edit mode. If another user is editing this Dataset, an error message will appear saying that this Dataset is being edited by another user and you cannot edit it.
3. Add or remove assets in the Dataset.
 - a) Click Add to add new assets to this Dataset.
 - b) Select one or more assets and click Remove to remove assets from this Dataset.
4. Click Save to save the changes that you made to the Dataset.
5. Click Cancel to undo any changes that you made to this Dataset.

Delete Datasets

You might want to delete an Datasets if you no longer need to track those Datasets, or if you want to reassign those assets to another Dataset. You can delete Datasets at any time. Deleting an Datasets does not delete the assets contained therein, it only disassembles the Datasets. You can re-create Datasets or reassign assets to new Datasets.

Procedure

1. From Data Catalog Datasets page, click the More Options icon beside the name of the Dataset you want to delete.
2. Click Delete.
3. Click Confirm.
You are returned to the Datasets home page.

Collaborate with other users

You can collaborate and share insights with other users in the enterprise regarding various datasets.

You can rate datasets and view the average rating of a dataset. This can help other users to find datasets with higher ratings easily. You can also add your knowledge and insights about the asset collection by adding comments. Other users can respond to your comments or add their comments about each data asset collection.

On the right hand side of each asset collection page, you can see additional details about the dataset. The collaboration details are also displayed in this tab. The tab displays the following details - average rating for the asset collection, the number of likes, the number of comments, and the bookmark icon indicating if the dataset is bookmarked by the current user or not.

You can perform the following collaboration actions for each dataset.

Like a Dataset

You can let other users know that you like a Dataset. The like icon on the Dataset page displays the total number of likes received by this Dataset.

Click the like icon to add the Dataset to your list of liked collections.

Comment and discuss about a Dataset

You might want to share your knowledge or insights about this Dataset with other users. Data Catalog allows you to collaborate with other users by adding comments.

Click the comment icon to add a comment about this Dataset. The Collaborate tab expands. Click Actions menu to reply to an existing comment. You can continue to add comments for each Dataset.

Bookmark the Dataset

In addition to sharing with other users, you can also bookmark Datasets for easy access in the future.

Click the bookmark icon to add the Dataset to your list of bookmarks. This Dataset will appear in the list of bookmarks when you click the Bookmarks link on the left navigation menu.

Rate the Dataset

You can also rate the datasets on a scale of one to five. Click the star icon to rate the open Dataset. The Collaborate tab expands.

Click the stars to provide your own rating. The rating on the Datasets page shows the average of the rating provided by various users. The Rating section also displays the number of votes given for this Dataset.

View the tags of an Dataset

You can add tags while creating the Dataset. You can also click on the tags to search for Datasets with similar tags. There are two types of tags. System tags are automatically generated based on the details of the assets in the Datasets. You can add more tags that appear in the list of user generated tags.

Search for Assets

On the Data Catalog Search page, select a data lake and enter a search string in the search box to view all the assets with details that contain the search string.

When you enter the search terms in Data Catalog Search, you are looking up names, types, descriptions, and other metadata collected by Data Catalog. The search index includes metadata (not data) about your environment and cluster data assets and operations. You can make the search more powerful by associating your own information (business metadata) to the assets that Data Catalog stores.

Related Information

[Understanding data assets](#)

Filters

When you select a property value, a filter breadcrumb shows above the search results.

You can further refine your search results using filters as follows:

- Owner - From all the owner names that appear, you can select the owner to further refine the results and display those search results with the selected owner.
- Database - Select the database to view all the assets stored in that database. This filter is applicable to Hive and HBase tables only.



Note: For information purposes, Database filter is displayed as Namespace in case of HBase tables.

- Entity Tag - Use entity tags to refine your search results. You can add business metadata as entity tags in Atlas and use these tags to refine your search results and view the details of the required data asset.
- Created Within - You can choose to refine your search results of assets within the data lake to view the data assets created within the last 7 days, 15 days, or 30 days. You can also add custom values such as 5 days or 10 days to view specific information.
- Created Before - Depending on the time when the assets were created, you can choose to refine the search results and view data assets created before 1 day, 7 days, or 15 days. You can add custom values to view data assets created before the days of your preference such as 8 days or 12 days.




Note: These two filters (Created Within and Created Before) are applicable only when Atlas provides the created time for the assets.

- Column Tag - You can search for Hive and HBase table assets by tags that have been applied on their children entities, that is, columns or column families using the column tags filter.
- Glossary - You can filter assets based on business glossary terms. You can search for any asset without any entity type restrictions.

Click Clear for any filter to clear the selection. You can use a combination of filters to view the required data assets.

Viewing Ranger and Atlas applications

For the selected data lake, click Ranger to view the Ranger app in a new browser tab. Click Atlas to view the Atlas app in a new browser tab.



The Atlas and Ranger buttons seen on the search page of Data Catalog allows you to navigate to the specific SDX component. Clicking on Atlas navigates to the Atlas landing page in a new browser tab and the same process takes place to land you on the Ranger landing page when you click on Ranger. This allows finer access and control over the assets and the surrounding policies.

Prepopulating Asset Owners

In Data Catalog, under the search page, you can filter for assets based on the owners.

Rather than having to type in the owners manually, the available asset owners are listed in drop down. Select the record from the list and add it as a filter criteria

For example, in the following diagram, the selected asset TYPE is “Hive”.

For the selected TYPE the owner “hive” is available in the drop-down and based on this condition, the assets can be filtered in the search page.

Data Catalog / Search

[Ranger](#)
[Atlas](#)
[Create Dataset](#)

Filters	Type	Name	Location	Created On	Owner	Source
TYPE Clear ^ <input checked="" type="checkbox"/> Hive Table <input type="checkbox"/> HBase Table + Add New Value	<input type="checkbox"/>	scheduled_queries	/information_schema	Mon Sep 07 2020	hive	hive
	<input type="checkbox"/>	home_stay	/travel	Mon Sep 07 2020	hrt_1	hive
	<input type="checkbox"/>	day_resort	/resort	Mon Sep 07 2020	hrt_qa	hive
	<input type="checkbox"/>	weather	/wonders	Mon Sep 07 2020	hrt_qa	hive
	<input type="checkbox"/>	lounge_classic	/airline	Mon Sep 07 2020	hrt_1	hive
	<input type="checkbox"/>	call_center	/tpcds_bin_partitioned_parquet_50	Mon May 11 2020	csso_mhussain	hive
	<input type="checkbox"/>	date_dim	/tpcds_bin_partitioned_parquet_50	Mon May 11 2020	csso_mhussain	hive
	<input type="checkbox"/>	compactions	/sys	Mon Sep 07 2020	hive	hive
	<input type="checkbox"/>	tables	/information_schema	Mon Sep 07 2020	hive	hive
	<input type="checkbox"/>	column_privileges	/information_schema	Mon Sep 07 2020	hive	hive
	<input type="checkbox"/>	table_privileges	/information_schema	Mon Sep 07 2020	hive	hive
	<input type="checkbox"/>	lounge_premium	/airline	Mon Sep 07 2020	hrt_1	hive
	<input type="checkbox"/>	lounge	/airline	Mon Sep 07 2020	hrt_1	hive
	<input type="checkbox"/>	version	/sys	Mon Sep 07 2020	hive	hive
	<input type="checkbox"/>	flight	/airline	Mon Sep 07 2020	hrt_1	hive
	<input type="checkbox"/>	world	/wonders	Mon Sep 07 2020	hrt_qa	hive
	<input type="checkbox"/>	schemata	/information_schema	Mon Sep 07 2020	hive	hive
	<input type="checkbox"/>	partition_stats_view	/sys	Mon Sep 07 2020	hive	hive
	<input type="checkbox"/>	scheduled_executions	/information_schema	Mon Sep 07 2020	hive	hive
	<input type="checkbox"/>	cdh_version	/sys	Mon Sep 07 2020	hive	hive

Accessing Data Lakes

In the Data Catalog search dashboard, the accessible data lakes are displayed under the search panel.

Users have access to the lakes based on the permissions that are granted. You can choose the available lake by selecting the appropriate radio button.

For more information about the user permissions, see [Prerequisite to access Data Catalog Service](#).

For example, in the following diagram, the logged in user has access to all the listed data lakes.

Search

Search Atlas Ranger

Data Lakes 2619
672
NA

Filters

TYPE

Hive Table
 HBase Table
[Add New Value](#) [Clear](#)

OWNERS

atlas
 CharlieFadel
 csso_mhussain
 csso_ram
 csso_rasharma
[Add New Value](#) [Clear](#)

Profiler Cluster is provisioned successfully

Type	Name	Qualified Name	Created On	Owner	Source	Action
<input type="checkbox"/>	Azure Container	container	abfs://container@sparktestingstorage...	-NA-	-NA-	adls
<input type="checkbox"/>	AWS S3 V2 Bucket	s3-extractor-test	s3a://s3-extractor-test@cm	-NA-	-NA-	aws
<input type="checkbox"/>	Hive Table	lounge	airline.lounge@cm	Mon Oct 04 2021	hrt_1	hive
<input type="checkbox"/>	Hive Table	world	wonders.world@cm	Mon Oct 04 2021	hrt_qa	hive
<input type="checkbox"/>	Hive Table	night_stay	resort.night_stay@cm	Mon Oct 04 2021	hrt_qa	hive
<input type="checkbox"/>	Hive Table	date_dim	tpcds_bin_partitioned_parquet_50.date...	Mon May 11 2020	csso_mhussain	hive
<input type="checkbox"/>	Hive Table	web_site	tpcds_bin_partitioned_parquet_50.web...	Mon May 11 2020	csso_mhussain	hive
<input type="checkbox"/>	Hive Table	reason	tpcds_bin_partitioned_parquet_50.reas...	Mon May 11 2020	csso_mhussain	hive
<input type="checkbox"/>	Hive Table	web_sales	tpcds_bin_partitioned_parquet_50.web...	Mon May 11 2020	csso_mhussain	hive
<input type="checkbox"/>	Hive Table	datagen_table_sensitive_168__1	default.datagen_table_sensitive_168__1...	Mon Oct 04 2021	hive	hive
<input type="checkbox"/>	Hive Table	new_data_table9d	default.new_data_table9d@cm	Mon Oct 04 2021	hive	hive
<input type="checkbox"/>	Hive Table	datagen_table_sensitive_488__1	default.datagen_table_sensitive_488__1...	Mon Oct 04 2021	hive	hive

Related Information

[Introduction to Data Lakes](#)

[Understanding Data Lake details](#)

Navigating to tables and databases in Hue

Data Catalog helps you to explore assets within your Data Lake. Hue allows you to run analytics on Hive assets. The integration between Data Catalog and Cloudera Data Warehouse (CDW) service provides a direct web link to the Hue instance from the Data Catalog web UI, making it easy to navigate across services.

Prerequisites for accessing Hue tables and databases

Hue is a part of the CDW service. Before you can access Hue from Data Catalog, you must set up the CDW service.

Before you begin

You must have the DWAdmin role to perform these tasks.

Procedure

1. An AWS or Azure environment in CDW that has been activated and registered in the CDP Management Console. Activating an AWS or Azure environment in CDW enables the CDW service to use the existing Data Lakes that are present in the CDP environment. This also creates a default Database Catalog that is used by a Virtual Warehouse.

For more information, see [Activating AWS environments](#) or [Activating Azure environments](#). Currently, CDW only supports AWS and Azure Cloud environments

2. A Hive or an Impala Virtual Warehouse created using CDW. Depending on your data set type, create a Hive or an Impala Virtual Warehouse using CDW.

For more information, see [Adding a new Virtual Warehouse](#).

3. Select the asset type in the Data Catalog UI.

The asset type must be either `hive_table` or `hive_db`.

After these conditions are met, Hue links for the selected assets are displayed in the Data Catalog UI.

What to do next

Accessing Hue tables and databases

When you log into Data Catalog, you can access web links to the Hue instances from the Data Catalog Search page or the Asset Details page.

Before you begin

You can access the Hue tables and databases by using one of the following options in Data Catalog,

Procedure

1. Log into Cloudera Data Catalog UI.
- 2.

When you navigate to the entity search page, you can click on the  icon present at the end of the row which opens the Link to Experiences dialog.

3. Directly on the selected asset's Asset Details page, you can click Link to Experiences.

Accessing Hue tables and databases from the search page


When you log into Data Catalog, you can access web links to the Hue instances from the Data Catalog Search page.

Procedure

1. Log into Cloudera Data Catalog UI.
2. Select the Data Lake associated with your environment.
3. Select the asset type under Filters, for example Hive Table.
Hive tables present within the Data Lake are displayed.

4.

Click the  icon at the end of the row for a table that you want to display in Hue.




The screenshot shows the Cloudera Data Catalog Search interface. A table named 'abc' is selected, and a 'Link to Experience' pop-up is displayed. The pop-up lists three Hue instances:

- panos-scheduler(hive)
- mustafa-vw(hive)
- rbalamohan-s3-tpcds-10tb-test(hive)

Type	Name	Location	Created On	Owner	Source
Hive Table	abc	/default	Tue Jul 07 2020	csso_ssomarajapuram	hive
Hive Table	income_band	/tpcds_bin_partitioned_orc_10000	Mon Jul 13 2020	csso_ndembia	hive
Hive Table	catalog_returns	/tpcds_bin_partitioned_orc_10000	Mon Jul 13 2020	csso_ndembia	hive
Hive Table	customer_demographics	/tpcds_bin_partitioned_orc_10000	Mon Jul 13 2020	csso_ndembia	hive
Hive Table	household_demographics	/tpcds_bin_partitioned_orc_10000	Mon Jul 13 2020	csso_ndembia	hive
Hive Table	store_sales_clust	/tpcds_bin_partitioned_orc_10000	Wed Jul 15 2020	csso_ndembia	hive
Hive Table	test_arr	/delete_orc_30	Mon Sep 14 2020	csso_rbalamohan	hive
Hive Table	test_exp	/delete_orc_30	Thu Sep 17 2020	csso_rbalamohan	hive
Hive Table	customer_c31	/tpcds_bin_partitioned_orc_10000	Thu Oct 08 2020	csso_ndembia	hive
Hive Table	customer_address_c31	/tpcds_bin_partitioned_orc_10000	Thu Oct 08 2020	csso_ndembia	hive
Hive Table	test_date_dim	/tpcds_bin_partitioned_orc_10000	Thu Oct 22 2020	csso_ndembia	hive
Hive Table	customer_address	/emeters_db	Fri Oct 23 2020	csso_ndembia	hive
Hive Table	customer	/emeters_db	Fri Oct 23 2020	csso_ndembia	hive
Hive Table	meter_reading	/emeters_db	Fri Oct 23 2020	csso_ndembia	hive
Hive Table	test_acid	/delete_orc_30	Tue Oct 27 2020	csso_rbalamohan	hive
Hive Table	query4_11_74_year_ws	/tpcds_bin_partitioned_orc_10000	Wed Oct 28 2020	csso_ndembia	hive
Hive Table	query4_11_74_year	/tpcds_bin_partitioned_orc_10000	Tue Oct 27 2020	csso_ndembia	hive
Hive Table	ship_mode	/tpcds_bin_partitioned_orc_10000	Mon Jul 13 2020	csso_ndembia	hive
Hive Table	promotion	/tpcds_bin_partitioned_orc_10000	Mon Jul 13 2020	csso_ndembia	hive
Hive Table	time_dim	/tpcds_bin_partitioned_orc_10000	Mon Jul 13 2020	csso_ndembia	hive

A Link to Experiences pop-up appears. It contains a list of Hue instances within the virtual warehouses that are associated with this particular table.

- Click the link to open Hue web interface.
The Hive table is displayed on the Hue Table Browser.



The screenshot shows the Hue Table Browser interface. The table 'abc' is displayed with the following properties:

- Table:** abc
- Managed and stored in location:** /default
- Created by on:** 01/01/1970 05:30 +05:30

The schema shows one column:


Column (1)	Type	Description	Sample
a	string		

Accessing Hue tables and databases from the Asset Details page


When you log into Data Catalog, you can access web links to the Hue instances from the Data Catalog Search Asset Details page. Log into Cloudera Data Catalog

Procedure

1. Log into Cloudera Data Catalog UI.
2. Select the Data Lake associated with your environment.
3. Select the asset type under Filters, for example Hive Table. All the Hive tables present within the Data Lake are displayed
4. Click on the asset name to open the Asset Details page. The Asset Details page contains the Link to Experience button as shown in the following image:



5. Click Link to Experience.
The pop-up contains a list of Hue instances within the Virtual Warehouses that are associated with this particular table.
6. Click the link to open Hue web interface.
The Hive table is displayed on the Hue Table Browser.



Accessing Hue assets

When you are on the Data Catalog search page or the Asset Details page, to access Hue assets, an external link button is used.


Before you begin

You must fulfill all the three conditions as listed in [Prerequisites for accessing Hue tables and databases](#) on page 10 for viewing the external link button.

You must activate Cloudera Data Warehouse on your selected environment.


Procedure

1. Login to Cloudera Data Platform.
2. Under Management Console > select Data Warehouse
3. On the Overview page, click on the left pane property displaying Environments. AWS/Azure environments are listed.
4. Locate the enabled AWS / Azure environment and activate CDW by clicking on the bolt icon. This action also creates a default Database Catalogs.



- Once the environment is activated and a DB Catalog is created and running, you can create a virtual warehouse as per the requirement.

For more information about AWS and Azure Environment, see [AWS environments overview](#) and [Azure environments overview](#).



You will now be able to navigate to the Hue assets on these virtual warehouses using the links provided by Data Catalog.

Searching for assets across multiple data lakes

In Data Catalog, the data lake search capabilities has been enhanced with the way you can search for the assets. You can now view the complete list of data lakes that are available in a specific Data Catalog instance.

Previously, to search for assets using a data lake, a drop-down menu was available to select a data lake. You can now use the radio button to select a specific data lake.

The number of assets that are visible against each data lake indicate that they are applicable to the search query that match. You can select a specific data lake and select one or more search query types to retrieve the total list of available assets in the selected data lake. The total count of the selected data lake can change based on the type of filter that is applied.

You can get the count of all the assets complying with the set search criteria from all the data lakes and display the same for each lake. Using the asset count details, you can optionally change the data lake and with which the result count is obtained from the selected lake. When you select a data lake, the search query gets updated by default. The previous query that was triggered on a previously selected data lake is not carried forward to the currently selected data lake.

For each selected data lake, you can set up different queries and the total asset count varies. Also, in certain scenarios, when a search query is triggered, the data lake count (when hovered on NA) displays the message Asset count for data lakes with Runtime version below 7.2.1 is not supported. The asset count for each selected data lake appears only if the Runtime version is above 7.2.1.

Search

Atlas Ranger

Data Lakes

- cod-7213 43
- glue.cod-7213 NA
- cod-7212 31
- glue.cod-7212 NA
- cod-7213-gcp 9
- spark-p5z3y 16
- Cluster 1, rachit NA
- Cluster 1, dc_rd NA

Filters

TYPE

- Hive Table
- HBase Table
- [+ Add New Value](#) Clear

OWNERS

- atlas
- hbase
- hive
- public
- Clear

Setup the Profiler for spark-p5z3y

Profiler runs data profiling operations as a pipeline on data located in the data lake which helps to view the profiled results for assets. Setting up a Profiler launches a cluster with various services like HDFS, YARN, Livy, Spark, HMS, Profiler Manager Service, and Profiler Scheduler Service. [Get Started >](#)

spark-p5z3y | 16

Type	Name	Qualified Name	Created On	Owner	Source
<input type="checkbox"/>	HBase Table	hbase.acl	Wed Dec 01 2021	hbase	
<input type="checkbox"/>	HBase Namespace	hbase	-NA-	hbase	
<input type="checkbox"/>	HBase Column Family	l	Wed Dec 01 2021	hbase	hbase
<input type="checkbox"/>	HBase Column Family	dt	Wed Dec 01 2021	hbase	hbase
<input type="checkbox"/>	HBase Table	ATLAS_ENTITY_AUDIT_EVENTS	Wed Dec 01 2021	hbase	hbase
<input type="checkbox"/>	HBase Column Family	m	Wed Dec 01 2021	atlas	hbase
<input type="checkbox"/>	HBase Column Family	g	Wed Dec 01 2021	atlas	hbase
<input type="checkbox"/>	HBase Column Family	l	Wed Dec 01 2021	atlas	hbase
<input type="checkbox"/>	HBase Column Family	h	-NA-	atlas	hbase
<input type="checkbox"/>	HBase Column Family	f	-NA-	atlas	hbase
<input type="checkbox"/>	HBase Column Family	t	-NA-	atlas	hbase
<input type="checkbox"/>	HBase Table	atlas_janus	Wed Dec 01 2021	atlas	hbase
<input type="checkbox"/>	HBase Column Family	s	Wed Dec 01 2021	atlas	hbase
<input type="checkbox"/>	HBase Column Family	i	Wed Dec 01 2021	atlas	hbase
<input type="checkbox"/>	HBase Namespace	default	-NA-	atlas	hbase

Search

Atlas Ranger

Data Lakes

- cod-7213 0
- glue.cod-7213 NA
- cod-7212 0
- glue.cod-7212 NA
- cod-7213-gcp 0
- spark-p5z3y 663
- Cluster 1, rachit NA
- Cluster 1, dc_rd NA

Filters

TYPE

- Hive Table
- HBase Table
- [+ Add New Value](#) Clear

OWNERS

- atlas
- hbase
- hive
- public
- Clear

Setup the Profiler for spark-p5z3y

Profiler runs data profiling operations as a pipeline on data located in the data lake which helps to view the profiled results for assets. Setting up a Profiler launches a cluster with various services like HDFS, YARN, Livy, Spark, HMS, Profiler Manager Service, and Profiler Scheduler Service. [Get Started >](#)

spark-p5z3y | 663

Type	Name	Qualified Name	Created On	Owner	Source
<input type="checkbox"/>	Hive Table	global_privs	Wed Dec 01 2021	hive	hive
<input type="checkbox"/>	Hive Table	database_params	Wed Dec 01 2021	hive	hive
<input type="checkbox"/>	Hive Table	columns_v2	Wed Dec 01 2021	hive	hive
<input type="checkbox"/>	Hive Table	bucketing_cols	Wed Dec 01 2021	hive	hive
<input type="checkbox"/>	Hive Table	db_privs	Wed Dec 01 2021	hive	hive
<input type="checkbox"/>	Hive Table	tbls	Wed Dec 01 2021	hive	hive
<input type="checkbox"/>	Hive Table	partitions	Wed Dec 01 2021	hive	hive
<input type="checkbox"/>	Hive Table	version	Wed Dec 01 2021	hive	hive
<input type="checkbox"/>	Hive Table	mv_creation_metadata	Wed Dec 01 2021	hive	hive
<input type="checkbox"/>	Hive Table	db_version	Wed Dec 01 2021	hive	hive
<input type="checkbox"/>	Hive Table	partition_params	Wed Dec 01 2021	hive	hive
<input type="checkbox"/>	Hive Table	part_privs	Wed Dec 01 2021	hive	hive
<input type="checkbox"/>	Hive Table	part_col_privs	Wed Dec 01 2021	hive	hive
<input type="checkbox"/>	Hive Table	roles	Wed Dec 01 2021	hive	hive
<input type="checkbox"/>	Hive Table	serdes	Wed Dec 01 2021	hive	hive

Download CSV File

Your file is getting downloaded

17

The screenshot shows the Data Catalog search interface. On the left, there is a sidebar with 'Data Lakes' and 'Filters'. The main area displays a search result for 'spark-p5zj3y' with a table of assets. A 'Download CSV File' notification is visible in the bottom right corner.

Type	Name	Qualified Name	Created On	Owner	Source
Hive Table	global_privs	sys.global_privs@cm	Wed Dec 01 2021	hive	hive
Hive Table	database_params	sys.database_params@cm	Wed Dec 01 2021	hive	hive
Hive Table	columns_v2	sys.columns_v2@cm	Wed Dec 01 2021	hive	hive
Hive Table	bucketing_cols	sys.bucketing_cols@cm	Wed Dec 01 2021	hive	hive
Hive Table	db_privs	sys.db_privs@cm	Wed Dec 01 2021	hive	hive
Hive Table	tbls	sys.tbls@cm	Wed Dec 01 2021	hive	hive
Hive Table	partitions	sys.partitions@cm	Wed Dec 01 2021	hive	hive
Hive Table	version	sys.version@cm	Wed Dec 01 2021	hive	hive
Hive Table	mv_creation_metadata	sys.mv_creation_metadata@cm	Wed Dec 01 2021	hive	hive
Hive Table	db_version	sys.db_version@cm	Wed Dec 01 2021	hive	hive
Hive Table	partition_params	sys.partition_params@cm	Wed Dec 01 2021	hive	hive
Hive Table	part_privs	sys.part_privs@cm	Wed Dec 01 2021	hive	hive
Hive Table	part_col_privs	sys.part_col_privs@cm	Wed Dec 01 2021	hive	hive

Searching for assets using Glossary

Use glossaries to define a common set of search terms that data users across your organization use to describe their data.

Data can describe a wide variety of content: lists of names or text or columns full of numbers. You can use algorithms to describe data as having a specific pattern, of being within a range or having wide variation, but what's missing from these descriptions is what does the data mean in a given business context and what is it used for? Is this column of integers the count of pallets that entered a warehouse on a given day or number of visitors for each room in a conference center?

The glossary is a way to organize the context information that your business uses to make sense of your data beyond what can be figured out just by looking at the content. The glossary holds the terms you've agreed upon across your organization so business users can use familiar terms to find what they are looking for.

Glossaries enable you to define a hierarchical set of business terms that represents your business domain.

Glossary terms can be thought of as of a flat (but searchable) list of business terms organized by glossaries. Unlike classifications, terms are not propagated through lineage relationships: the context of the term is what's important, so propagation may or may not make sense.

Using Terms in Data Catalog

You can use the Asset Details page in Data Catalog to add or modify "terms" for your selected assets.

A new widget called "Terms" is available in the Asset Details page. You can define rich glossary vocabularies using the natural terminology (technical terms and/or business terms). To semantically relate the term(s) to each other. And finally to map assets to glossary terms(s).

You can assign terms with entities, search for entities, filter entities by glossary term(s), and also search for entities by using associated term(s).



Note: When you work with terms in Data Catalog and map them to your assets, you can search for the same datasets in Atlas by using the corresponding terms.

Asset Details

The screenshot shows the 'world' asset details page. The 'Properties' section includes: Type: HIVE TABLE, # of Columns: 4, Data Lake: [redacted], Datasets: 1, Owner: hrt_Laa, Created On: Mon Oct 04 2021 12:12:39 GMT+0530 (India Stan...), Last Access Time: Mon Oct 04 2021 12:12:39 GMT+0530 (Indi...), Table Type: MANAGED_TABLE, Database: wonders, DB Catalog: cm, Parent: wonders. The 'Qualified Name' is wonders.world@cm. The 'Classifications' section shows one classification: test_dss_atlas_tag_j69ef_val25, ... with a 'Managed' status. The 'Terms' section is empty with an 'Add Terms' button. The 'Profilers' section shows two profilers: Cluster Sensitivity Profiler (Last run: an hour ago, Status: FAILED, Next Schedule Run: Today at 6:50 PM) and Hive Column Profiler (Last run: an hour ago, Status: FAILED, Next Schedule Run: Today at 11:30 PM). The navigation bar includes Overview, Schema, Metadata Audits, Policy, and Access Audits.

Mapping glossary terms

Data Catalog contains the glossary terms that are created in Atlas.



You can search for those terms in Data Catalog and map specific terms with Data assets. You can search for terms in Data Catalog to either add and delete them from the selected data asset. The selected asset displays the total number of terms associated or mapped accordingly.

When you map a specific term for your dataset, the term is displayed in the following format:


```
<termname>@glossaryname>
```

The screenshot shows the 'data' asset details page. The 'Properties' section includes: Type: HIVE TABLE, # of Columns: 12, Data Lake: [redacted], Datasets: 0, Owner: daprofiler, Created On: Mon Mar 29 2021 14:48:32 GMT+0530 (India Standard Time), Last Access Time: Mon Mar 29 2021 14:48:32 GMT+0530 (India Standar...), Table Type: EXTERNAL_TABLE, Database: default, DB Catalog: cm, Parent: default. The 'Qualified Name' is default.data@cm. The 'Classifications' section shows five classifications: dp, Nam venenatis elit et ultrices sollicitudin, Proin dictum mauris velit, and two others with a '+2' indicator. The 'Terms' section is highlighted with a red box and shows three mapped terms: 'New term for corporate finance', 'Automated Teller Machine (ATM)', and 'Gross Profit'. The 'Profilers' section shows two profilers: Cluster Sensitivity Profiler (Last run: a day ago, Status: SUCCESS, Next Schedule Run: Tomorrow at 3:50 PM) and Hive Column Profiler (Last run: a day ago, Status: SUCCESS, Next Schedule Run: Today at 11:30 PM). The 'Lineage' section shows a flow from /user/dpprofiler/... to data to test_tbl.

You can use the icon in the Terms widget on the Asset Details page to add new terms for your data asset. Click Save to save the changes.



You can search for the same asset in the corresponding Atlas environment as shown in the example image.



Additionally, you can also associate terms to your datasets by selecting one or more assets on the Data Catalog search page. You can associate terms with multiple datasets at a time.

Data Catalog / Search

Search

Type	Name	Location	Created On	Owner	Source
<input checked="" type="checkbox"/> Hive Table	testmanaged	/default	Mon Mar 29 2021	hive	hive
<input checked="" type="checkbox"/> Hive Table	test100	/test	Mon Mar 29 2021	hive	hive
<input checked="" type="checkbox"/> Hive Table	test_tbl	/default	Mon Mar 29 2021	dpprofiler	hive
<input checked="" type="checkbox"/> Hive Table	data	/default	Mon Mar 29 2021	dpprofiler	hive
<input checked="" type="checkbox"/> Hive Table	testmanaged100	/test	Mon Mar 29 2021	hive	hive
<input checked="" type="checkbox"/> Hive Table	testtext	/default	Mon Mar 29 2021	hive	hive

Data Catalog / Search

Add Terms to 6 selected entities

Term	Glossary
<input type="checkbox"/> term -1	glossary - 2
<input type="checkbox"/> Accounting Rate of Re...	Corporate Finance
<input type="checkbox"/> New term for corporat...	Corporate Finance
<input type="checkbox"/> Automated Teller Mac...	Corporate Finance
<input type="checkbox"/> Compound Annual Gr...	Corporate Finance
<input type="checkbox"/> Gross Profit	Corporate Finance
<input type="checkbox"/> a very long term is bel...	Corporate Finance
<input type="checkbox"/> Employee Stock Owne...	Corporate Finance

When you select a Hive table asset and navigate to the Asset Details page, under the Schema tab, you can view the list of terms associated with the asset.

Overview Schema Metadata Audits Policy Access Audits

Search Column

Chart Type	Column Name	Type	Unique Values *	Null Values	Max	Min	Mean	Comment	Classifications	Terms
▼	age	int	21	18	49	1	23.66		Nam venenatis elit et. + 1	
▼	cabin	string	9	0					Nam venenatis elit et. + 1	Accounting Rate of ... + 1
▼	embarked	string	3	0					dp_ukpassportnumbe + 2	Compound Annual G... + 1
▼	fare	float	35	0	262.38		23.78		dp_ukpassportnumbe + 1	New term for corpor... + 5
▼	name	string	54	0					dp_ukpassportnumbe + 6	New term for corpor... + 5
▼	parch	int	3	0	2		0.42		dp_ukpassportnumbe + 1	New term for corpor... + 6
▼	passengerid	int	50	0	53	1	27		dp_ukpassportnumbe + 2	New term for corpor... + 2
▼	pclass	int	3	0	3	1	2.42		dp_ukpassportnumber	New term for corpor... + 5
▼	sex	string	2	0					dp_ukpassportnumber	a very long term is b... + 6
▼	sibsp	int	4	0	8		0.43			
▼	survived	int	2	0	1		0.72			
▼	ticket	string	48	0						

Rows per page: 20 1 - 12 of 12

You can add or update the terms for the associated datasets by clicking the Edit button.

The screenshot shows the Cloudera Data Catalog interface for an asset's details. The left sidebar contains navigation options: Search, Datasets, Bookmarks, Profilers, Atlas Tags, Get Started, and Help. The main content area is titled "Data Catalog / Asset Details" and has tabs for Overview, Schema, Metadata Audits, Policy, and Access Audits. The "Schema" tab is active, displaying a table of columns. A search bar at the top of the table is labeled "Search Column". The table columns include Chart Type, Column Name, Type, Unique Values, Null Values, Max, Min, Mean, Comment, Classifications, Terms, and Classifications. The "Terms" column contains filters such as "a very long term is b... +7". A red arrow points to the "Terms" column header, and a dropdown menu is open showing "Terms" and "Classifications". A "Feedback" button is visible on the right side of the table.

Chart Type	Column Name	Type	Unique Values *	Null Values	Max	Min	Mean	Comment	Classifications	Terms	Classifications
▼	lat	age	int	21	18	49	1	23.66	Nam venenatis elit et. +1	a very long term is b... +7	
▼	lat	cabin	string	9	0				Nam venenatis elit et. +1	a very long term is b... +7	
▼	lat	embarked	string	3	0				dp_ukpassportnumbe +2	a very long term is b... +7	
▼	lat	fare	float	35	0	262.38	23.78		dp_ukpassportnumbe +1	a very long term is b... +7	
▼	lat	name	string	54	0				dp_ukpassportnumbe +6	a very long term is b... +7	
▼	lat	parch	int	3	0	2	0.42		dp_ukpassportnumbe +1	a very long term is b... +7	
▼	lat	passengerid	int	50	0	53	1	27	dp_ukpassportnumbe +2	a very long term is b... +7	
▼	lat	pclass	int	3	0	3	1	2.42	dp_ukpassportnumbe	a very long term is b... +7	
▼	lat	sex	string	2	0				dp_ukpassportnumbe	a very long term is b... +7	
▼	lat	sibsp	int	4	0	8	0.43			a very long term is b... +7	
▼	lat	survived	int	2	0	1	0.72			a very long term is b... +7	
▼	lat	ticket	string	48	0					a very long term is b... +7	

Searching for assets using glossary terms

You can search for the datasets using the Glossary terms filter available on the Data Catalog search page.

 **CLOUDERA**
Data Catalog

 **Search**

 Datasets

 Bookmarks

 Profilers

 Atlas Tags

→ Get Started

ⓘ Help



Data Catalog / Search

- [NA](#)
- [NA](#)
- [NA](#)

Filters

TYPE [Clear](#) 

Hive Table

HBase Table

[+ Add New Value](#)

OWNERS [Clear](#) 

atlas

dpprofiler

hive

public

ENTITY TAG [Clear](#) 

[+ Add New Value](#)

GLOSSARY TERMS [Clear](#) 

[+ Add New Value](#)

Additional search options for asset types

Using Data Catalog, you can add or edit asset description values to search for data assets across both Data Catalog and Atlas services by using the asset content.

In the Asset Details page for each asset type that you select, you can add or edit comment and description fields. For each asset type in Data Catalog, you can add or edit comments or include a description. Including these values for the selected asset helps you to identify your chosen asset when you perform the search operation.

Later, using the same set of values (comment or description), you can search for the asset types in Atlas.



Note: The comment and description options are supported only for Hive table and Hive Column assets. For other asset types, only the description option is supported.

Data Catalog / Asset Details

ww_customers Atlas

Properties

Type: HIVE TABLE
of Columns: 40
Data Lake:
Datasets: 0
Owner: hive
Created On: Tue Mar 09 2021 10:48:45 GMT+0530 (India Stand...
Last Access Time: Tue Mar 09 2021 10:48:45 GMT+0530 (Indi...
Table Type: EXTERNAL_TABLE
Database: hortoniabank
DB Catalog:
Parent: hortoniabank

Qualified Name
hortoniabank.ww_customers@cm

Comment
[+ Add Comment](#)

Description
[+ Add Description](#)

Profilers | 2

Cluster Sensitivity Profiler Run
Last run: 8 hours ago | Status: SUCCESS
Next Schedule Run: Thursday at 11:50 AM

Hive Column Profiler Run
Last run: 8 hours ago | Status: SUCCESS
Next Schedule Run: Tomorrow at 5:30 PM

Click + besides Comment and Description to include the respective values.

Data Catalog / Asset Details

ww_customers Atlas

Properties Cancel Save

Type: HIVE TABLE
of Columns: 40
Data Lake:
Datasets: 0
Owner: hive
Created On: Tue Mar 09 2021 10:48:45 GMT+0530 (India Stand...
Last Access Time: Tue Mar 09 2021 10:48:45 GMT+0530 (Indi...
Table Type: EXTERNAL_TABLE
Database: hortoniabank
DB Catalog:
Parent: hortoniabank

Qualified Name
hortoniabank.ww_customers@cm

Comment

Description

Profilers | 2

Cluster Sensitivity Profiler Run
Last run: 9 hours ago | Status: SUCCESS
Next Schedule Run: Thursday at 11:50 AM

Hive Column Profiler Run
Last run: 8 hours ago | Status: SUCCESS
Next Schedule Run: Tomorrow at 5:30 PM

Click Save to save the changes.

Data Catalog / Asset Details

ww_customers Atlas

Asset details were updated successfully.

Properties

Type: HIVE TABLE
of Columns: 40
Data Lake:
Datasets: 0
Owner: hive
Created On: Tue Mar 09 2021 10:48:45 GMT+0530 (India Stand...
Last Access Time: Tue Mar 09 2021 10:48:45 GMT+0530 (Indi...
Table Type: EXTERNAL_TABLE
Database: hortoniabank
DB Catalog:
Parent: hortoniabank

Qualified Name
hortoniabank.ww_customers@cm

Comment
passport_number

Description
visa_number

Profilers | 2

Cluster Sensitivity Profiler Run
Last run: 9 hours ago | Status: SUCCESS
Next Schedule Run: Thursday at 11:50 AM

Hive Column Profiler Run
Last run: 8 hours ago | Status: SUCCESS
Next Schedule Run: Tomorrow at 5:30 PM



Note: You can also edit the already saved valued by clicking the  icon.

Clicking on the Atlas button will navigate to the corresponding Atlas asset page as displayed.



ww_customers (hive_table)

Classifications: 

Terms: 

Properties Lineage Relationships Classifications Audits Schema

Technical properties 

columns (40) 

```
title
givenname
middleinitial
```

comment passport_number

createTime 03/09/2021 10:48:45 AM (IST)

db hortoniabank 

dcProfiledData 

```
{
  samplePercent: "100.0",
  rowCount: 50000,
}
```

description visa_number

User-defined properties 

Labels 

Business Metadata 

[Switch to Beta UI](#)

Searching for assets in Data Catalog using additional search options

Consider a scenario in Data Catalog, where you select a data asset type and under the Asset Details page, you insert a comment and provide the description for the selected asset.

Navigate to the Data Catalog search query pane and enter the Comment and Description value(s) that you saved for the selected asset type in Data Catalog. The result page displays the asset type that you added for the Comment and Description fields in Data Catalog.

When you query for the entered Comment value for the selected asset type in Data Catalog, the relevant asset type is displayed in the search result page.

CloudERA Data Catalog

Data Catalog / Search

Search

Atlas Ranger

Data Lakes

	1
	0
	NA
	0

Filters

TYPE

Hive Table

HBase Table

[Add New Value](#) [Clear](#)

OWNERS

hive [Clear](#)

DATABASE

information_schema

sys

Setup the Profiler for [redacted]

Profiler runs data profiling operations as a pipeline on data located in the data lake which helps to view the profiled results for assets. Setting up a Profiler launches a cluster with various services like HDFS, YARN, Livy, Spark, HMS, Profiler Manager Service, and Profiler Scheduler Service. [Get Started](#)

cloudera-kc3fw4 | 1 [Action](#)

Type	Name	Qualified Name	Created On	Owner	Source
<input type="checkbox"/> Hive Table	role_map	sys.role_map@cm	Fri Aug 27 2021	hive	hive

Clicking on the asset type in Data Catalog displays the comment and description values as it was assigned in Data Catalog.

The screenshot shows the 'role_map' asset details page. The 'Properties' section includes:

- Type: HIVE TABLE
- # of Columns: 8
- Data Lake: [Redacted]
- Datasets: 0
- Owner: hive
- Created On: Fri Aug 27 2021 10:51:33 GMT+0530 (India Standard Time)
- Last Access Time: Fri Aug 27 2021 10:51:33 GMT+0530 (India Standard Time)
- Table Type: EXTERNAL_TABLE
- Database: sys
- DB Catalog: cm
- Parent: sys

The 'Comment' field contains 'Visa Number' and the 'Description' field contains 'Passport Number'. Both fields are highlighted with a red box. The 'Classifications' section shows 'Managed', 'System', and 'Propagated' buttons. The 'Terms' section has an 'Add Terms' button. The 'Lineage' section has a filter by 'Depth: 3' and 'Process Node: Hide'.

When you query for the entered Description value for the selected asset type in Data Catalog, the relevant asset type is displayed in the search result page.

The screenshot shows the search results page for 'Passport Number'. The search bar contains 'Passport Number'. The results table shows one result:

Type	Name	Qualified Name	Created On	Owner	Source
<input type="checkbox"/>	Hive Table	role_map	sys.role_map@cm	Fri Aug 27 2021	hive

The search bar and the 'role_map' link in the table are highlighted with a red box. The 'Filters' section on the left shows 'TYPE' with 'Hive Table' selected, and 'OWNERS' with 'hive' selected. The 'DATABASE' section shows 'information_schema' and 'sys' as options.

Your search query displays the results.

Accessing Tables based on Ranger policies

In Data Catalog service, when a table (in blue color link) is clicked, the Asset Details view page is displayed.

If a user is not authorized to click or view table details, it implies that the user permissions have not been set-up in the Ranger.



Note: The user permissions to view table details are configured in Ranger.

As seen in the following diagram, if users are not able to view the table details, a message appears next to the same table "Some information might not be available to unauthorised users".

The screenshot shows a search result for the table 'ww_customers *'. The table is listed as a 'hive table' with a creation date of 'Created -NA-' and an owner of 'Owner -NA-'. The source is 'hive'. A message below the table states: '* Some information might not be available to unauthorised users'. On the left, there is a 'Filters' section with 'TYPE' set to 'hive table' and an 'Add New Value' link.

In the next example diagram, tables that have the permissions to view are embedded in blue color link. And the ones that do not have read permissions are visible in grey.

The screenshot shows a list of tables in the Data Catalog. The tables are listed with their names, schemas, creation dates, owners, and sources. The table names are color-coded: blue for tables with read permissions and grey for those without. The tables are:

Table Name	Schema	Created	Owner	Source
scheduled_queries	/information_schema	Tue Apr 07 2020	hive	hive
schemata	/information_schema	Tue Apr 07 2020	hive	hive
table_stats_view	/sys	Tue Apr 07 2020	hive	hive
scheduled_executions	/information_schema	Tue Apr 07 2020	hive	hive
andromeda	/-	-	-	hive
milky	/-	-	-	hive
bear	/-	-	-	hive
n170	/-	-	-	hive
umajor5	/-	-	-	hive

Creating Classification for selected assets

You can create a classification that can be associated with an asset.

1. From Data Catalog > navigate to the search page.
2. You can perform one or more of the following:
 - Select Add Classifications on action button in search page
 - Select Add classification in classification widget on Asset Details page.
3. On the Add Classification slider, click Create button.
4. Enter the necessary values in the fields and click the Create button.

Adding Classifications / Terms for selected assets

You can add classification or terms that can be associated with an asset.

Procedure

1. From Data Catalog > navigate to the search page.
2. You can perform one or more of the following:
 - a) Select Add Classifications / Terms on action button in the search page.
 - b) Select Add Classifications / Terms in classification widget on Asset Details page.
3. On the Add Classifications / terms slider, click on the Add icon against classification / term.
4. Enter other values in the fields, if required and click Save.

Additional Entity type selection for searching Assets

Using the Data Catalog service, you can search for assets by using the entity types.

Data Catalog users can search and discover assets of more types. Users can search assets of types just like they do for Hive Table with some restrictions.

Supported entity types include:

- AWS S3 Object
- AWS S3 Bucket
- AWS S3 Pseudo Dir
- HBase Table
- HBase Column Family
- HBase Namespace
- HDFS Path
- Hive DB
- Hive Table
- Hive Column
- ML Project
- ML Model Build
- ML Model Deployment
- NiFi Flow
- NiFi Data
- Impala Process
- Impala Column Lineage
- Impala Process Execution
- Kafka Topic
- RDBMS DB
- RDBMS Column
- RDBMS Foreign Key
- RDBMS Index
- RDBMS Instance
- RDBMS Table
- Spark Process
- Spark Application
- Spark Column
- Spark Column Lineage

- Spark DB
- Spark ML Directory
- Spark ML Model
- Spark ML Pipeline
- Spark Process Execution
- Spark Table

Selecting a type triggers a search query for that type. Currently two types of entities are supported but totally about twelve types of generic entities can be selected to search for assets depending on the data lake.

Owners data is derived from the response received from type based queries.

The following example diagrams depict the entity type selection search results.

Search

The screenshot shows a search interface with a search bar at the top. Below it, there are two tabs: 'Atlas' and 'Ranger'. A green notification banner at the top of the results area says 'Profiler Cluster is provisioned successfully'. On the left, there is a sidebar with 'Data Lakes' (157), 'Filters', 'TYPE' (with 'Hive Table' selected and highlighted by a red box), and 'OWNERS' (listing users like csso_mhussain, csso_santhosh, hive, hrt_l1, hrt_0a). The main results area is a table with columns: Type, Name, Qualified Name, Created On, Owner, and Source. The table lists various Hive Tables such as global_privs, partition_key_vals, partition_keys, tbls, sort_cols, skewed_string_list_values, skewed_values, compaction_queue, key_constraints, wm_mappings, wm_resourceplans, and wm_triggers.

Type	Name	Qualified Name	Created On	Owner	Source	
<input type="checkbox"/>	Hive Table	global_privs	sys.global_privs@cm	Mon Oct 04 2021	hive	hive
<input type="checkbox"/>	Hive Table	partition_key_vals	sys.partition_key_vals@cm	Mon Oct 04 2021	hive	hive
<input type="checkbox"/>	Hive Table	partition_keys	sys.partition_keys@cm	Mon Oct 04 2021	hive	hive
<input type="checkbox"/>	Hive Table	tbls	sys.tbls@cm	Mon Oct 04 2021	hive	hive
<input type="checkbox"/>	Hive Table	sort_cols	sys.sort_cols@cm	Mon Oct 04 2021	hive	hive
<input type="checkbox"/>	Hive Table	skewed_string_list_values	sys.skewed_string_list_values@cm	Mon Oct 04 2021	hive	hive
<input type="checkbox"/>	Hive Table	skewed_values	sys.skewed_values@cm	Mon Oct 04 2021	hive	hive
<input type="checkbox"/>	Hive Table	compaction_queue	sys.compaction_queue@cm	Mon Oct 04 2021	hive	hive
<input type="checkbox"/>	Hive Table	key_constraints	sys.key_constraints@cm	Mon Oct 04 2021	hive	hive
<input type="checkbox"/>	Hive Table	wm_mappings	sys.wm_mappings@cm	Mon Oct 04 2021	hive	hive
<input type="checkbox"/>	Hive Table	wm_resourceplans	sys.wm_resourceplans@cm	Mon Oct 04 2021	hive	hive
<input type="checkbox"/>	Hive Table	wm_triggers	sys.wm_triggers@cm	Mon Oct 04 2021	hive	hive

Search

The screenshot shows a search interface with a search bar at the top. Below it, there are two tabs: 'Atlas' and 'Ranger'. A green notification banner at the top of the results area says 'Profiler Cluster is provisioned successfully'. On the left, there is a sidebar with 'Data Lakes' (5), 'Filters', 'TYPE' (with 'HBase Table' selected and highlighted by a red box), and 'OWNERS' (listing users like atlas, hbase). The main results area is a table with columns: Type, Name, Qualified Name, Created On, Owner, and Source. The table lists various HBase Tables such as atlas_janus, t1, t2, ATLAS_ENTITY_AUDIT_EVENTS, and hbase:acl.

Type	Name	Qualified Name	Created On	Owner	Source	
<input type="checkbox"/>	HBase Table	atlas_janus	default:atlas_janus@cm	Mon Oct 04 2021	atlas	hbase
<input type="checkbox"/>	HBase Table	t1	default:t1@cm	Tue Jun 09 2020	hbase	hbase
<input type="checkbox"/>	HBase Table	t2	default:t2@cm	Tue Jun 09 2020	hbase	hbase
<input type="checkbox"/>	HBase Table	ATLAS_ENTITY_AUDIT_EVENTS	default:ATLAS_ENTITY_AUDIT_EVENTS@cm	Fri Jun 05 2020	atlas	hbase
<input type="checkbox"/>	HBase Table	hbase:acl	hbase:acl@cm	Tue Jun 09 2020	hbase	hbase

Viewing Data Asset Details

The Asset Details page comprises four tabs (Overview, Schema, Policy, and Audit).

To access the Asset Details page, click an asset in the Data Catalog Search page. This brings you to the Overview tab, the first of the four tabs that form the Asset Details page.

- Overview: Displays an overview for the data asset.
 - Table properties: Number of rows, number of columns, number of partitions, owner, and tags
 - Lineage: Shows the chain of custody for the data from relevant metadata repositories such as Apache Atlas. Lineage shows both upstream paths (lineage) into and downstream paths (impact) out of a given asset.
- Schema: Displays the schema of the data asset for structured data (such as Hive tables) from the relevant metadata repositories (such as Atlas).
- Policy: The policy view shows security (authorization) policies defined on assets such as those present in Apache Ranger. It includes both resource (physical asset based) as well as classification based policies
- Audit: The data asset audit logs page shows the most recent access audits from Apache Ranger.

Viewing Data Assets

The Data Asset Overview page displays all the Apache Atlas metadata associated with a particular data asset.

About this task

The Data Asset Overview page displays:

Asset properties: Displays properties information relevant to asset type, like in case of Hive table - Number of rows, number of columns, number of partitions, and the owner.

From the Data Catalog search page, click to select a data asset.

The Asset Overview window opens.

The following matrix captures the supported fields for different asset types:

Asset Type	Lineage	Tagging	Access Metrics	Schema	Policy	Audit	Atlas Punch out
aws_S3_bucket	Yes	Yes	Not Supported	Not Supported	Not Supported	Not Supported	Yes
aws_S3_Object	Yes	Yes	Not Supported	Not Supported	Not Supported	Not Supported	Yes
aws_S3_pseudo_dir	Yes	Yes	Not Supported	Not Supported	Not Supported	Not Supported	Yes
aws_s3_v2_object	Yes	Yes	Not Supported	Not Supported	Not Supported	Yes	Yes
aws_s3_v2_directory	Yes	Yes	Not Supported	Not Supported	Not Supported	Yes	Yes
aws_s3_v2_bucket	Yes	Yes	Not Supported	Not Supported	Not Supported	Yes	Yes
adls_gen2_directory	Yes	Yes	Not Supported	Not Supported	Not Supported	Yes	Yes
adls_gen2_blob	Yes	Yes	Not Supported	Not Supported	Not Supported	Yes	Yes

Asset Type	Lineage	Tagging	Access Metrics	Schema	Policy	Audit	Atlas Punch out
adls_gen2_container	Yes	Yes	Not Supported	Not Supported	Not Supported	Yes	Yes
Hive DB	Not Supported	Yes	Not Supported	Not Supported	Yes	Yes	Yes
Hive Table	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Hive Column	Yes	Yes	Not Supported	Not Supported	Yes	Yes	Yes
Hbase Namespace	Yes	Yes	Not Supported	Not Supported	Yes	Yes	Yes
Hbase Table	Yes	Yes	Not Supported	Yes	Yes	Yes	Yes
Hbase Column Family	Yes	Yes	Not Supported	Not Supported	Yes	Yes	Yes
impala_process	Yes	Yes	Not Supported	Not Supported	Not Supported	Not Supported	Yes
impala_column_lineage	Yes	Yes	Not Supported	Not Supported	Not Supported	Not Supported	Yes
impala_process_execution	Yes	Yes	Not Supported	Not Supported	Not Supported	Not Supported	Yes
ML_Project	Yes	Yes	Not Supported	Not Supported	Not Supported	Not Supported	Yes
ML_Model_Build	Yes	Yes	Not Supported	Not Supported	Not Supported	Not Supported	Yes
ML_Model_Deploy	Yes	Yes	Not Supported	Not Supported	Not Supported	Not Supported	Yes
rdbms_db	Yes	Yes	Not Supported	Not Supported	Not Supported	Not Supported	Yes
rdbms_column	Yes	Yes	Not Supported	Not Supported	Not Supported	Not Supported	Yes
rdbms_foreign_key	Yes	Yes	Not Supported	Not Supported	Not Supported	Not Supported	Yes
rdbms_index	Yes	Yes	Not Supported	Not Supported	Not Supported	Not Supported	Yes
rdbms_instance	Yes	Yes	Not Supported	Not Supported	Not Supported	Not Supported	Yes
rdbms_table	Yes	Yes	Not Supported	Not Supported	Not Supported	Not Supported	Yes
spark_process	Yes	Yes	Not Supported	Not Supported	Not Supported	Not Supported	Yes
spark_application	Yes	Yes	Not Supported	Not Supported	Not Supported	Not Supported	Yes
spark_column	Yes	Yes	Not Supported	Not Supported	Not Supported	Not Supported	Yes
spark_column_lineage	Yes	Yes	Not Supported	Not Supported	Not Supported	Not Supported	Yes
spark_db	Yes	Yes	Not Supported	Not Supported	Not Supported	Not Supported	Yes
spark_ml_directory	Yes	Yes	Not Supported	Not Supported	Not Supported	Not Supported	Yes

Asset Type	Lineage	Tagging	Access Metrics	Schema	Policy	Audit	Atlas Punch out
spark_ml_model	Yes	Yes	Not Supported	Not Supported	Not Supported	Not Supported	Yes
spark_ml_pipeline	Yes	Yes	Not Supported	Not Supported	Not Supported	Not Supported	Yes
spark_process_execution	Yes	Yes	Not Supported	Not Supported	Not Supported	Not Supported	Yes
spark_table	Yes	Yes	Not Supported	Not Supported	Not Supported	Not Supported	Yes

View Data Asset Schema

From the Asset Details Schema page, you can view the schema of the data asset for structured data (such as Hive tables) from the relevant metadata repositories (such as Atlas).

Procedure

1. From the Data Catalog search page, select an asset.
The Asset Overview window opens.
2. Click Schema.
The Schema table shows the data asset schema as retrieved from Apache Atlas.
3. (Optional) To edit tags:
 - a) Click Edit Tags.
 - b) Click the (+) icon.
 - c) Select or deselect the tags you choose, then click Save.

You can now manage and edit tags at the table level.

Navigating from the container asset to the parent asset from Asset Details page

A generic Assets Details page is available for container data types like buckets and databases.

A Contents tab (similar to the Schema tab) lists all the contents of the selected entity. Clicking on any element available in the selected entity list navigates you to the Asset Details page.

Data Catalog / Asset Details

The screenshot shows the 'default' asset details page. It includes a 'Properties' section with details like Type (HBASE NAMESPACE), Data Lake, Owner (atlas), and Status (ACTIVE). Below are 'Classifications' (Managed, System, Propagated) and 'Terms' (new_term1@new_glossary). The 'Content' tab is selected, showing a table of contained entities.

Type	Name	Location	Created On	Owner	Source
hbase_table	ATLAS_ENTITY_AUDIT_EVENTS	/default	Wed Apr 07 2021	atlas	hbase

For example, for a database entity having a list of tables, clicking on any listed table navigates to the Asset Details page of the same table. Helps you understand the parent-child relationship as far as asset management is concerned. The Contents tab displays entities that are contained within assets of container entity types. The entities in the table of Contents tab are clickable, which will allow you to navigate to the Asset Details page of these contained assets.

The following table lists the entity types, their parent, and contents.

Type	Parent	Content
Hive DB	-	Hive Table
HBase Namespace	-	HBase Table
ML Project	-	ML Model Build
ML Model Build	ML Project	ML Model Deployment
AWS S3 Bucket	-	AWS S3 Pseudo Dir
AWS S3 Pseudo Dir	AWS S3 Bucket	AWS S3 Object
RDBMS Instance	-	RDBMS DB
RDBMS DB	RDBMS Instance	RDBMS Table

View Authorization Policies on a Data Asset

The Asset Details Policy page displays all the Apache Ranger policy details associated with a particular data asset. This helps you understand how data access is secured and protected: what users can see what data (or metadata) under what conditions (security policies, data protection, and anonymization).

Procedure

1. From the Data Catalog search page, select a data asset.
The Asset Overview window opens.
2. Click the Policy tab.
The Policy table shows the data asset policies as retrieved from Apache Ranger.

View Data Asset Audit Logs

The Asset Details Audit page displays all the Apache Ranger audit events associated with a particular data asset. This helps you to view who has accessed what data from a forensic audit or compliance perspective, and to visualize access patterns and identify anomalies.

Procedure

1. From the Data Catalog search page, select a data asset.
The Asset Overview window opens.
2. Click the Audit tab.
The Audit table shows the most recent raw audit event data by type of access and access outcome (authorized/unauthorized).
3. (Optional) You can filter the audit results by Access Type or Result.
Access type: SELECT, UPDATE, CREATE, DROP, ALTER, INDEX, READ, WRITE.
Result: ALLOWED, DENIED.

Navigation Support for Hive entity within Lineage

When you click a Hive entity within lineage, the Asset Details page of the selected Hive entity is displayed.

Previously, when you clicked on any entity for which slider information was available, a slider would display the entity details. As of now, as seen in the corresponding images, the Asset Details page of the Hive entity is displayed. The option selected in Depth drop-down and Show Process nodes are now displayed on the upper-left corner of the Lineage module.

Data Catalog / Asset Details

The screenshot displays the 'Asset Details' page for a data asset. The top section includes metadata such as 'Data Lake: cloudera-kc3fw4', 'Owner: hive', and 'Table Type: EXTERNAL_TABLE'. Below this, there are sections for 'Classifications' (Managed, System, Propagated) and 'Terms'. A navigation bar shows 'Overview', 'Schema', 'Metadata Audits', 'Policy', and 'Access Audits'. The 'Lineage' section is active, showing a filter for 'Depth: 3' and 'Process Node: Hide'. A lineage diagram shows a flow from '/warehouse/tables...' to 'role_map', with an information icon (i) next to the 'role_map' node.

Alternatively, if you do not want to navigate away from the current page and want to view the information with

respect to any entity, hover on the entity and click the information icon  to view the details.

The screenshot depicts the slider information for the clicked entity:

Data Catalog / Asset Details

Table Type: EXTERNAL_TABLE
Database: sys
DB Catalog: cm
Parent: sys

[Add Description](#)

Classifications

Managed System Propagated

[Add Classification](#)

Terms

[Add Terms](#)

[Overview](#)
[Schema](#)
[Metadata Audits](#)
[Policy](#)
[Access Audits](#)

Lineage

Filter By: Depth: 9 Process Node: Show

→ Lineage → Impact → Replication →

partition_params

Guid: [redacted]

Type Name: hive_table

Classifications(0): --

Owner: hive

Qualified Name: sys.partition_params@cm

Created On: Fri Aug 27 2021 10:51:31 GMT+0530 (India Standard Time)

Last Access Time: Fri Aug 27 2021 10:51:31 GMT+0530 (India Standard Time)

Table Type: EXTERNAL_TABLE

Database: sys

DB Catalog: cm

Adding Hive asset to one or more datasets on Asset Details screen

On the Asset Details screen, users are provided with an option to add the asset to the dataset as shown in the diagram.

Data Catalog / Asset Details

campaigns

[Atlas](#)

[Add to Dataset](#)

Properties

Type: HIVE TABLE
of Columns: 5
Data Lake: [redacted]
Datasets: 0
Owner: hive
Created On: Wed Apr 07 2021 15:27:03 GMT+0530 (India Stand...
Last Access Time: Wed Apr 07 2021 15:27:03 GMT+0530 (Indi...
Table Type: EXTERNAL_TABLE
Database: marketing
DB Catalog: cm
Parent: marketing

Qualified Name
marketing.campaigns@cm

Comment
This table contains marketing campaigns information.

Description
[+ Add Description](#)

Profilers | 2

Cluster Sensitivity Profiler
Last run: 2 hours ago | Status: SUCCESS
Next Schedule Run: NA, Profiler is Disabled. [Run](#)

Hive Column Profiler
Last run: 2 hours ago | Status: SUCCESS
Next Schedule Run: NA, Profiler is Disabled. [Run](#)

Classifications

Managed System Propagated

[+ Add Classification](#)

Terms | 1

[new_term1@new_glossary](#)

[Overview](#)
[Schema](#)
[Metadata Audits](#)
[Policy](#)
[Access Audits](#)

Lineage

[T](#) [Q](#) [Q](#) [v](#)

The Add to Dataset window provides an option to add the asset into one or more existing datasets or even create a new one.

Datasets that already contain the asset are disabled and marked as checked. Datasets which are currently in edit state are disabled and marked with a *.

Data Catalog / Asset Details

campaigns

Properties

Type: **HIVE TABLE**
 # of Columns: **5**
 Data Lake: **[REDACTED]**
 Datasets: **0**
 Owner: **hive**
 Created On: **Wed Apr 07 2021 15:27:03 GMT+0530 (India Stand...)**
 Last Access Time: **Wed Apr 07 2021 15:27:03 GMT+0530 (Indi...)**
 Table Type: **EXTERNAL_TABLE**
 Database: **marketing**
 DB Catalog: **cm**
 Parent: **marketing**

Qualified Name
marketing.campaigns@cm

Comment
This table contains marketing campaigns information.

Description
[+ Add Description](#)

Classifications

Managed System Propagated

[+ Add Classification](#)

Terms | 1
[new_term1@new_glossary](#)

Overview Schema Metadata Audits Policy Access Audits

Lineage

/warehouse/tables... campaigns

Add to Dataset

Search by Name Search by Tag [+ New Dataset](#)

<input type="checkbox"/>	Name↑	Owner↑	# of Assets↑
<input checked="" type="checkbox"/>	Credit card	Srinivas Sudhindra	1
<input type="checkbox"/>	Town1234	Srinivas Sudhindra	1
<input checked="" type="checkbox"/>	City	Srinivas Sudhindra	1
<input type="checkbox"/>	Visa	Srinivas Sudhindra	1
<input checked="" type="checkbox"/>	SSN1	Srinivas Sudhindra	1
<input type="checkbox"/>	Passport123	Srinivas Sudhindra	1

[Add Asset](#) [Cancel](#)

Users can search for an existing dataset by name or by tags applied on the dataset. Users can select one or more datasets from the list and then click on the Add Asset button which adds the asset to these dataset(s).

Data Catalog / Asset Details

warehouse

Properties

Type: **HIVE TABLE**
 # of Columns: **14**
 Data Lake: **[REDACTED]**
 Datasets: **0**
 Owner: **hive**
 Created On: **Wed Apr 07 2021 12:58:54 GMT+0530 (India Stand...)**
 Last Access Time: **Wed Apr 07 2021 12:58:54 GMT+0530 (Indi...)**
 Table Type: **EXTERNAL_TABLE**
 Database: **test_dss_db**
 DB Catalog: **cm**
 Parent: **test_dss_db**

Qualified Name
test_dss_db.warehouse@cm

Comment
[+ Add Comment](#)

Description
[+ Add Description](#)

Classifications

Managed System Propagated

[+ Add Classification](#)

Terms
[+ Add Terms](#)

Overview Schema Metadata Audits Policy Access Audits

Lineage

Add to Dataset

New Dataset

Name*

Description*

Tags
 Add tags to your dataset for context and subsequent lookup

Public

[Create](#) [Cancel](#)

There are instances, where there are no datasets present or the user just wants to create a new dataset to add the asset. In that case, the user can click on the New Dataset button which opens up a new dataset form. Once the user fills in the form and clicks on the Create button, a new dataset with the given properties is created and the asset is added to it automatically. This is reflected in the datasets list where the newly added dataset is highlighted.

Data Catalog / Asset Details

warehouse

Properties

Type: HIVE TABLE
 # of Columns: 14
 Data Lake: [redacted]
 Datasets: 6
 Owner: [redacted]
 Created On: Mon May 11 2020 13:02:22 GMT+0530 (India Stan...
 Last Access Time: Mon May 11 2020 13:02:22 GMT+0530 (Indi...
 Table Type: EXTERNAL_TABLE
 Database: [redacted]
 DB Catalog: cm
 Parent: [redacted]

Qualified Name
 [redacted]

Comment
 + Add Comment

Description
 + Add Description

Classifications

+ Add Classification

Overview Schema Metadata Audits Policy Access Audits

Lineage

Add to Dataset

Search by Name 🔍 Search by Tag ▾ + New Dataset

<input type="checkbox"/>	Name↑	Owner↑	# of Assets↑
<input checked="" type="checkbox"/>	Link test	Srinivas Sudhindra	1
<input checked="" type="checkbox"/>	Demotest	Srinivas Sudhindra	1
<input checked="" type="checkbox"/>	Social Security Number	Srinivas Sudhindra	1
<input checked="" type="checkbox"/>	Visa number	Srinivas Sudhindra	1
<input type="checkbox"/>	passport12	Srinivas Sudhindra	0
<input type="checkbox"/>	Demo1234	Srinivas Sudhindra	0
<input checked="" type="checkbox"/>	Test1357	Srinivas Sudhindra	2
<input type="checkbox"/>	Demo	Srinivas Sudhindra	1
<input checked="" type="checkbox"/>	Hive123	Srinivas Sudhindra	2

Feedback

Viewing Atlas Entity Audits

In Data Catalog, Atlas audits help Data Stewards to identify and track the entity changes or modifications that are performed over a period of time.

Information about the Atlas entity audit events are displayed for each entity in the Asset Details page in Data Catalog. Using this information, Data Stewards can distinguish between entity audits and data audits that emanate from Ranger.

On the Asset Details page, a new tab called Metadata Audits displays information related to the selected entity type and about the events that occurred based on the user activities.

Overview Schema **Metadata Audits** Policy Access Audits

Clicking on Metadata Audits, tab, you can view manage information about:

- The user who made the changes to the specific entity
- The time when the entity was changed
- The kind of change that was made to the entity
- Any other relevant changes pertaining to the audit entries

The changes that can be identified for:

- Created entities and related updates
- Tagged entities
- Labeled entities
- Export and Import operations

For example, the following image displays information about the Atlas audit events that are performed by each Atlas user that is displayed in the Asset Details page in Data Catalog.

Data Catalog / Asset Details

ATLAS_ENTITY_AUDIT_EVENTS [Atlas](#)

Properties

Type: HBASE TABLE
 Data Lake:
 Owner: atlas
 Created On: Wed Apr 07 2021 10:50:42 GMT+0530 (India Standard Time)
 Modified Time: Wed Apr 07 2021 10:50:42 GMT+0530 (India Standard Time)
 Namespace GUID: f4658406-3a4b-4076-afb0-6e74745934b6
 URI: ATLAS_ENTITY_AUDIT_EVENTS
 Parent: default

Qualified Name
default:ATLAS_ENTITY_AUDIT_EVE ...

Description
ATLAS_ENTITY_AUDIT_EVENTS

Classifications Managed System Propagated

+ Add Classification

Terms

+ Add Terms

Overview Schema Metadata Audits Policy Access Audits

≡ ≡

User	Timestamp	Actions
atlas	Wed Apr 07 2021 10:50:48 GMT+0530 (India Standard Time)	Entity created

Feedback

Clicking on any line item displays the JSON format, which is directly derived from Atlas, in other words the source of data available in Atlas.

Data Catalog / Asset Details

ATLAS_ENTITY_AUDIT_EVENTS [Atlas](#)

Properties

Type: HBASE TABLE
 Data Lake:
 Owner: atlas
 Created On: Wed Apr 07 2021 10:50:42 GMT+0530 (India Standard Time)
 Modified Time: Wed Apr 07 2021 10:50:42 GMT+0530 (India Standard Time)
 Namespace GUID: f4658406-3a4b-4076-afb0-6e74745934b6
 URI: ATLAS_ENTITY_AUDIT_EVENTS
 Parent: default

Qualified Name
default:ATLAS_ENTITY_AUDIT_EVE ...

Description
ATLAS_ENTITY_AUDIT_EVENTS

Classifications Managed System Propagated

+ Add Classification

Terms

+ Add Terms

Overview Schema Metadata Audits Policy Access Audits

≡ ≡

User	Timestamp	Actions
atlas	Wed Apr 07 2021 10:50:48 GMT+0530 (India Standard Time)	Entity created

Created:

```
{
  "typeName": "hbase_table",
  "attributes": {
    "owner": "atlas",
    "isNormalizationEnabled": false,

```

Feedback

Use the toggle icon (on the top-right corner) for viewing Atlas Audits in different formats. By default, you can view Metadata Audits in tabular format in the Asset Details page and when you toggle the view icon, you can view the Timeline format. The events are listed as timelines in this format.

Data Catalog / Asset Details

ATLAS_ENTITY_AUDIT_EVENTS [Atlas](#)

Properties

Type: HBASE TABLE
 Data Lake:
 Owner: atlas
 Created On: Wed Apr 07 2021 10:50:42 GMT+0530 (India Standard Time)
 Modified Time: Wed Apr 07 2021 10:50:42 GMT+0530 (India Standard Time)
 Namespace GUID: f4658406-3a4b-4076-afb0-6e74745934b6
 URI: ATLAS_ENTITY_AUDIT_EVENTS
 Parent: default

Qualified Name
 default:ATLAS_ENTITY_AUDIT_EVE ...

Description
 ATLAS_ENTITY_AUDIT_EVENTS

Classifications Managed System Propagated

+ Add Classification

Terms

+ Add Terms

Overview Schema Metadata Audits Policy Access Audits

Timeline Timeline List

Wed Apr 07 2021 10:50:48 GMT+0530 (India Standard Time) atlas
Entity created

Feedback

Clicking on a user in the Timeline format displays the JSON data, which is again derived from Atlas.

Data Catalog / Asset Details

ATLAS_ENTITY_AUDIT_EVENTS [Atlas](#)

Properties

Type: HBASE TABLE
 Data Lake:
 Owner: atlas
 Created On: Wed Apr 07 2021 10:50:42 GMT+0530 (India Standard Time)
 Modified Time: Wed Apr 07 2021 10:50:42 GMT+0530 (India Standard Time)
 Namespace GUID: f4658406-3a4b-4076-afb0-6e74745934b6
 URI: ATLAS_ENTITY_AUDIT_EVENTS
 Parent: default

Qualified Name
 default:ATLAS_ENTITY_AUDIT_EVE ...

Description
 ATLAS_ENTITY_AUDIT_EVENTS

Classifications Managed System Propagated

+ Add Classification

Terms

+ Add Terms

Overview Schema Metadata Audits Policy Access Audits

Timeline Timeline List

Wed Apr 07 2021 10:50:48 GMT+0530 (India Standard Time) atlas
Entity created

Details Close

atlas

Snapshot

```
Created:
{
  "typeName": "hbase_table",
  "attributes": {
    "owner": "atlas",
    ...
  }
}
```

Feedback

Managing Profilers

The Data Catalog profiler engine runs data profiling operations as a pipeline on data located in multiple data lakes. These profilers create metadata annotations that summarize the content and shape characteristics of the data assets.

Table 1: List of built-in profilers

Profiler Name	Description
Cluster Sensitivity Profiler	A sensitive data profiler- PII, PCI, HIPAA, etc.
Ranger Audit Profiler	A Ranger audit log summarizer.
Hive Column Profiler	Provides summary statistics like Maximum, Minimum, Mean, Unique, and Null values at the Hive column level.

Related Information

[Understanding the data catalog profiler](#)

[Understanding the sensitive data profiler](#)

[Understanding the ranger audit profiler](#)

Data Catalog profiler data testing

You must note the important information about profiler services.

The Data Catalog profilers are not tested at par with the Hive scale, The following dataset has been validated and works as expected

- DataHub Master: m5.4xlarge
- Hive tables: 3000 Hive assets
- Total Number of assets (including Hive columns, tables, databases) : 1,000,000
- Total Data Size = 1 GB
- Partitions on Hive tables: Around 5000 partitions spread across five tables

Launch profiler Cluster

You must launch the Profiler cluster to view the profiler results for your assets and datasets. You must be a Power User to launch Profiler cluster.

About this task

A new user interface which is introduced to launch profilers in Data Catalog. The Profiler Services is now supported by enabling the High Availability (HA) feature.



Note: The profiler HA feature is under entitlement. Based on the entitlement, the HA functionality is supported on the Profiler cluster. Contact your Cloudera account representative to activate this feature in your CDP environment.



Attention: By default when you launch a Profiler cluster, the instance type of the Master node will be:

- AWS - m5.4xlarge
- Azure - Standard_D16_v3
- GCP - e2-standard-16



Note: This is applicable for the latest build of Data Catalog version 2.0.17: 2.0.17-b26

There are two types of Profiler Services:

- Profiler Manager
- Profiler Scheduler

The Profiler Manager service consists of Profiler administrators, metrics, and data discovery services. These three entities support HA. The HA feature supports Active-Active mode.



Important: The Profiler Scheduler service does not support the HA functionality.

How to launch the cluster profiler

On the Data Catalog search page, select the data lake from which you want to launch the profiler cluster. On the right-hand side of the window, the application displays the page to set up the profiler for the selected data lake. Click the Get Started link to proceed.

Profiler Setup - [REDACTED]

Setting up the profiler enables the cluster to fetch the data related to the profiled assets. The profiled assets contain summarized information pertaining to Cluster Sensitivity Profiler, Ranger Audit Profiler, and Hive Column Profiler.

Enable High Availability

The Profiler High Availability (HA) cluster provides failure resilience for several of the services, including Knox, HDFS, YARN, HMS, and Profiler Manager Service. Services that do not run in HA mode yet include Cloudera Manager, Livy, and Profiler Scheduler Service.

Setup Profiler

For setting up the profiler, you have the option to enable or disable the HA.

Note that the HA functionality is being supported only from Cloudera Runtime 7.2.10 release onwards. If you are using the Cloudera Runtime version below 7.2.10, you shall not be able to use the HA feature for launching the profiler services.

Profiler Setup - [REDACTED]

Setting up the profiler enables the cluster to fetch the data related to the profiled assets. The profiled assets contain summarized information pertaining to Cluster Sensitivity Profiler, Ranger Audit Profiler, and Hive Column Profiler.

Enable High Availability

The Profiler High Availability (HA) cluster provides failure resilience for several of the services, including Knox, HDFS, YARN, HMS, and Profiler Manager Service. Services that do not run in HA mode yet include Cloudera Manager, Livy, and Profiler Scheduler Service.

When enabled, the HA Profiler cluster provides greater resiliency and scalability by using more virtual machines that incur additional corresponding cloud provider costs.

Setup Profiler

Once you enable HA and click Setup Profiler, Data Catalog processes the request and the profiler creation is in progress.

Profiler Cluster is being created						
2619						Action
<input type="checkbox"/> Type	Name	Qualified Name	Created On	Owner	Source	
<input type="checkbox"/> Azure Container	container	abfs://container@sparktestingstorage...	-NA-	-NA-	adls	
<input type="checkbox"/> AWS S3 V2 Bucket	s3-extractor-test	s3a://s3-extractor-test@cm	-NA-	-NA-	aws	
<input type="checkbox"/> Hive Table	lounge	airline.lounge@cm	Mon Oct 04 2021	hrt_1	hive	

Later, a confirmation message appears that the profiler cluster is created.

Profiler Cluster is provisioned successfully						
2619						Action
<input type="checkbox"/> Type	Name	Qualified Name	Created On	Owner	Source	
<input type="checkbox"/> Azure Container	container	abfs://container@sparktestingstorage...	-NA-	-NA-	adls	
<input type="checkbox"/> AWS S3 V2 Bucket	s3-extractor-test	s3a://s3-extractor-test@cm	-NA-	-NA-	aws	
<input type="checkbox"/> Hive Table	lounge	airline.lounge@cm	Mon Oct 04 2021	hrt_1	hive	

Next, you can verify the profiler cluster creation under CDP Management Console > Environments > DataHubs pane.

Note that the newly created profiler cluster has some unique representations under the following categories:

Environments / | 2619 / Clusters

Child environment to souravb-env-ycloud
Checking for Data Lake upgrade...

DATA LAKE NAME: [souravb-env-ycloud](#) | NIDES: 2 | DATA LAKE SCALE: Custom | DATA LAKE STATUS: ● Running | REASON: Datalake is running | [Atlas](#) [Ranger](#) [Data Catalog](#)

DATA LAKE ORN: [cm.cdp.datalake.us-west-1-9d74eee4-1cad-45d7-b645-7ccf9edbb73d.datalake.16166144-1154-43a3-a228-63afa311821](#)

Data Hubs | Data Lake | Cluster Definitions | Summary

Data Hubs

Search

<input type="checkbox"/>	Status	Name ↓	Data Hub Type	Version	Node Count	Created
<input type="checkbox"/>	● Running	dc-pro-c7bfc246	v6-cdp-datacatalog-profiler-ha_7_2_10-0	CDH 7.2.10	6	07/28/21, 03:27 PM GMT+5:30

[Create Data Hub](#)

- Data Hub Type - The term “ha” is appended to the type of cluster that is newly created.
- Version - 7.2.10
- Node Count - (Which is 6)

Your Profiler cluster with HA is set up successfully.

Related Information

[Understanding the data catalog profiler](#)

[Understanding the cluster sensitivity profiler](#)

[Understanding the ranger audit profiler](#)

Launching profilers using Command-line

Data Catalog now supports launching Data profilers using the Command-Line Interface (CLI) option.

This, apart from launching the profilers using the Data Catalog UI. The CLI will be one executable and will not have any external dependencies. You can execute some operations in the Data Catalog service using the CDP CLI commands.

Users must have valid permission(s) to launch profilers on a data lake.

For more information about the access details, see [Prerequisites to access Data Catalog service](#).

You must have the following entitlement granted to use this feature:

DATA_CATALOG_ENABLE_API_SERVICE

For more information about the CDP command-line interface and setting up the same, see [CDP CLI](#).

In your CDP CLI environment, enter the following command to get started in the CLI mode.

```
cdp datacatalog --help
```

This command provides information about the available commands in Data Catalog.

The output is displayed as:

NAME

datacatalog

DESCRIPTION

Cloudera Data Catalog Service is a web service, using this service user can execute operations like launching profilers in Data Catalog.

AVAILABLE SUBCOMMANDS

launch-profilers

You get additional information about this command by using:

```
cdp datacatalog launch-profilers --help
```

NAME

launch-profilers -

DESCRIPTION

Launches DataCatalog profilers in a given datalake.

SYNOPSIS

launch-profilers

--datalake <value>

[--cli-input-json <value>]

[--generate-cli-skeleton]

OPTIONS

--datalake (string) The Name or CRN of the Datalake.

```
--cli-input-json (string) Performs service operation based on the JSON string provided. The JSON string follows the format provided by --generate-cli-skeleton. If other arguments are provided on the command line, the CLI values will override the JSON-provided values.
```

```
--generate-cli-skeleton (boolean) Prints a sample input JSON to standard output. Note the specified operation is not run if this argument is specified. The sample input can be used as an argument for --cli-input-json.
```

OUTPUT

datahubCluster -> (object)

Information about a cluster.

clusterName -> (string)

The name of the cluster.

crn -> (string)

The CRN of the cluster.

creationDate -> (datetime)

The date when the cluster was created.

clusterStatus -> (string)

The status of the cluster.

nodeCount -> (integer)

The cluster node count.

workloadType -> (string)

The workload type for the cluster.

cloudPlatform -> (string)

The cloud platform.

imageDetails -> (object)

```
The details of the image used for cluster instances.
```

name -> (string)

```
The name of the image used for cluster instances.
```

id -> (string)

```
The ID of the image used for cluster instances.
```

```
This is internally generated by the cloud provider to Uniquely identify the image.
```

catalogUrl -> (string)

The image catalog URL.

catalogName -> (string)

The image catalog name.

environmentCrn -> (string)

The CRN of the environment.

credentialCrn -> (string)

The CRN of the credential.

datalakeCrn -> (string)

The CRN of the attached datalake.

clusterTemplateCrn -> (string)

```
The CRN of the cluster template used for the cluster
```

creation.

You can use the following CLI command to launch the Data profiler:

```
cdp datacatalog launch-profilers --datalake <datalake name or datalake CRN>
```

Example

```
cdp datacatalog launch-profilers --datalake test-env-ycloud
```

```
{
```

```
"datahubCluster": {
```

```
"clusterName": "cdp-dc-profilers-24835599",
```

```
  "crn" :
```

```
    "crn:cdp:datahub:us-west-1:9d74eee4-1cad-45d7-b645-7ccf9edbb73d:cluster:dfaa7646-d77f-4099-a3ac-6628e1576160",
```

```
"creationDate": "2021-06-04T11:31:23.735000+00:00",
```

```
"clusterStatus": "REQUESTED",
```

```
"nodeCount": 3,
```

```
"workloadType": "v6-cdp-datacatalog-profiler_7_2_8-1",
```

```
"cloudPlatform": "YARN",
```

```
"imageDetails": {
```

```
  "name" :
```

```
    "docker-sandbox.infra.cloudera.com/cloudbreak/centos-76:2020-05-18-17-16-16",
```

```
"id": "d558405b-b8ba-4425-94cc-a8baff9ffb2c",
```

```
  "catalogUrl" :
```

```
    "https://cloudbreak-imagecatalog.s3.amazonaws.com/v3-test-cb-image-catalog.json",
```

```
"catalogName": "cdp-default"
```

```
},
```

```
  "environmentCrn" :
```

```
    "crn:cdp:environments:us-west-1:9d74eee4-1cad-45d7-b645-7ccf9edbb73d:environment:bf795226-b57c-4c4d-8520-82249e57a54f",
```

```
  "credentialCrn" :
```

```
"crn:altus:environments:us-west-1:9d74eee4-1cad-45d7-b645-7ccf9edb
b73d:credential:3adc8ddf-9ff9-44c9-bc47-1587db19f539" ,

"datalakeCrn" :
  "crn:cdp:datalake:us-west-1:9d74eee4-1cad-45d7-b645-7ccf9edbb73d
:datalake:5e6471cf-7cb8-42cf-bda4-61d419cfbc53" ,

"clusterTemplateCrn" :
  "crn:cdp:datahub:us-west-1:9d74eee4-1cad-45d7-b645-7ccf9edbb73d:c
lustertemplate:16a5d8bd-66d3-42ea-8e8d-bd8765873572"

}

}
```

Deleting profiler cluster

Deleting profiler cluster removes all the Custom Sensitivity Profiler rules and other updates to the specific cluster. It could also cause loss of data specific to currently applied rules on the deleted profiler cluster.

About this task

To overcome this situation, when you decide to delete the profiler cluster, there is a provision to retain the status of the Custom Sensitivity Profiler rules. If your profiler cluster has rules that are not changed or updated, you can directly delete the profiler cluster. If the rules were modified or updated, you have an option to download the modified rules along with deletion. The modified rules consist of the suspended System rules and the deployed Custom rules. Using the downloaded rules, you can manually add or modify them to your newly added profiler cluster.

Procedure

1. On the search page, select the Data Lake from the list.
2. Click the Actions drop-down menu and select Delete Cluster.

3. Click Yes to proceed.

The application displays the following message.

The screenshot shows a confirmation dialog box titled "Are you sure to delete the profiler on sonamdh-env-ycloud?". The dialog contains the following text:

Deleting the profiler cluster will disable the associated services like HDFS, YARN, Livy, Spark, HMS, Profiler Manager Service, and Profiler Scheduler Service. You will no longer be able to view information related to **Cluster Sensitivity Profiler**, **Ranger Audit Profiler** and **Hive Column Profiler**.

Verifying the state of the Cluster Sensitivity Profiler rules...

The background shows a table of Hive tables for the cluster "sonamdh-env-ycloud | 693".

Type	Name	Qualified Name	Created On	Owner	Source
Hive Table	bucketing_cols	sys.bucketing_cols@cm	Mon Oct 18 2021	hive	hive
Hive Table			Mon Oct 18 2021	hive	hive
Hive Table			Mon Oct 18 2021	hive	hive
Hive Table			Mon Oct 18 2021	hive	hive
Hive Table			Mon Oct 18 2021	hive	hive
Hive Table			Mon Oct 18 2021	hive	hive

When you upgrade / launch Data Catalog service in Cloudera Runtime version 7.2.14, and later if the profiler cluster is deleted, the following message is displayed.

The screenshot shows a confirmation dialog box titled "Are you sure to delete the profiler on sonam-env-ycloud?". The dialog contains the following text:

Deleting the profiler cluster will disable the associated services like HDFS, YARN, Livy, Spark, HMS, Profiler Manager Service, and Profiler Scheduler Service. You will no longer be able to view information related to **Cluster Sensitivity Profiler**, **Ranger Audit Profiler** and **Hive Column Profiler**.

I understand this action cannot be undone.

Buttons:

The background shows a table of Hive tables for the cluster "sonam-env-ycloud | 32".

Type	Name	Qualified Name	Created On	Owner	Source
Hive Table	inherited_data	default.inherited_data@cm	Mon Oct 25 2021	dpprofiler	hive
Hive Table	user_data		Oct 25 2021	dpprofiler	hive
Hive DB	default			public	hive
Hive Column	email			dpprofiler	hive
Hive Column	parch			dpprofiler	hive
Hive Column	embarke			dpprofiler	hive
Hive Column	parch			dpprofiler	hive
Hive Column	credit	default.user_data.credit@cm	-NA-	dpprofiler	hive



Note: Using Data Catalog with Cloudera Runtime version 7.2.12 and below, and later when you delete a profiler cluster that has modified Custom Sensitivity Profiler rules, the following message is displayed.

The screenshot shows a confirmation dialog box titled "Are you sure to delete the profiler on sonam-env-ycloud?". The dialog contains the following text:

Deleting the profiler cluster will disable the associated services like HDFS, YARN, Livy, Spark, HMS, Profiler Manager Service, and Profiler Scheduler Service. You will no longer be able to view information related to **Cluster Sensitivity Profiler**, **Ranger Audit Profiler** and **Hive Column Profiler**.

The system and custom rules pertaining to the Cluster Sensitivity Profiler have been modified. Before deleting the profiler, you can save the modified rules.

Yes, I would like to download the modified rules.
 No, I do not want to download the modified rules.


I understand this action cannot be undone.

Buttons:

The background shows a table of Hive tables for the cluster "sonam-env-ycloud | 32".

Type	Name	Qualified Name	Created On	Owner	Source
Hive Table	inherited_data	default.inherited_data@cm	Mon Oct 25 2021	dpprofiler	hive
Hive Table	user_data		Oct 25 2021	dpprofiler	hive
Hive DB	default			public	hive
Hive Column	email			dpprofiler	hive
Hive Column	parch			dpprofiler	hive
Hive Column	embarke			dpprofiler	hive
Hive Column	parch			dpprofiler	hive
Hive Column	credit			dpprofiler	hive
Hive Column	sex			dpprofiler	hive
Hive Column	age			dpprofiler	hive
Hive Column	age			dpprofiler	hive
Hive Column	passengerid	default.user_data.passengerid@cm	-NA-	dpprofiler	hive

While using Data Catalog with Cloudera Runtime version 7.2.12 and below, and if the profiler cluster does not have any modified Custom Sensitivity Profiler rules, the following message is displayed.



The profiler cluster is deleted successfully.

Additionally, note that you can delete the profiler cluster in these situations, when:

- Profiler cluster is up and running
- Profiler cluster is created but stopped
- Profiler cluster creation failed but is registered with the data lake
- Profiler cluster is down and inaccessible



Note: If the profiler cluster is not registered with the data lake, Data Catalog cannot locate or trace the profiler cluster. Users have to delete the profiler cluster from the DataHub page (Cloudera Management Console).

On-Demand Profilers

You can use on-demand profilers to profile specific assets without depending on the cron-based scheduling of profilers jobs. On-demand profiler option is available on the asset details page of the selected asset.

For example, the diagram displays the Asset Details page of an asset. Run On-Demand profiler for Hive Column Statistics and Custom Sensitivity Profiler by clicking on the appropriate Run button. The next scheduled run provides details about the next scheduled profiling for the respective profilers.



Note: You can use the On-Demand Profiler feature to profile both External and Managed tables.

Profilers | 2

Hive Column Profiler

Last run: 10 mins ago | Status: SUCCESS ▶ Run

Next Schedule Run: Today at 11:30 PM

Cluster Sensitivity Profiler

Last run: 12 mins ago | Status: SUCCESS ▶ Run

Next Schedule Run: NA, Profiler is Disabled.

Profiling table data in non-default buckets

You must configure a parameter in Profiler Scheduler in your Cloudera Manager instance, to profile table data in non-default buckets.

Configuration > Search for "spark" in the filters field > Profiler Scheduler Spark conf > Add `spark.yarn.access.hadoopFileSystems=s3a://default-bucket,s3a://bucket-1,s3a://bucket-2`

The screenshot shows the Cloudera Manager interface for configuring the Profiler Scheduler. The left sidebar contains navigation options like Clusters, Hosts, Diagnostics, Charts, Administration, Parcels, Running Commands, and Support. The main content area is titled 'Profiler Scheduler' and shows the configuration for 'Profiler Scheduler Spark conf'. A search bar contains 'spark'. The configuration list includes several parameters, with the last one being `spark.yarn.access.hadoopFileSystems=s3a://default-bucket,s3a://bucket-1,s3a://bucket-2`. A 'Filters' panel on the left shows the search results for 'spark'.



Note: bucket-1 and bucket-2 are non-default buckets.



Attention: For more information, see [Accessing data stored in Amazon S3 through Spark](#).

High Availability support for Profiler services

The Profiler Services is now supported by enabling the High Availability (HA) feature.

There are two types of Profiler Services:

- Profiler Manager
- Profiler Scheduler


The Profiler Manager service consists of Profiler administrators, metrics, and data discovery services. These three entities support HA. The HA feature supports Active-Active mode.



Note: The Profiler Scheduler service does not support the HA functionality.

As of this update, there is a new user interface which is introduced to launch profilers in Data Catalog.

On the Data Catalog search page, select the data lake from which you want to launch the profiler cluster. On the right-hand side of the window, the application displays the page to set up the profiler for the selected data lake. Click the Get Started link to proceed.



Profiler Setup - dcpro-dss-app-xyz1 ✕

Setting up the profiler enables the cluster to fetch the data related to the profiled assets. The profiled assets contain summarized information pertaining to Cluster Sensitivity Profiler, Ranger Audit Profiler, and Hive Column Profiler.


Enable High Availability

The Profiler High Availability (HA) cluster provides failure resilience for several of the services, including Knox, HDFS, YARN, HMS, and Profiler Manager Service. Services that do not run in HA mode yet include Cloudera Manager, Livy, and Profiler Scheduler Service.

Setup Profiler

For setting up the profiler, you have the option to enable or disable the HA. Note that the HA functionality is being supported only from Cloudera Runtime 7.2.10 release onwards. If you are using the Cloudera Runtime version below 7.2.10, you shall not be able to use the HA feature for launching the profiler services.

Once you enable HA and click Setup Profiler, Data Catalog processes the request and the profiler creation is in progress.



Profiler Setup - dcpro-dss-app-xyz1 ✕

Setting up the profiler enables the cluster to fetch the data related to the profiled assets. The profiled assets contain summarized information pertaining to Cluster Sensitivity Profiler, Ranger Audit Profiler, and Hive Column Profiler.

Enable High Availability

The Profiler High Availability (HA) cluster provides failure resilience for several of the services, including Knox, HDFS, YARN, HMS, and Profiler Manager Service. Services that do not run in HA mode yet include Cloudera Manager, Livy, and Profiler Scheduler Service.

When enabled, the HA Profiler cluster provides greater resiliency and scalability by using more virtual machines that incur additional corresponding cloud provider costs.

Setup Profiler

Profiler Cluster is being created

dcpro-dss-app-xyz1 | 206

Type	Name	Qualified Name	Created On	Owner	Source
AWS S3 V2 Bucket	cdp-e2einterop-shared-env	s3a://cdp-e2einterop-shared-env@cm	-NA-	-NA-	aws
Hive Table	compactions	sys.compactions@cm	Mon Mar 06 2023	hive	hive
Hive Table	columns	information_schema.columns@cm	Mon Mar 06 2023	hive	hive
Hive Table	notification_log	sys.notification_log@cm	Wed Mar 08 2023	hive	hive

Later, a confirmation message appears that the profiler cluster is created.

Profiler Cluster is provisioned successfully

dcpro-dss-app-xyz1 | 206

Type	Name	Qualified Name	Created On	Owner	Source
AWS S3 V2 Bucket	cdp-e2einterop-shared-env	s3a://cdp-e2einterop-shared-env@cm	-NA-	-NA-	aws
Hive Table	compactions	sys.compactions@cm	Mon Mar 06 2023	hive	hive
Hive Table	columns	information_schema.columns@cm	Mon Mar 06 2023	hive	hive
Hive Table	notification_log	sys.notification_log@cm	Wed Mar 08 2023	hive	hive
Hive Table	compactions	information_schema.compactions@cm	Mon Mar 06 2023	hive	hive

Next, you can verify the profiler cluster creation under CDP Management Console > Environments > DataHubs pane. Note that the newly created profiler cluster has some unique representations under the following categories:

Environments / dcpro-dss-app-xyz1 / Clusters

dcpro-dss-app-xyz1
 cm:cdp.environments.us-west-1:54a0cb3c-7efa-40ba-8494-7cb260f1c109:environment:34c386a5-f821-4fe5-96aa-d6042820d0a8
 US West (Oregon) - us-west-2
 Environment created by e2e-interop dcpro-dss-app-xyz1
 Data Lake upgrade available

sdx Data Lake Details

NAME	NODES	SCALE	QUICK LINKS
dcpro-dss-app-xyz1	2	Light Duty	Atlas Ranger Data Catalog

STATUS: Data Lake Upgrade In Progress...
 STATUS REASON: Upgrading data lake stack
 CRN: cm:cdp.data lake:us-west-1:54a0cb3c-7efa-40ba-8494-7cb260f1c109:data lake:ff68a4b8-e028-44ed-9a0c-1a677...

Data Hubs

Create Data Hub action is disabled because the Data Lake for this Environment is not Available.

Search

There are no Data Hubs to display.

2.68.0-b119

- Data Hub Type - The term “ha” is appended to the type of cluster that is newly created.
- Version - 7.2.10
- Node Count - (Which is 6)

Your Profiler cluster with HA is set up successfully.

Tracking Profiler Jobs

The Data Catalog profiler page is updated to provide a better user experience for tracking respective profiler jobs.

A new placeholder named “Schedule” is introduced under the Profilers section to provide tracking information of each profiler job. Under Schedule, you can find the type of profiler job that has run or in progress or has completed profiling data assets.

Status	Job ID ↑	Start Time	Stage	Queue	Assets Profiled
Ranger Audit					
Finished	4	Dec 10 2020 09:05:51	Metrics Service	-	NA
Finished	3	Dec 10 2020 09:01:47	Metrics Service	-	NA
Finished	2	Dec 10 2020 09:00:04	Livy	default	NA
Finished	1	Dec 10 2020 09:00:01	Scheduler Service	-	NA

For each profiler job, you can view the details about:

- Job Status
- Type
- Job ID
- Start Time
- Stage
- Job Queue
- Total assets profiled

Data Catalog / Profilers

Status	Job ID ↑	Start Time	Stage	Queue	Assets Profiled
Ranger Audit					
Running	280	Dec 09 2020 09:27:17	Livy	default	NA
Finished	279	Dec 09 2020 09:27:16	Scheduler Service	-	NA

Using this data can help you to troubleshoot failed jobs or even understand how the jobs were profiled and other pertinent information that can help you to manage your profiled assets. Whenever the Schedule status appears in green, it indicates that the profiler job has run successfully. When the color appears in blue and red, it indicates that the profiler job is running or has failed.

Profiler job runs in three phases:

- Scheduler Service - Part of Profiler Admin which queues the profiler requests.
- Livy - This service is managed by YARN and where the actual asset profiling takes place.
- Metrics Service - Reads the profiled data files and publishes them.



Note: More than one occurrence of Scheduler Service or Livy indicates that there could be more assets to be profiled. For example, if a HBase schedule has about 80 assets to be profiled, the first 50 assets would be profiled in the first Livy batch and the other assets get profiled in the next batch.

Clicking on each profiled asset would navigate to the profiled asset details page. The asset profiled page provides information about the profiled asset, profiled status, the profiled job id, and other relevant details.

In case of Ranger Audit profiling, there could be a “NA” status for the total number of assets profiled. It indicates that the auditing that happens is dependent on the Ranger policies. In other words, the Ranger policies are actually profiled and not the assets.

Important: Currently, the On-Demand schedule is not supported for this version of the profiler. The job schedule is either grayed out or disabled in such a scenario.

Viewing Profiler Jobs

You can monitor the overall health of your profiler jobs by viewing their status on the [Profiler Jobs](#) .

Each profiler runs a Spark job on a user-defined schedule defined via the profiler configuration. You can view the status of each of those jobs for all your clusters.

Monitoring the profiler jobs has the following uses:

- By seeing long-term trends in job execution, you can determine the overall health of your profilers.
- If you do a data ingest, you can find out if the profiling has completed.
- Knowing when jobs first failed can help when troubleshooting problems with profilers.

You can take the following actions:

1. Filter by cluster, job status, or profiler.
2. Sort by jobs ID, status, start time, cluster, queue, or profilers.
3. Expand or narrow to show a day, week, or month of jobs.

Related Information

[Understanding the data catalog profiler](#)

[Understanding the sensitive data profiler](#)

[Understanding the ranger audit profiler](#)

Viewing Profiler Configurations

You can monitor the overall health of individual profilers by viewing their status on [Profiler Configs](#) .

Monitoring the profiler configurations has the following uses:

- See which profilers are active and inactive.
- View asset coverage for a particular profiler over time- for instance, if you change a configuration for a profiler, you can see if new assets become covered.

You can take the following actions:

1. Filter by cluster.
2. Expand the execution status of an individual profiler.
3. Edit the profiler configuration.
4. Toggle each profiler on/off.

Related Information

[Understanding the data catalog profiler](#)

[Understanding the sensitive data profiler](#)

[Understanding the ranger audit profiler](#)

Edit Profiler Configuration

In addition to turning on and off the profiler configurations, the individual profilers can be run with their own execution parameters. These parameters are for submission of the profiler job onto Spark. You can edit the configuration of profilers and update these parameters to run profiler jobs.

Procedure

1. Click Profilers in the main navigation menu on the left.
2. Click Configs to view all of the configured profilers.
3. Select the cluster for which you need to edit profiler configuration.

The list of profilers for the selected clusters is displayed.

4. Click the name of the profiler whose configuration you wish to edit.

The Profiler Configuration tab is displayed in the right panel.

5. Select a schedule to run the profiler. This is implemented as a quartz cron expression.

For more information, see [Understanding Cron Expression generator](#) on page 56.

6. Select Last Run Check.

Last Run Check configuration enables profilers like Hive Column Statistics and Cluster Sensitivity Profiler to avoid profiling the same asset on each scheduled run. If you have scheduled a cron job, say for about an hour, and have enabled the Last Run Check configuration for two days, this set-up ensures that the job scheduler filters out any asset which was already profiled in the last two days.

If the Last Run Check configuration is disabled, assets will be picked up for profiling as per the job cron schedule, honoring the asset filter rules, if any.



Caution: This configuration is not applicable to the Ranger Audit Profiler.

7. Update the advanced options.

- Number of Executors - Enter the number of executors to launch for running this profiler.
- Executor Cores - Enter the number of cores to be used for each executor.
- Executor Memory - Enter the amount of memory in GB to be used per executor process.
- Driver Cores - Enter the number of cores to be used for the driver process.
- Driver Memory - Enter the memory to be used for the driver processes.

For more information, see [Configuring SPARK on YARN Applications](#) and [Tuning Resource Allocation](#).

8. Toggle the state of the profiler from Active to Inactive as needed.
9. Click Save to apply the configuration changes to the selected profiler. The changes should appear in the profiler description.

Additional Configuration for Cluster Sensitivity Profiler

In addition to the generic configuration, there are additional parameters for the Cluster Sensitivity Profiler that can optionally be edited.

Procedure

1. Click Profilers in the main navigation menu on the left.
2. Click Configs to view all of the configured profilers.
3. Select the cluster for which you need to edit profiler configuration.

The list of profilers for the selected clusters is displayed.

4. Click the Cluster Sensitivity Profiler to edit.
The Profiler Configuration tab is displayed in the right panel.
5. Toggle the Enable button to enable Cluster Sensitivity Profiler. Select Disable if you do not want to run the Cluster Sensitivity Profiler.
6. Select the Sample Data Size.
 - a) From the drop down, select the type of sample data size.
 - b) Enter the value based on the previously selected type.
7. Select the queue, schedule, and advanced configuration details as specified in Edit Profiler Configuration.
8. Add Asset Filter Rules as needed to customize the selection and deselection of assets which the profiler profiles. For more information, see [Setting Asset filter rules](#) on page 56.
9. Toggle the state of the profiler from Active to Inactive as needed.
10. Click Save to apply the configuration changes to the selected profiler. The changes should appear in the profiler description.

Related Information

[Understanding the data catalog profiler](#)

[Understanding the sensitive data profiler](#)

Associating Custom Sensitivity Profiler tags to Hive assets

Associating Custom Sensitivity Profiler tags to Hive assets fails on the 7.2.16 Cloudera Runtime cluster.

The issue can be resolved by adding the Spark configuration:

`spark.sensitive.profiler.tableSamplePercentage=50` to profiler scheduler conf by adding the configuration under the key - `profiler_scheduler_spark_conf`.

The value passed in the configuration must be an integer value ranging from 1 to 100.

This value indicates the percentage of rows to be picked up as a sample for the profiler job.

Additional Configuration for Hive Column Profiler

In addition to the generic configuration, there are additional parameters for the Hive Column Profiler that can optionally be edited.

Procedure

1. Click Profilers in the main navigation menu on the left.
2. Click Configs to view all of the configured profilers.
3. Select the cluster for which you need to edit profiler configuration.

The list of profilers for the selected clusters is displayed.

4. Click the Hive Column Profiler to edit.

The Profiler Configuration tab is displayed in the right panel.

5. Select the queue and schedule details as specified in [Edit Profiler Configuration](#) on page 54.
6. Add Asset Filter Rules as needed to customize the selection and deselection of assets which the profiler profiles. For more information, see [Setting Asset filter rules](#) on page 56.



Note: The schedule for Hive Column Profiler is set to run once every six hours. After installation, you will be able to see the output of Hive Column Profiler after six hours. If you want to view the output in advance, update the cron expression accordingly.

7. Select the Sample Data Size.
 - a. From the drop down, select the type of sample data size.
 - b. Enter the value based on the previously selected type.

- Click Save to apply the configuration changes to the selected profiler. The changes should appear in the profiler description.

Understanding Cron Expression generator

A cron expression details about when the schedule executes and visualizes the next execution dates of your cron expression. The cron expression utilizes the quartz engine.

The cron expression uses a typical format as seen in the table:

Cron Expression: * * * * * * ? *

Each * in the cron represents a unique value.

For example, consider a cron with the following values:

Cron Expression: 1 2 3 2 5 ? 2 0 2 1

The cron is scheduled to run the profiler job at: 03:02:01am, on the 2nd day, in May, in 2021.

You can change the value of cron as and when it is required depending on how you want to schedule your profiler job.

Setting Asset filter rules

Add Asset filter rules as needed to customize the selection and deselection of assets which the profiler profiles.



Note: You can configure the Deny-list and Allow-list for both Cluster Sensitivity Profiler and Hive Column Profiler. The same filter rules do not apply to Ranger Audit Profiler.

Data Catalog / Profilers / Configs / Detail

Cluster Sensitivity Profiler

Data Lake: [redacted]

The Cluster Sensitivity Profiler automatically performs context and content inspection to detect various types of sensitive data and suggest suitable classifications or tags based on the type of sensitive content detected or discovered.

Active

Schedule*
0 20 * * * ?

Last Run Check*
2 Days

Sample Data Size*
Number of Rows 100

^ Advance Options

Number of Executors*
1

Executor Cores*
1

Executor Memory (in GB)*
1

Driver Core*
2

Driver Memory (in GB)*
1

Data Catalog / Profilers / Configs / Detail

Hive Column Profiler

Data Lake: [REDACTED]

You can view who has accessed which data from a forensic audit or compliance perspective, visualize access patterns, and identify anomalies in access patterns using the Ranger Audit Profiler.

Active

Schedule*
0 0 0/6 1/1 * * ? *

Last Run Check*
1 Day

Sample Data Size*
Sample Percentage 100

▼ Advance Options

Asset Filter Rules

Deny List Allow List

Profiler will skip profiling assets which meet any of deny list rules

Search Deny List [Add New](#)

Status	Key ↑	Operator	Value
--------	-------	----------	-------

Data Catalog / Profilers / Configs / Detail

Ranger Audit Profiler

Data Lake: [REDACTED]

You can view the shape or distribution characteristics of the columnar data within a Hive table based on the Hive Column Profiler.

Active

Schedule*
0 */30 * * * *

^ Advance Options

Number of Executors*
1

Executor Cores*
1

Executor Memory (in GB)*
1

Driver Core*
1

Driver Memory (in GB)*
1

- Deny-list - The profiler will skip profiling assets that meet any defined Deny-list criteria.
 - Select the Deny-list tab.
 - Click Add New to include rules for Deny-list.
 - Select the key from the drop down list. You can select a database name, name of the asset, name of the owner of the asset, path to the assets, or created date.
 - Select the operator from the drop down list. Depending on the keys selected, you can select an operator such as equals, contains. For example, you can select the name of assets that contain a particular string.
 - Enter the value corresponding to the key. For example, you can enter a string as mentioned in the previous example here.
 - Click Done. Once it is added, you can toggle the state of the new rule to enable it or disable it as needed.

Asset Filter Rules

[Deny List](#) [Allow List](#)

Profiler will skip profiling assets which meet any of deny list rules

Search Deny List Add New

Status	Key ↑	Operator	Value	
<input checked="" type="checkbox"/>	table	equals	us_customers	⋮

SAVE Cancel

Data Catalog / Profilers / Configs / Detail

PERFORMANCE OPTIMIZATION

Number of Executors* ⓘ

Executor Cores* ⓘ

Executor Memory (in GB)* ⓘ

Driver Core* ⓘ

Driver Memory (in GB)* ⓘ

Asset Filter Rules

[Deny List](#) [Allow List](#)

Profiler will skip profiling assets which meet any of deny list rules

Search Deny List Add New

Status	Key ↑	Operator	Value	
<input checked="" type="checkbox"/>	table	equals	us_customers	⋮

SAVE Cancel

Add Deny List ✕


Db Name Select operator Type value 🗑️

+

- equals
- contains
- starts with
- ends with

Add Cancel

- Allow-list - The profiler will include only assets that satisfy any defined Allow-list criteria. If no Allow-list is defined, the profiler will profile all the assets.
 - Select the Allow-list tab.
 - Click Add New to include rules for the Allow-list.
 - Select the key from the drop down list. You can select a database name, name of the asset, name of the owner of the asset, path to the assets, or created date.
 - Select the operator from the drop down list. Depending on the keys selected, you can select an operator such as equals, contains. For example, you can select the name of assets that contain a particular string.
 - Enter the value corresponding to the key. For example, you can enter a string as mentioned in the previous example.
 - Click Done. Once it is added, you can toggle the state of the new rule to enable or disable it as needed.



Note: If an asset meets both Allow-list and Deny-list rules, the Deny-list rule overrides the Allow-list.

Backing up and Restoring Profiler Database

Using certain scripts that can be executed by the root users, you can take the backup of the Profiler databases. Later, if you want to delete the existing DataHub cluster and launch a new DataHub cluster, you must have an option to restore the old data.

Data Catalog includes Profiler services that run data profiling operations on data that is located in multiple Data Lakes. As of the latest Cloudera Runtime release, the Profiler services run on a DataHub cluster. When you delete the DataHub cluster, the profiled data and the user configuration information stored in the local databases are lost.

Profiler clusters run on the DataHub cluster using a couple of embedded databases - `profiler_agent` and `profiler_metrics`.



Note: If you download the modified Custom Sensitivity Profiler rules before deleting the Profiler cluster, and later when you create a new Profiler cluster, you can restore the state of the rules manually. If the System rules are part of the downloaded files, you must Suspend those rules. If Custom rules are part of the downloaded files, you must Deploy those rules. This is applicable if the Profiler cluster has Cloudera Runtime below 7.2.14 version.

About the script

The Backup and Restore script can be used only on Amazon Web Services, Microsoft Azure, and Google Cloud Platform clusters where they support cloud storage.

Scenarios for using the script

- When you upgrade the Data Lake cluster and preserve Profiler data in the DataHub cluster. You might want to delete the DataHub cluster but preserve the Profiler data.

- When you want to re-launch the Profiler and access the older processed data. You might want to delete a DataHub cluster but preserve the Profiler data of the DataHub cluster.
-  **Note:** For users using Data Catalog on Cloudera Runtime 7.2.14 version, note the following

- No user action or manual intervention needed after the upgrading DataHub cluster to 7.2.14 version is completed.
- Also, as an example use case scenario, in case a new profiler cluster is launched that contains Custom Sensitivity Profiler tags and which is deleted and relaunched later, the changes are retained and no further action is required.
- No user action is required to backup and restore the profiler data. The changes are automatically restored.

When upgrading below Cloudera Runtime 7.2.11 version to 7.2.11:

Navigate to the following locations to pick up your scripts:

Back up: `bash /opt/cloudera/parcels/PROFILER_MANAGER/profileradmin/scripts/users/backup_db.sh`

Restore: `bash /opt/cloudera/parcels/PROFILER_MANAGER/profileradmin/scripts/users/restore_db.sh`

When upgrading below or equal to Cloudera Runtime 7.2.11 version to 7.2.12:

Navigate to the following locations to pick up your scripts:

Back up: `bash /opt/cloudera/parcels/PROFILER_MANAGER/profileradmin/scripts/users/backup_db.sh`

Restore: `bash /opt/cloudera/parcels/CDH/lib/profiler_manager/profileradmin/scripts/users/restore_db.sh`

When backing up and restoring for a cluster having the Cloudera Runtime 7.2.12 and onwards:

Navigate to the following location to pick up your scripts:

Back up: `bash /opt/cloudera/parcels/CDH/lib/profiler_manager/profileradmin/scripts/users/backup_db.sh`

Restore

`bash /opt/cloudera/parcels/CDH/lib/profiler_manager/profileradmin/scripts/users/restore_db.sh`

Running the script

When you run the script, note that there are a couple of phases through which you can accomplish your task.

Firstly you backup your Profiler database and next you can restore the Profiler database.

To backup the Profiler database:

1. Stop the Profiler Manager and Profiler Scheduler services from the Cloudera Manager instance of the DataHub cluster.
2. SSH to the node where Profiler Manager is installed as a root user.

3. Execute the backup_db.sh script:



Attention: For users of Cloudera Runtime below 7.2.8 version, contact [Cloudera Support](#).



Note: If the profiler cluster having the Cloudera Runtime version 7.2.11 or below, you must run the following command:

```
bash /opt/cloudera/parcels/PROFILER_MANAGER/profileradmin/scripts/users/backup_db.sh
```



Note: If the profiler cluster having the Cloudera Runtime version 7.2.12 or onwards , you must run the following command:

```
bash /opt/cloudera/parcels/CDH/lib/profiler_manager/profileradmin/scripts/users/backup_db.sh
```

4. Delete the Profiler cluster.

5. Install a new version of Profiler cluster:

- [Scenario-1] When the Data Lake upgrade is successfully completed.
- [Scenario-2] When the user decides to launch a new version of the Profiler cluster.

To restore the Profiler database:

1. Stop the Profiler Manager and Profiler Scheduler services from the Cloudera Manager instance of the DataHub cluster.
2. SSH to the node where Profiler Manager is installed as a root user.
3. Execute the restore_db.sh script.



Attention: For users of Cloudera Runtime below 7.2.8 version, contact [Cloudera Support](#).



Note: If the profiler cluster having the Cloudera Runtime version 7.2.11 or below, you must run the following command:

```
bash /opt/cloudera/parcels/PROFILER_MANAGER/profileradmin/scripts/users/restore_db.sh
```



Note: If the profiler cluster having the Cloudera Runtime version 7.2.12 or onwards , you must run the following command:

```
bash /opt/cloudera/parcels/CDH/lib/profiler_manager/profileradmin/scripts/users/restore_db.sh
```

4. Start the Profiler Manager and Profiler Scheduler services from Cloudera Manager.



Note: When you upgrade the Data Lake cluster and a new version of Profiler cluster is installed, the Profiler configurations that have been modified by users in the older version is replaced with new values as detailed:

- Schedule
- Last Run Check
- Number of Executors
- Executor Cores
- Executor Memory (in GB)
- Driver Core
- Driver Memory (in GB)

Enable or Disable Profilers

By default, profilers are enabled and run every 30 minutes. If you want to disable (or re-enable) a profiler, you can do this by selecting the appropriate profiler from the Configs tab.

Procedure

1. From Profiler Configs
2. Select the profiler to proceed further.



Profiler Tag Rules

You can use preconfigured tag rules or create new rules based on regular expressions and allow or deny files on specific columns in your tables.

Rules are categorized into three groups:

- **System Deployed** : These are in-built rules that cannot be edited.
- **Custom Deployed**: Tag rules that you create and deploy on clusters after validation will appear under this category. Hover your mouse over the tag rules to deploy or suspend them as needed. You can also edit these tag rules.
- **Custom Draft** : You can create new tag rules and save them for later validation and deployment on clusters. Such rules appear under this category.

Jobs Configs **Tag Rules**

Rule Groups

System Deployed	77
Custom Deployed	52
Custom Draft	22

Q [+ New](#)

<input type="checkbox"/>	Name	Description	Associated Tags	Created By	Status
<input type="checkbox"/>	AUT_PassporDetection	AUT_PassporDetection	AUT_PassporDetection	Cloudera	Deployed
<input type="checkbox"/>	SVK_NationalID_Detection	SVK_NationalID_Detection	SVK_NationalID_Detection	Cloudera	Deployed
<input type="checkbox"/>	LVA_IBAN_Detection	LVA_IBAN_Detection	LVA_IBAN_Detection	Cloudera	Deployed
<input type="checkbox"/>	ROU_IBAN_Detection	ROU_IBAN_Detection	ROU_IBAN_Detection	Cloudera	Deployed
<input type="checkbox"/>	NOR_NationalID_Detection	NOR_NationalID_Detection	NOR_NationalID_Detection	Cloudera	Deployed
<input type="checkbox"/>	FRA_IBAN_Detection	FRA_IBAN_Detection	FRA_IBAN_Detection	Cloudera	Deployed
<input type="checkbox"/>	DEU_IBAN_Detection	DEU_IBAN_Detection	DEU_IBAN_Detection	Cloudera	Deployed
<input type="checkbox"/>	FIN_NationalID_Detection	FIN_NationalID_Detection	FIN_NationalID_Detection	Cloudera	Deployed
<input type="checkbox"/>	ESP_PassportDetection	ESP_PassportDetection	ESP_PassportDetection	Cloudera	Deployed
<input type="checkbox"/>	DEU_PassportDetection	DEU_PassportDetection	DEU_PassportDetection	Cloudera	Deployed
<input type="checkbox"/>	CYP_IBAN_Detection	CYP_IBAN_Detection	CYP_IBAN_Detection	Cloudera	Deployed
<input type="checkbox"/>	FIN_PassportDetection	FIN_PassportDetection	FIN_PassportDetection	Cloudera	Deployed
<input type="checkbox"/>	email	email	email	Cloudera	Deployed
<input type="checkbox"/>	AUT_IBAN_Detection	AUT_IBAN_Detection	AUT_IBAN_Detection	Cloudera	Deployed
<input type="checkbox"/>	GRC_NationalID_Detection	GRC_NationalID_Detection	GRC_NationalID_Detection	Cloudera	Deployed
<input type="checkbox"/>	BEL_IBAN_Detection	BEL_IBAN_Detection	BEL_IBAN_Detection	Cloudera	Deployed
<input type="checkbox"/>	EST_IBAN_Detection	EST_IBAN_Detection	EST_IBAN_Detection	Cloudera	Deployed
<input type="checkbox"/>	CHE_NationalID_Detection	CHE_NationalID_Detection	CHE_NationalID_Detection	Cloudera	Deployed
<input type="checkbox"/>	POL_PassportDetection	POL_PassportDetection	POL_PassportDetection	Cloudera	Deployed

Tag Management

From Atlas tags UI in Data Catalog, you can create, modify, and delete any of the Atlas tags in a Data Catalog instance.

You can access the Atlas link by logging into Data Catalog > Atlas Tags .

Atlas Tags allows the user to perform the following activities with a selected Data Lake for tag management:

- Selecting a Data Lake
- Searching for a tag
- Adding a tag
- Editing a tag
- Deleting a tag

The new Atlas tags UI is displayed as seen in the diagram.

The screenshot shows the 'Data Catalog / Atlas Tags' interface. On the left is a dark sidebar with navigation options: Search, Datasets, Bookmarks, Profilers, and Atlas Tags (highlighted). Below the sidebar are links for 'Get Started' and 'Help', and the version '2.0.9-b92'. The main content area has a search bar and a table of tags. The table has columns for 'Tag', 'Description', 'Created By', and 'Created On'. A blue 'Add Tag' button is in the top right of the table area. A 'Feedback' button is on the far right edge.

Tag ↑	Description	Created By	Created On
dp	dp	dpprofiler	Mar 12 2021 12:40:11
dp_bankaccount	dp_bankaccount	dpprofiler	Mar 12 2021 15:53:23
dp_BEL_Passport_Detection	dp_BEL_Passport_Detection	dpprofiler	Mar 12 2021 15:53:23
dp_BGR_IBAN_Detection	dp_BGR_IBAN_Detection	dpprofiler	Mar 12 2021 15:53:23
dp_BGR_NationalID_Detection	dp_BGR_NationalID_Detection	dpprofiler	Mar 12 2021 15:53:19
dp_CHE_IBAN_Detection	dp_CHE_IBAN_Detection	dpprofiler	Mar 12 2021 15:53:23
dp_creditcard	dp_creditcard	dpprofiler	Mar 12 2021 15:53:19
dp_CZE_NationalID_Detection	dp_CZE_NationalID_Detection	dpprofiler	Mar 12 2021 15:53:19
dp_DEU_IBAN_Detection	dp_DEU_IBAN_Detection	dpprofiler	Mar 12 2021 15:53:23
dp_DEU_Passport_Detection	dp_DEU_Passport_Detection	dpprofiler	Mar 12 2021 15:53:19
dp_DNK_NationalID_Detection	dp_DNK_NationalID_Detection	dpprofiler	Mar 12 2021 15:53:19
dp_email	dp_email	dpprofiler	Mar 12 2021 15:53:19
dp_ESP_Passport_Detection	dp_ESP_Passport_Detection	dpprofiler	Mar 12 2021 15:53:23
dp_EST_IBAN_Detection	dp_EST_IBAN_Detection	dpprofiler	Mar 12 2021 15:53:23
dp_EST_NationalID_Detection	dp_EST_NationalID_Detection	dpprofiler	Mar 12 2021 15:53:19

You can create a new tag in the Atlas tags UI. The following diagram provides an overview about the Create a new tag page.

This screenshot shows the same 'Data Catalog / Atlas Tags' interface as the previous one, but with a 'Create a new tag' dialog box open on the right side. The dialog has a close button (x) in the top right. It contains the following fields and options:

- Name***: A required text input field.
- Description**: A text input field.
- Select classification to inherit attributes(optional)**: A dropdown menu.
- Attributes(optional)**: A section with a blue button labeled 'Add new attributes'.
- At the bottom of the dialog are 'SAVE' and 'Cancel' buttons.

 The table of tags in the background is partially visible and appears to be the same as in the previous screenshot. A 'Feedback' button is also visible on the right edge of the main interface.

You can add or update Atlas tags. The created or updated tag is highlighted in the tag list as seen in the following diagram.

Data Catalog / Atlas Tags

passport2 created successfully

Tags (Atlas Tags)

Tag	Description	Created By	Created On
passport2	check	csso_ssudhindra	Mar 12 2021 16:52:12
passport1	check	csso_ssudhindra	Mar 12 2021 16:50:49
dp_JRL_Passport_Detection	dp_JRL_Passport_Detection	dpprofiler	Mar 12 2021 15:53:23
dp_ITA_Passport_Detection	dp_ITA_Passport_Detection	dpprofiler	Mar 12 2021 15:53:23
dp_FRA_Passport_Detection	dp_FRA_Passport_Detection	dpprofiler	Mar 12 2021 15:53:23
dp_BEL_Passport_Detection	dp_BEL_Passport_Detection	dpprofiler	Mar 12 2021 15:53:23
dp_GRC_Passport_Detection	dp_GRC_Passport_Detection	dpprofiler	Mar 12 2021 15:53:23
dp_ITA_NationalID_Detection	dp_ITA_NationalID_Detection	dpprofiler	Mar 12 2021 15:53:23
dp_bankaccount	dp_bankaccount	dpprofiler	Mar 12 2021 15:53:23
dp_PRT_IBAN_Detection	dp_PRT_IBAN_Detection	dpprofiler	Mar 12 2021 15:53:23
dp_POL_IBAN_Detection	dp_POL_IBAN_Detection	dpprofiler	Mar 12 2021 15:53:23
dp_BGR_IBAN_Detection	dp_BGR_IBAN_Detection	dpprofiler	Mar 12 2021 15:53:23
dp_FIN_IBAN_Detection	dp_FIN_IBAN_Detection	dpprofiler	Mar 12 2021 15:53:23


You can also edit or delete the Atlas tag as shown in the image. When you are editing the tag, you can only change the description or add new attributes.

Data Catalog / Atlas Tags

Tags (Atlas Tags)

Tag	Description	Created By	Created On
passport2	check	csso_ssudhindra	Mar 12 2021 16:52:12
passport1	check	csso_ssudhindra	Mar 12 2021 16:50:49
dp_JRL_Passport_Detection	dp_JRL_Passport_Detection	dpprofiler	Mar 12 2021 15:53:23
dp_ITA_Passport_Detection	dp_ITA_Passport_Detection	dpprofiler	Mar 12 2021 15:53:23
dp_FRA_Passport_Detection	dp_FRA_Passport_Detection	dpprofiler	Mar 12 2021 15:53:23
dp_BEL_Passport_Detection	dp_BEL_Passport_Detection	dpprofiler	Mar 12 2021 15:53:23
dp_GRC_Passport_Detection	dp_GRC_Passport_Detection	dpprofiler	Mar 12 2021 15:53:23
dp_ITA_NationalID_Detection	dp_ITA_NationalID_Detection	dpprofiler	Mar 12 2021 15:53:23
dp_bankaccount	dp_bankaccount	dpprofiler	Mar 12 2021 15:53:23
dp_PRT_IBAN_Detection	dp_PRT_IBAN_Detection	dpprofiler	Mar 12 2021 15:53:23
dp_POL_IBAN_Detection	dp_POL_IBAN_Detection	dpprofiler	Mar 12 2021 15:53:23
dp_BGR_IBAN_Detection	dp_BGR_IBAN_Detection	dpprofiler	Mar 12 2021 15:53:23
dp_FIN_IBAN_Detection	dp_FIN_IBAN_Detection	dpprofiler	Mar 12 2021 15:53:23
dp_JRL_IBAN_Detection	dp_JRL_IBAN_Detection	dpprofiler	Mar 12 2021 15:53:23

You can delete one Atlas tag at a time. A separate confirmation message appears.




Tagging Multiple Assets

On the Data Catalog search page, you can add tags to multiple assets based on the asset type that you select based on the search result.

When you select an asset, you can add one or more available tags to the selected asset. You can also create one or more new tags and associate the newly created tags to the selected asset. The number of selected assets that you plan to tag is displayed. As you add the number of tags to one or more selected assets, The Add Tag panel displays the number of tags assigned.

Data Catalog / Search





Note: If you do not save your changes without clicking the Add button in Add Tags panel, the changes are not retained in the Data Catalog instance. You have to retag the assets and later click the Add button.

Data Catalog / Search

Q us_custome
Act Add Tags to 2 selected entities

Type	Name	Location
<input type="checkbox"/>	HDFS Path	/warehouse/tablespace/external/hive/t... /hdfs://dc-pro-9jcxz-master0.dc-pro-6.svbr-n...
<input checked="" type="checkbox"/>	Hive Table	us_customers /hortoniabank
<input type="checkbox"/>	Hive Column	emailaddress /hortoniabank.us_customers.emailaddress@cm
<input type="checkbox"/>	Hive Column	tropicalzodiac /hortoniabank.us_customers.tropicalzodiac@...
<input type="checkbox"/>	Hive Column	age /hortoniabank.us_customers.age@cm
<input type="checkbox"/>	Hive Column	vehicle /hortoniabank.us_customers.vehicle@cm
<input type="checkbox"/>	Hive Column	height /hortoniabank.us_customers.height@cm
<input checked="" type="checkbox"/>	Hive Column	zipcode /hortoniabank.us_customers.zipcode@cm
<input type="checkbox"/>	Hive Column	weight /hortoniabank.us_customers.weight@cm
<input type="checkbox"/>	Hive Column	givenname /hortoniabank.us_customers.givenname@cm
<input type="checkbox"/>	Hive Column	country /hortoniabank.us_customers.country@cm
<input type="checkbox"/>	Hive Column	latitude /hortoniabank.us_customers.latitude@cm
<input type="checkbox"/>	Hive Column	streetaddress /hortoniabank.us_customers.streetaddress@cm
<input type="checkbox"/>	Hive Column	ccexpires /hortoniabank.us_customers.ccexpires@cm
<input type="checkbox"/>	Hive Column	insuranceid /hortoniabank.us_customers.insuranceid@cm
<input type="checkbox"/>	Hive Column	domain /hortoniabank.us_customers.domain@cm
<input type="checkbox"/>	Hive Column	middleinitial /hortoniabank.us_customers.middleinitial@cm
<input type="checkbox"/>	Hive Column	occupation /hortoniabank.us_customers.occupation@cm
<input type="checkbox"/>	Hive Column	telephonenumber /hortoniabank.us_customers.telephonenumber@cm
<input type="checkbox"/>	Hive Column	mothersmaiden /hortoniabank.us_customers.mothersmaiden@cm

Filters

TYPE Clear ^

Q
↺
Add Tag

Tag ↑	Description
<input type="checkbox"/>	dp dp
<input type="checkbox"/>	dp_AUT_IBAN_Detection dp_AUT_IBAN_Detect...
<input type="checkbox"/>	dp_AUT_Passport_Dete... dp_AUT_Passport_De...
<input type="checkbox"/>	dp_bankaccount dp_bankaccount
<input checked="" type="checkbox"/>	dp_BEL_IBAN_Detection dp_BEL_IBAN_Detecti...
status* (string) <input type="text" value="abcd"/>	
<input checked="" type="checkbox"/>	dp_BEL_Passport_Detec... dp_BEL_Passport_De...
status* (string) <input type="text" value="sdgf"/>	
<input checked="" type="checkbox"/>	dp_BGR_IBAN_Detection dp_BGR_IBAN_Detect...
status* (string) <input type="text" value="cdjh"/>	
<input type="checkbox"/>	dp_BGR_NationalID_Det... dp_BGR_NationalID_...
<input type="checkbox"/>	dp_CHE_IBAN_Detection dp_CHE_IBAN_Detect...
<input checked="" type="checkbox"/>	dp_CHE_Passport_Dete... dp_CHE_Passport_De...
status* (string) <input type="text" value="kjhd"/>	
<input type="checkbox"/>	dp_creditcard dp_creditcard
<input type="checkbox"/>	dp_custom_tag_policyic4 dp_custom_tag_polic...
<input type="checkbox"/>	dp_custom_tag_policyc... dp_custom_tag_polic...

Add
Cancel
4 selected

When you add one or more tags to the selected entities, the assigned tags are displayed having been tagged to the number of selected entities. Another scenario could throw a message saying that the selected asset is already tagged.

Propagated Asset tagging

Data Catalog supports the concept of propagated tags. This feature is derived from Apache Atlas.

Whenever you add a new tag, you can mark them as propagated and use those tags accordingly while tagging assets.

Data Catalog / Asset Details

employee1 Atlas

Properties

Type: HIVE TABLE
of Columns: 4
Data Lake: [redacted]
Datasets: 0
Owner: [redacted]
Created On: Mon Mar 15 2021 14:21:43 GMT+0530 (India Stan...
Last Access Time: Mon Mar 15 2021 14:21:43 GMT+0530 (Indi...
Table Type: EXTERNAL_TABLE
Database: default
DB Catalog: [redacted]
Parent: default

Qualified Name
default.employee1@cm

Comment
[+ Add Comment](#)

Description
[+ Add Description](#)

Profilers | 2

Cluster Sensitivity Profiler
Last run: 21 mins ago | Status: SUCCESS
Next Schedule Run: Wednesday at 3:50 PM Run

Hive Column Profiler
Last run: - | Status: NA
Next Schedule Run: Today at 5:30 PM Run

Classifications | 4 Managed System Propagated

test_tag1 test_tag dp_email dp

Overview Schema Metadata Audits Policy Access Audits

Lineage Filter Search Refresh

```

graph LR
    A[warehouse/tables...] --> B[employee1]
    B --> C[employee2]
  
```

For example, consider table1 as a parent asset and table2 as a child asset. Create a tag and mark that tag as propagated, and later apply the same tag to table1. The tag gets applied to table2 as well. Propagated tag works on the basis of parent -> child tagging relationship.

Data Catalog / Asset Details

employee2 Atlas

Properties

Type: HIVE TABLE
of Columns: 4
Data Lake: [redacted]
Datasets: 0
Owner: [redacted]
Created On: Mon Mar 15 2021 15:01:11 GMT+0530 (India Stan...
Last Access Time: Mon Mar 15 2021 15:01:11 GMT+0530 (Indi...
Table Type: MANAGED_TABLE
Database: default
DB Catalog: [redacted]
Parent: default

Qualified Name
default.employee2@cm

Comment
[+ Add Comment](#)

Description
[+ Add Description](#)

Profilers | 2

Cluster Sensitivity Profiler
Last run: - | Status: NA
Next Schedule Run: Today at 3:50 PM Run

Hive Column Profiler
Last run: - | Status: NA
Next Schedule Run: Today at 5:30 PM Run

Classifications | 4 Managed System Propagated

test_tag1 test_tag dp_email dp

Overview Schema Metadata Audits Policy Access Audits

Lineage Filter Search Refresh

```

graph LR
    A[warehouse/tables...] --> B[employee1]
    B --> C[employee2]
  
```



Note: When you delete or remove the propagated tag from the parent asset, the same tag is removed from all the child assets.



Attention: The propagated tag concept is not supported with child -> parent relationships.

Creating Custom Profiler Rules

You can create a custom profiler by adding the required tags, regex entries, and attaching whitelist or blacklist files to specific columns within your tables.

Procedure

1. On the Profilers page, click Tag Rules.
2. On the Tag Rules tab, click New to create a new profiler tag rule.
3. Enter the name of the new custom profiler tag rule.
4. Enter the description for the custom tag rule.
5. Select the Tags. You can select tags from the drop down list and or enter a new value to create a new tag.
New tags that you create here are added with a dp_ prefix in the list of Atlas tags. For example, if you add a new tag called credit_card, this tag will be added as dp_credit_card in Atlas.
6. Enter the rule for the column name. As you enter the values, regex name and resource names are auto populated. Select the column that is needed for your custom profiler.
7. Enter the column value for the DSL.

Based on your entry, Data Catalog auto populates values from the entries already available in the Resources tab. You can use a combination of regex entries and whitelist or blacklist files and other behaviors. For more information about behaviors, see DSL Grammar.

8. Click Save and Validate.

Data Catalog / Profilers

Custom Rule

Name *

Description

Tags *

Column Name Expression

Column Value Expression *

Resources

Regex Q +

SampleRegex_1580209003967
SampleRegex_1.58020939186e+12
DeployRegex1580209681238
SampleRegex_1.58020999412e+12
SampleRegex_1.58021014275e+12
SampleRegex_1.58021014308e+12
DeployRegex1580210288950
SampleRegex_1580276618318
SampleRegex_1580277217453

In the validation pop up window that appears, enter data to validate your custom profiler tag rule. Make sure you separate each data entry with a new line.

9. Click Save to create a tag rule and validate and deploy it later.

Adding Custom Regular Expressions

To use custom regex entries within your new custom profiler tag rules, you can also add new regex values.

Procedure

1. Click Resources in the right panel on the New Custom Profiler Rules page.
2. Click + icon on the Regex tab. The Regular Expression Editor page appears.
3. Enter the name of the new regular expression.

4. Enter a valid regular expression.

For example:

```
\b((([a-zA-Z0-9_-\.\ ]+))@((\[[0-9]{1,3}\.[0-9]{1,3}\.[0-9]{1,3}\.))|((([a-zA-Z0-9_-\ ]+\.)))+))([a-zA-Z]{2,4}|[0-9]{1,3})(\ )?\b
```

5. Enter the list of test strings to evaluate the new regular expression.
If the test string is valid, then the match information gets auto populated in the Match Information box.
6. Click Save to add the new regular expression to the list of Regex Resources.

Adding Lookup Files

When you have too many allowed and denied entries and cannot add them inline, you can create allowed or denied files with one value in each line and add them to your DSL.

Procedure

1. Click Resources in the right panel on the New Custom Profiler Rules page.
2. Click + icon on the Lookups tab. The New Lookup File page appears.
3. Enter the name of the new Lookup file.
4. Click Choose File to upload the file.
5. Click Save.

Using Behaviors

You can use various behaviors to take single inputs of type text and evaluate them to a Boolean value.

The profiler can take column values of any type and pass the values to each behaviour as text. Behaviors include the following:

1. Regular expressions
2. File based allowlist and denylist checks
3. File based allowlist and denylist checks
4. Luhn algorithm

Regular expressions

You can include one or more regular expressions and evaluate to True if one of these matches the provided value.

Keyword: regex

A regex that matches everything can be defined as follows:

```
regex(\"[\\\\\\\\s\\\\\\\\S]+\")
```

A regex that includes multiple expressions can be defined as follows:

```
regex(\"[\\\\\\\\s\\\\\\\\S]+\", \"^[0-9]*$\")
```

File based denylist and allowlist checks

When the number of allowlist and denylist entries are many and cannot be defined inline, you can create allowlist or denylist files with one value in each line.

Keywords: allow-list, deny-list

Make sure to place the file in an HDFS location that is accessible to the Profiler Agent user.

You can provide the location of the file as an attribute in the DSL definition.

For example:

```
whitelist(\"/apps/dpprofiler/profilers/sensitive_info_profiler/1.0/lib/kraptr/meta/whitelist\")
```

```
blacklist(\"/apps/dpprofiler/profilers/sensitive_info_profiler/1.0/lib/kraptr/meta/blacklist\")
```

Luhn algorithm

You can do a Luhn check on identification numbers in columns.

Keyword: luhn_check

Use the Luhn algorithm or Luhn formula to validate a variety of identification numbers such as credit card number, IMEI numbers, National Provider Identifier numbers in the United States, Canadian Social Insurance numbers, Israel ID Numbers, and Greek Social Security Numbers.

Using DSL Grammar

Using DSL grammar, you can combine different behaviours in intuitive ways to bring out functionality while creating custom profiler rules.

The two behaviors available in this framework are as follows:

1. falseIdentity - Always evaluates to false, regardless of the input.
2. trueIdentity - Always evaluates to true, regardless of the input.

These two behaviors are used in the following examples and descriptions.

Binary AND operator

Keyword: and

And works the same way it does other languages. Hence following observations.

```
falseIdentity and trueIdentity == falseIdentity
```

```
falseIdentity and falseIdentity == falseIdentity
```

```
trueIdentity and trueIdentity == trueIdentity
```

```
trueIdentity and falseIdentity == falseIdentity
```

Here we are using == to show their equality.

Binary OR operator

The or operator works the same way it does in other languages.

```
falseIdentity or trueIdentity == trueIdentity
```

```
falseIdentity or falseIdentity == falseIdentity
```

```
trueIdentity or trueIdentity == trueIdentity
```

```
trueIdentity or falseIdentity == trueIdentity
```

Expand DSL to use as follows.

```
val rule1= falseIdentity and trueIdentity and trueIdentity
```

```
val rule2= trueIdentity and trueIdentity and trueIdentity
```

```
val rule3=rule1 and rule2
```

```
rule3 or trueIdentity
```

The above expression evaluates to true.