

Cloudera Runtime 7.0.2

Ranger Authorization

Date published: 2019-11-01

Date modified:

CLOUDERA

<https://docs.cloudera.com/>

Legal Notice

© Cloudera Inc. 2024. All rights reserved.

The documentation is and contains Cloudera proprietary information protected by copyright and other intellectual property rights. No license under copyright or any other intellectual property right is granted herein.

Unless otherwise noted, scripts and sample code are licensed under the Apache License, Version 2.0.

Copyright information for Cloudera software may be found within the documentation accompanying each component in a particular release.

Cloudera software includes software from various open source or other third party projects, and may be released under the Apache Software License 2.0 (“ASLv2”), the Affero General Public License version 3 (AGPLv3), or other license terms. Other software included may be released under the terms of alternative open source licenses. Please review the license and notice files accompanying the software for additional licensing information.

Please visit the Cloudera software product page for more information on Cloudera software. For more information on Cloudera support services, please visit either the Support or Sales page. Feel free to contact us directly to discuss your specific needs.

Cloudera reserves the right to change any products at any time, and without notice. Cloudera assumes no responsibility nor liability arising from the use of products, except as expressly agreed to in writing by Cloudera.

Cloudera, Cloudera Altus, HUE, Impala, Cloudera Impala, and other Cloudera marks are registered or unregistered trademarks in the United States and other countries. All other trademarks are the property of their respective owners.

Disclaimer: EXCEPT AS EXPRESSLY PROVIDED IN A WRITTEN AGREEMENT WITH CLOUDERA, CLOUDERA DOES NOT MAKE NOR GIVE ANY REPRESENTATION, WARRANTY, NOR COVENANT OF ANY KIND, WHETHER EXPRESS OR IMPLIED, IN CONNECTION WITH CLOUDERA TECHNOLOGY OR RELATED SUPPORT PROVIDED IN CONNECTION THEREWITH. CLOUDERA DOES NOT WARRANT THAT CLOUDERA PRODUCTS NOR SOFTWARE WILL OPERATE UNINTERRUPTED NOR THAT IT WILL BE FREE FROM DEFECTS NOR ERRORS, THAT IT WILL PROTECT YOUR DATA FROM LOSS, CORRUPTION NOR UNAVAILABILITY, NOR THAT IT WILL MEET ALL OF CUSTOMER’S BUSINESS REQUIREMENTS. WITHOUT LIMITING THE FOREGOING, AND TO THE MAXIMUM EXTENT PERMITTED BY APPLICABLE LAW, CLOUDERA EXPRESSLY DISCLAIMS ANY AND ALL IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO IMPLIED WARRANTIES OF MERCHANTABILITY, QUALITY, NON-INFRINGEMENT, TITLE, AND FITNESS FOR A PARTICULAR PURPOSE AND ANY REPRESENTATION, WARRANTY, OR COVENANT BASED ON COURSE OF DEALING OR USAGE IN TRADE.

Contents

Using Ranger to Provide Authorization in CDP.....	5
Ranger Policies Overview.....	5
Ranger tag-based policies.....	5
Tags and policy evaluation.....	6
Ranger access conditions.....	8
Using the Ranger Console.....	10
Accessing the Ranger console.....	11
Ranger console navigation.....	12
Resource-based Services and Policies.....	15
Configuring resource-based services.....	15
Configure a resource-based service: Atlas.....	15
Configure a resource-based service: HBase.....	17
Configure a resource-based service: HDFS.....	19
Configure a resource-based service: Hive.....	21
Configure a resource-based service: Kafka.....	23
Configure a resource-based service: Knox.....	25
Configure a resource-based service: NiFi.....	27
Configure a resource-based service: NiFi Registry.....	29
Configure a resource-based service: Solr.....	31
Configure a resource-based service: YARN.....	33
Configuring resource-based policies.....	35
Configure a resource-based policy: Atlas.....	36
Configure a resource-based policy: HBase.....	37
Configure a resource-based policy: HDFS.....	39
Configure a resource-based policy: Hive.....	41
Configure a resource-based policy: Kafka.....	44
Configure a resource-based policy: Knox.....	46
Configure a resource-based policy: NiFi.....	48
Configure a resource-based policy: NiFi Registry.....	50
Configure a resource-based policy: Solr.....	52
Configure a resource-based policy: YARN.....	54
Wildcards and variables in resource-based policies.....	56
Preloaded resource-based services and policies.....	57
Importing and exporting resource-based policies.....	62
Import resource-based policies for a specific service.....	64
Import resource-based policies for all services.....	66
Export resource-based policies for a specific service.....	69
Export all resource-based policies for all services.....	70
Row-level filtering and column masking in Hive.....	72
Row-level filtering in Hive with Ranger policies.....	72
Dynamic resource-based column masking in Hive with Ranger policies.....	81
Dynamic tag-based column masking in Hive with Ranger policies.....	89

Tag-based Services and Policies.....	95
Adding a tag-based service.....	95
Adding tag-based policies.....	102
Using tag attributes and values in Ranger tag-based policy conditions.....	107
Adding a tag-based PII policy.....	108
Default EXPIRES ON tag policy.....	115
Importing and exporting tag-based policies.....	120
Import tag-based policies.....	122
Export tag-based policies.....	126
Create a time-bound policy.....	132
Ranger Security Zones.....	134
Overview.....	134
Adding a Ranger security zone.....	135
Administering Ranger Users, Groups, Roles, and Permissions.....	153
Add a user.....	155
Edit a user.....	160
Delete a user.....	166
Add a group.....	167
Edit a group.....	172
Delete a group.....	179
Add or edit permissions.....	182
Administering Ranger Reports.....	184
View Ranger reports.....	186
Search Ranger reports.....	188
Export Ranger reports.....	190

Using Ranger to Provide Authorization in CDP

Apache Ranger manages access control through a user interface that ensures consistent policy administration across Cloudera Data Platform (CDP) components. Security administrators can define security policies at the database, table, column, and file levels, and can administer permissions for specific LDAP-based groups or individual users. Rules based on dynamic conditions such as time or geolocation can also be added to an existing policy rule. The Ranger authorization model is pluggable and can be easily extended to any data source using a service-based definition.

Once a user has been authenticated, their access rights must be determined. Authorization defines user access rights to resources. For example, a user may be allowed to create a policy and view reports, but not allowed to edit users and groups. You can use Ranger to set up and manage access to Hadoop services.

Ranger enables you to create services for specific resources (HDFS, HBase, Hive, etc.) and add access policies to those services. Ranger security zones enable you to organize service resources into multiple security zones. You can also create tag-based services and add access policies to those services. Using tag-based policies enables you to control access to resources across multiple components without creating separate services and policies in each component. You can also use Ranger TagSync to synchronize the Ranger tag store with an external metadata service such as Apache Atlas.

Ranger Policies Overview

Ranger has two types of policies: resource-based and tag-based.

Resource-based policies

Ranger enables you to configure resource-based services (HDFS, HBase, Hive, etc.) and add access policies to those services.

Tag-based policies

Ranger enables you to create tag-based services and add access policies to those services.

Ranger tag-based policies

Ranger enables you to create tag-based services and add access policies to those services.

Tag-Based Policies Overview

- An important feature of Ranger tag-based authorization is the separation of resource-classification from access-authorization. For example, resources (HDFS file/directory, Hive database/table/column etc.) containing sensitive data such as social security numbers, credit card numbers, or sensitive health care data can be tagged with PII/PCI/PHI – either as the resource enters the Hadoop ecosystem or at a later time. Once a resource is tagged, the authorization for the tag would be automatically enforced, thus eliminating the need to create or update policies for the resource.
- Using tag-based policies also enables you to control access to resources across multiple Hadoop components without creating separate services and policies in each component.
- Tag details are stored in a tag store. Ranger TagSync can be used to synchronize the tag store with an external metadata service such as Apache Atlas.

Tag Store

Details of tags associated with resources are stored in a tag store. Apache Ranger plugins retrieve the tag details from the tag store for use during policy evaluation. To minimize the performance impact during policy evaluation (in

finding tags for resources), Apache Ranger plugins cache the tags and periodically poll the tag store for any changes. When a change is detected, the plugins update the cache. In addition, the plugins store the tag details in a local cache file – just as the policies are stored in a local cache file. On component restart, the plugins will use the tag data from the local cache file if the tag store is not reachable.

Apache Ranger plugins download the tag details from the store managed by Ranger Admin. Ranger Admin persists the tag details in its policy store and provides a REST interface for the plugins to download the tag details.

Tags

Ranger Tags can have attributes. Tag attribute values can be used in Ranger tag-based policies to influence the authorization decision.

For example, to deny access to a resource after a specific date:

1. Add the EXPIRES_ON tag to the resource.
2. Add an expiry_date tag attribute and set its value to the expiry date.
3. Create a Ranger policy for the EXPIRES_ON tag.
4. Add a condition in this policy to deny access when the date specified in the expiry_date tag attribute is later than the current date.

Note that the EXPIRES_ON tag policy is created as the default policy in tag service instances.

TagSync


Ranger TagSync is used to synchronize the tag store with an external metadata service such as Apache Atlas. TagSync is a daemon process similar to the Ranger UserSync process.

Ranger TagSync receives tag details from Apache Atlas via change notifications. As tags are added to, updated, or deleted from resources in Apache Atlas, Ranger TagSync receives notifications and updates the tag store.

Tags and policy evaluation

When authorizing an access request, an Apache Ranger plugin evaluates applicable Ranger policies for the resource being accessed. The following diagram shows the details of the policy evaluation flow. More details on the steps in this workflow are provided in the subsequent sections.

Apache Ranger Policy Evaluation Flow with Tags



Apache Ranger Policy Evaluation Flow

Finding Tags

Apache Ranger supports a service to register context enrichers, which are used to update context data to the access request.

The Ranger Tag service, which is part of the tag-based policies feature, adds a context enricher named `RangerTagEnricher`. This context enricher is responsible for finding tags for the requested resource and adding the tag details to the request context. This context enricher keeps a cache of the available tags; while processing an access request, it finds the tags applicable for the requested resource and adds the tags to the request context. The context enricher keeps the cache updated by periodically polling Ranger Admin for changes.

Evaluating Tag-Based Policies

Once the list of tags for the requested resource is found, the Apache Ranger policy engine evaluates the tag-based policies applicable to the tags. If a policy for one of these tag results in a deny, access will be denied. If none of the tags are denied, and if a policy allows for one of the tags, access will be allowed. If there is no result for any tag, or if there are no tags for the resource, the policy engine will evaluate the resource-based policies to make the authorization decision.

Using Tags in Conditions

Apache Ranger allows the use of custom conditions while evaluating authorization policies. The Apache Ranger policy engine makes various request details – such as user, groups, resource, and context – available to the conditions. Tags in the request context, which are added by the enricher, are available to the conditions and can be used to influence the authorization decision.

The default policy in tag service instances, the EXPIRES_ON tag, uses such condition to check to see if the request date is later than the value specified in tag attribute expiry_date. This default policy does not work unless an EXPIRES_ON tag has been created in Atlas.

Related Information

[Apache Ranger Wiki > Context Enrichers](#)

Ranger access conditions

The Apache Ranger access policy model consists of two major components: specification of the resources a policy is applied to, such as HDFS files and directories, Hive databases, tables, and columns, HBase tables, column-families, and columns, and so on; and the specification of access conditions for specific users and groups

Allow Deny and Exclude Conditions

Apache Ranger supports the following access conditions:

- Allow
- Exclude from Allow
- Deny
- Exclude from Deny

These access conditions enable you to set up fine-grained access control policies.

For example, you can allow access to a "finance" database to all users in the "finance" group, but deny access to all users in the "interns" group. Let's say that one of the members of the "interns" group, "scott", needs to work on an assignment that requires access to the "finance" database. In that case, you can add an Exclude from Deny condition that will allow user "scott" to access the "finance" database. The following image shows how this policy would be set up in Apache Ranger:

Policy Details :

Policy ID **15**

Policy Name * enabled

Hive Database * include

table * include

Hive Column * include

Description

Audit Logging YES

Allow Conditions :

Select Group	Select User	Permissions	Delegate Admin	
<input type="text" value="x finance"/>	<input type="text" value="Select User"/>	<input checked="" type="checkbox"/> All <input type="checkbox"/> [edit]	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>

Exclude from Allow Conditions :

Deny Conditions :


Select Group	Select User	Permissions	Delegate Admin	
<input type="text" value="x interns"/>	<input type="text" value="Select User"/>	<input checked="" type="checkbox"/> All <input type="checkbox"/> [edit]	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>

Exclude from Deny Conditions :

Select Group	Select User	Permissions	Delegate Admin	
<input type="text" value="Select Group"/>	<input type="text" value="x SCOTT"/>	<input checked="" type="checkbox"/> select <input type="checkbox"/> [edit]	<input type="checkbox"/>	<input checked="" type="checkbox"/>

Policy Evaluation of Access Conditions

Apache Ranger policies are evaluated in a specific order to ensure predictable results (if there is no access policy that allows access, the authorization request will typically be denied). The following diagram shows the policy evaluation work-flow:



Apache Ranger Policy Evaluation Flow


Using the Ranger Console

This chapter contains an overview of the Ranger console.


Accessing the Ranger console

How to access the Ranger console.

To access the Ranger Console, click the Ranger link on the applicable CDP environment page, enter your user name and password, then click Sign In.

The image shows the Ranger Console Home Page. At the top, the word "Ranger" is displayed in a large, white, sans-serif font against a dark background. Below this, there is a sign-in form with a dark background and light-colored text and input fields. The form contains two input fields: "Username:" with the text "admin" entered, and "Password:" with a masked password represented by seven dots. Below the input fields is a blue button with the text "Sign In" in white.

Ranger Console Home Page




After you log in, your user name is displayed at the top right of the Ranger Console.


Ranger console navigation

Explains the basic Ranger console/GUI.

- The Service Manager for Resource Based Policies page is displayed when you log in to the Ranger Console. You can use this page to create services for Hadoop resources (HDFS, HBase, Hive, etc.) and add access policies to those resources.




Clicking Access Manager in the top menu opens the Service Manager for Resource Based Policies page, and also displays a submenu with links to Resource Based Policies, Tag Based Policies, and Reports (this submenu is also displayed when you pass the mouse over the Access Manager link).




- Access Manager > Resource Based Policies -- Opens the Service Manager for Resource Based Policies page. You can use this page to create services for resources (HDFS, HBase, Hive, etc.) and add access policies to those services.
- Access Manager > Tag Based Policies -- Opens the Service Manager for Tag Based Policies page. You can use this page to create tag-based services and add access policies to those services. Using tag-based policies enables you to control access to resources across multiple components without creating separate services and policies in each component.
- Access Manager > Reports -- Opens the Reports page. You can use this page to generate user access reports for resource and tag-based policies based on search criteria such as policy name, resource, group, and user name.


- Audit -- You can use the Audit page to monitor user activity at the resource level, and also to set up conditional auditing based on users, groups, or time. The Audit page includes the Access, Admin, Login Sessions, Plugins, Plugin Status, and User Sync tabs.



- Security Zone -- Lets you organize resource and tag-based services and policies into separate security zones. You can assign one or more administrators for each security zone. Security zone administrators can then create and update policies for their security zone.



- Settings -- Enables you to manage and assign policy permissions to users and groups. Clicking or passing the mouse over Settings displays a submenu with links to the Users/Groups/Roles and Permissions pages.







Resource-based Services and Policies

Ranger enables you to configure resource-based services for Hadoop components (e.g. HBase, Kafka, Storm, etc.) and add access policies to those services.

Configuring resource-based services

The Service Manager for Resource Based Policies page is displayed when you log in to the Ranger Console. You can also access this page by selecting Access Manager > Resource Based Policies. You can use this page to create services for Hadoop resources (HDFS, HBase, Hive, etc.) and add access policies to those resources.

- To add a new resource-based service, click the Add icon () in the applicable box on the Service Manager page. Enter the required configuration settings, then click Add.
- To edit a resource-based service, click the Edit icon () at the right of the service. Edit the service settings, then click Save to save your changes.
- To delete a resource-based service, click the Delete icon () at the right of the service. Deleting a service also deletes all of the policies for that service.




The screenshot displays the Ranger Service Manager interface. At the top, there is a navigation bar with 'Ranger', 'Access Manager', 'Audit', 'Security Zone', and 'Settings'. The main area is titled 'Service Manager' and includes a 'Security Zone' dropdown menu and 'Import' and 'Export' buttons. Below this, there are several service cards for HDFS, HBASE, HIVE, YARN, KNOX, SOLR, KAFKA, NIFI, NIFI-REGISTRY, ATLAS, and OZONE. Each card contains the service name, a configuration icon, and management icons for Add, Edit, and Delete. Blue arrows point from the 'Add', 'Edit', and 'Delete' labels to the corresponding icons on the SOLR service card.

Configure a resource-based service: Atlas


How to add an Atlas service.

Procedure

1.

On the Service Manager page, click the Add icon () next to Atlas.

The Create Service page appears.



2. Enter the following information on the Create Service page:

Table 1: Service Details

Field name	Description
Service Name	The name of the service; required when configuring agents.
Description	A description of the service.
Active Status	Enabled or Disabled.

Field name	Description
Select Tag Service	Select a tag-based service to apply the service and its tag-based policies to Atlas.

Table 2: Configuration Properties

Field name	Description
Username	The end system username that can be used for connection.
Password	The password for the username entered above.
atlas.rest.address	Atlas host and port: : http://atlas_host_FQDN:21000.
Common Name For Certificate	The name of the certificate. This field is interchangeably named Common Name For Certificate and Ranger Plugin SSL CName in Create Service pages.
Add New Configurations	Add any other new configuration(s).


3. Click Test Connection.
4. Click Add.


Configure a resource-based service: HBase

How to add an HBase service.

Procedure

1.

On the Service Manager page, click the Add icon () next to HBase. The Create Service page appears.



2. Enter the following information on the Create Service page:

Table 3: Service Details

Field name	Description
Service Name	The name of the service; required when configuring agents.
Description	A description of the service.

Field name	Description
Active Status	Enabled or Disabled.
Select Tag Service	Select a tag-based service to apply the service and its tag-based policies to HBase.

Table 4: Configuration Properties


Field name	Description
Username	The end system username that can be used for connection.
Password	The password for the username entered above.
hadoop.security.authorization	The complete connection URL, including port and database name. (Default port: 10000.) For example, on the sandbox, jdbc:hive2://sandbox:10000/.
hbase.master.kerberos.principal	The Kerberos principal for the HBase Master. (Required only if Kerberos authentication is enabled.)
hbase.security.authentication	As noted in the hadoop configuration file hbase-site.xml.
hbase.zookeeper.property.clientPort	As noted in the hadoop configuration file hbase-site.xml.
hbase.zookeeper.quorum	As noted in the hadoop configuration file hbase-site.xml.
zookeeper.znode.parent	As noted in the hadoop configuration file hbase-site.xml.
Common Name for Certificate	The name of the certificate. This field is interchangeably named Common Name For Certificate and Ranger Plugin SSL CName in Create Service pages.
Add New Configurations	Add any other new configuration(s).

3. Click Test Connection.
4. Click Add.

Configure a resource-based service: HDFS

How to add an HDFS service.

Procedure

1. On the Service Manager page, click the Add icon () next to HDFS. The Create Service page appears.

2. Enter the following information on the Create Service page:

Table 5: Service Details

Field name	Description
Service Name	The name of the service; required when configuring agents.

Field name	Description
Description	A description of the service.
Active Status	Enabled or Disabled.
Select Tag Service	Select a tag-based service to apply the service and its tag-based policies to HDFS.

Table 6: Configuration Properties

Field name	Description
Username	The end system username that can be used for connection.
Password	The password for the username entered above.
NameNode URL	hdfs://NAMENODE_FQDN:8020 The location of the Hadoop HDFS service, as noted in the hadoop configuration file core-site.xml OR (if this is a HA environment) the path for the primary NameNode. This field was formerly named fs.defaultFS.
Authorization Enabled	Authorization involves restricting access to resources. If enabled, user need authorization credentials.
Authentication Type	The type of authorization in use, as noted in the hadoop configuration file core-site.xml; either simple or Kerberos. (Required only if authorization is enabled). This field was formerly named hadoop.security.authorization.
hadoop.security.auth_to_local	Maps the login credential to a username with Hadoop; use the value noted in the hadoop configuration file, core-site.xml.
dfs.datanode.kerberos.principal	The principal associated with the datanode where the service resides, as noted in the hadoop configuration file hdfs-site.xml. (Required only if Kerberos authentication is enabled).
dfs.namenode.kerberos.principal	The principal associated with the NameNode where the service resides, as noted in the hadoop configuration file hdfs-site.xml. (Required only if Kerberos authentication is enabled).
dfs.secondary.namenode.kerberos.principal	The principal associated with the secondary NameNode where the service resides, as noted in the hadoop configuration file hdfs-site.xml. (Required only if Kerberos authentication is enabled).
RPC Protection Type	Only authorised user can view, use, and contribute to a dataset. A list of protection values for secured SASL connections. Values: Authentication, Integrity, Privacy
Common Name For Certificate	The name of the certificate. This field is interchangeably named Common Name For Certificate and Ranger Plugin SSL CName in Create Service pages.
Add New Configurations	Add any other new configuration(s).


3. Click Test Connection.
4. Click Add.

Configure a resource-based service: Hive


How to add a Hive service.

Procedure

1.

On the Service Manager page, click the Add icon () next to Hive.

The Create Service page appears.



2. Enter the following information on the Create Service page:

Table 7: Service Details

Field name	Description
Service Name	The name of the service; required when configuring agents.
Description	A description of the service.
Active Status	Enabled or Disabled.

Field name	Description
Select Tag Service	Select a tag-based service to apply the service and its tag-based policies to Hive.

Table 8: Configuration Properties

Field name	Description
Username	The end system username that can be used for connection.
Password	The password for the username entered above.
jdbc.driver ClassName	The full classname of the driver used for Hive connections. Default: org.apache.hive.jdbc.HiveDriver
jdbc.url	The complete connection URL, including port and database name. (Default port: 10000.) For example, on the sandbox, jdbc:hive2://sandbox:10000/.
Common Name For Certificate	The name of the certificate. This field is interchangeably named Common Name For Certificate and Ranger Plugin SSL CName in Create Service pages.
Add New Configurations	Add any other new configuration(s).


3. Click Test Connection.
4. Click Add.

Configure a resource-based service: Kafka


How to add a Kafka service.

Procedure

1.

On the Service Manager page, click the Add icon () next to Kafka.

The Create Service page appears.



2. Enter the following information on the Create Service page:

Table 9: Service Details

Field name	Description
Service Name	The name of the service; required when configuring agents.
Description	A description of the service.
Active Status	Enabled or Disabled.

Field name	Description
Select Tag Service	Select a tag-based service to apply the service and its tag-based policies to Kafka.

Table 10: Configuration Properties


Field name	Description
Username	The end system username that can be used for connection.
Password	The password for the username entered above.
ZooKeeper Connect String	Defaults to localhost:2181 (Provide FQDN of zookeeper host : 2181).
Ranger Plugin SSL CName	Provide common.name.for.certificate which is registered with Ranger (in Wire Encryption environment). This field is interchangeably named Common Name For Certificate and Ranger Plugin SSL CName in Create Service pages.
Add New Configurations	Add any other new configuration(s).


3. Click Test Connection.
4. Click Add.

Configure a resource-based service: Knox

How to add a Knox service.

Procedure

1. On the Service Manager page, click the Add icon () next to Knox.
The Create Service page appears.



2. Enter the following information on the Create Service page:

Table 11: Service Details

Field name	Description
Service Name	The name of the service; required when configuring agents.
Description	A description of the service.
Active Status	Enabled or Disabled.

Field name	Description
Select Tag Service	Select a tag-based service to apply the service and its tag-based policies to Knox.

Table 12: Configuration Properties

Field name	Description
Username	The end system username that can be used for connection.
Password	The password for the username entered above.
knox.url	The Gateway URL for Knox.
Common Name For Certificate	The name of the certificate. This field is interchangeably named Common Name For Certificate and Ranger Plugin SSL CName in Create Service pages.
Add New Configurations	Add any other new configuration(s).


3. Click Test Connection.
4. Click Add.

Configure a resource-based service: NiFi

How to add a NiFi service.

Procedure

1.

On the Service Manager page, click the Add icon () next to NiFi. The Create Service page appears.

2. Enter the following information on the Create Service page:

Table 13: Service Details

Field name	Description
Service Name	The name of the service; required when configuring agents.
Description	A description of the service.
Active Status	Enabled or Disabled.

Field name	Description
Select Tag Service	Select a tag-based service to apply the service and its tag-based policies to NiFi.

Table 14: Configuration Properties

Field name	Description
NiFi URL	The complete NiFi host URL.
Authentication Type	None or SSL.
Keystore	The keystore to use when Ranger makes an https connection to NiFi. This keystore contains the certificate that represents the Ranger server.
Keystore Type	The keystore type (JKS or PKCS12).
Keystore Password	The keystore password.
Truststore	The truststore to use when Ranger makes an https connection to NiFi. This truststore contains the public key of the certificate authority that signed the NiFi server certificates.
Truststore Type	The truststore type (JKS or PKCS12).
Truststore Password	The truststore password.
Add New Configurations	Add any other new configuration(s).


3. Click Test Connection.
4. Click Add.

Configure a resource-based service: NiFi Registry

How to add a NiFi Registry service.

Procedure

1.

On the Service Manager page, click the Add icon () next to NiFi Registry. The Create Service page appears.

2. Enter the following information on the Create Service page:

Table 15: Service Details

Field name	Description
Service Name	The name of the service; required when configuring agents.
Description	A description of the service.
Active Status	Enabled or Disabled.

Field name	Description
Select Tag Service	Select a tag-based service to apply the service and its tag-based policies to NiFi.

Table 16: Configuration Properties

Field name	Description
NiFi Registry URL	The complete NiFi Registry URL.
Authentication Type	None or SSL.
Keystore	The keystore to use when Ranger makes an https connection to the NiFi Registry. This keystore contains the certificate that represents the Ranger server.
Keystore Type	The keystore type (JKS or PKCS12).
Keystore Password	The keystore password.
Truststore	The truststore to use when Ranger makes an https connection to the NiFi Registry. This truststore contains the public key of the certificate authority that signed the NiFi server certificates.
Truststore Type	The truststore type (JKS or PKCS12).
Truststore Password	The truststore password.
Add New Configurations	Add any other new configuration(s).

3. Click Test Connection.
4. Click Add.

Configure a resource-based service: Solr


How to add a Solr service.

Procedure

1.

On the Service Manager page, click the Add icon () next to Solr.

The Create Service page appears.



2. Enter the following information on the Create Service page:

Table 17: Service Details

Field name	Description
Service Name	The name of the service; required when configuring agents.
Description	A description of the service.
Active Status	Enabled or Disabled.

Field name	Description
Select Tag Service	Select a tag-based service to apply the service and its tag-based policies to Solr.

Table 18: Configuration Properties

Field name	Description
Username	The end system username that can be used for connection.
Password	The password for the username entered above.
Solr URL	http://Solr_host:8983
Ranger Plugin SSL CName	Provide common.name.for.certificate which is registered with Ranger (in Wire Encryption environment). This field is interchangeably named Common Name For Certificate and Ranger Plugin SSL CName in Create Service pages.
Add New Configurations	Add any other new configuration(s).


3. Click Test Connection.
4. Click Add.

Configure a resource-based service: YARN

How to add a YARN service.

Procedure

1.

On the Service Manager page, click the Add icon () next to YARN.

The Create Service page appears.

2. Enter the following information on the Create Service page:

Table 19: Service Details

Field name	Description
Service Name	The name of the service; required when configuring agents.
Description	A description of the service.
Active Status	Enabled or Disabled.

Field name	Description
Select Tag Service	Select a tag-based service to apply the service and its tag-based policies to YARN.



Table 20: Configuration Properties


Field name	Description
Username	The end system username that can be used for connection.
Password	The password for the username entered above.
YARN REST URL	Http or https://RESOURCEMANAGER_FQDN:8088.
Authentication Type	The type of authorization in use, as noted in the hadoop configuration file core-site.xml; either simple or Kerberos. (Required only if authorization is enabled). This field was formerly named hadoop.security.authorization.
Common Name For Certificate	The name of the certificate. This field is interchangeably named Common Name For Certificate and Ranger Plugin SSL CName in Create Service pages.
Add New Configurations	Add any other new configuration(s).

3. Click Test Connection.
4. Click Add.

Configuring resource-based policies

To view the policies associated with a service, click the service name on the Resource Based Policies Service Manager page. The policies for that service will be displayed in a list, along with a search box.

- To add a new resource-based policy to the service, click Add New Policy.
- To edit a resource-based policy, click the Edit icon () for the service. Edit the policy settings, then click Save to save your changes.
- To delete a resource-based policy, click the Delete icon () for the service.









Ranger Access Manager Audit Security Zone Settings admin

Service Manager cm_hbase Policies

List of Policies : cm_hbase

Search for your policy... Add New Policy

Policy ID	Policy Name	Policy Labels	Status	Audit Logging	Roles	Groups	Users	Action
3	all - table, column-family, column	--	Enabled	Enabled	--	--	hbase rangerlookup	  
4	ATLAS_HBASE_TABLES	--	Enabled	Enabled	--	--	atlas	  

Related Information


[Importing and exporting resource-based policies](#)

Configure a resource-based policy: Atlas

How to add a new policy to an existing Atlas service.

Procedure

1. On the Service Manager page, select an existing Atlas service.
The List of Policies page appears.
2. Click Add New Policy.
The Create Policy page appears.



3. Complete the Create Policy page as follows:

Table 21: Policy Details

Field	Description
Policy Name	Enter an appropriate policy name. This name cannot be duplicated across the system. This field is mandatory.
normal/override	Enables you to specify an override policy. When override is selected, the access permissions in the policy override the access permissions in existing policies. This feature can be used with Add Validity Period to create temporary access policies that override existing policies.
type-category	Select type-category, entity-type, atlas-service, or relationship-type.
Description	(Optional) Describe the purpose of the policy.
Audit Logging	Specify whether this policy is audited. (De-select to disable auditing).
Policy Label	Specify a label for this policy. You can search reports and filter policies based on these labels.

Field	Description
Add Validity Period	Specify a start and end time for the policy.

Table 22: Allow Conditions

Label	Description
Select Role	Specify the roles to which this policy applies. To designate a role as an Administrator, select the Delegate Admin check box. Administrators can edit or delete the policy, and can also create child policies based on the original policy.
Select Group	Specify the groups to which this policy applies. To designate a group as an Administrator, select the Delegate Admin check box. Administrators can edit or delete the policy, and can also create child policies based on the original policy. The public group contains all users, so granting access to the public group grants access to all users.
Select User	Specify the users to which this policy applies. To designate a user as an Administrator, select the Delegate Admin check box. Administrators can edit or delete the policy, and can also create child policies based on the original policy.
Permissions	Add or edit permissions: Create Type, Update Type, Delete Type, Select/Deselect All.
Delegate Admin	You can use Delegate Admin to assign administrator privileges to the roles, groups, or users specified in the policy. Administrators can edit or delete the policy, and can also create child policies based on the original policy.

- You can use the Plus (+) symbol to add additional conditions. Conditions are evaluated in the order listed in the policy. The condition at the top of the list is applied first, then the second, then the third, and so on.
- You can use Deny All Other Accesses to deny access to all other users, groups, and roles other than those specified in the allow conditions for the policy.
- Click Add.

Related Information

[Wildcards and variables in resource-based policies](#)

Configure a resource-based policy: HBase

How to add a new policy to an existing HBase service.

Procedure

- On the Service Manager page, select an existing HBase service.
The List of Policies page appears.

2. Click Add New Policy.

The Create Policy page appears.

Ranger Access Manager Audit Security Zone Settings admin

Service Manager > cm_hbase Policies > Create Policy

Create Policy

Policy Details :

Policy Type: **Access** Add Validity Period

Policy Name * enabled normal

Policy Label:

HBase Table * include

HBase Column-family * include

HBase Column * include

Description:

Audit Logging: **YES**

Allow Conditions : hide ^

Select Role	Select Group	Select User	Permissions	Delegate Admin	
<input type="text" value="Select Roles"/>	<input type="text" value="Select Groups"/>	<input type="text" value="Select Users"/>	Add Permissions +	<input type="checkbox"/>	x

3. Complete the Create Policy page as follows:

Table 23: Policy Details

Label	Description
Policy Name	Enter an appropriate policy name. This name cannot be duplicated across the system. This field is mandatory.
normal/override	Enables you to specify an override policy. When override is selected, the access permissions in the policy override the access permissions in existing policies. This feature can be used with Add Validity Period to create temporary access policies that override existing policies.
HBase Table	Select the appropriate database. Multiple databases can be selected for a particular policy. This field is mandatory.
HBase Column-family	For the selected table, specify the column families to which the policy applies.
HBase Column	For the selected table and column families, specify the columns to which the policy applies.
Description	(Optional) Describe the purpose of the policy.
Audit Logging	Specify whether this policy is audited. (De-select to disable auditing).
Policy Label	Specify a label for this policy. You can search reports and filter policies based on these labels.

Label	Description
Add Validity Period	Specify a start and end time for the policy.

Table 24: Allow Conditions

Label	Description
Select Role	Specify the roles to which this policy applies. To designate a role as an Administrator, select the Delegate Admin check box. Administrators can edit or delete the policy, and can also create child policies based on the original policy.
Select Group	Specify the groups to which this policy applies. To designate a group as an Administrator, select the Delegate Admin check box. Administrators can edit or delete the policy, and can also create child policies based on the original policy. The public group contains all users, so granting access to the public group grants access to all users.
Select User	Specify the users to which this policy applies. To designate a user as an Administrator, select the Delegate Admin check box. Administrators can edit or delete the policy, and can also create child policies based on the original policy.
Permissions	Add or edit permissions: Read, Write, Create, Admin, Select/Deselect All.
Delegate Admin	You can use Delegate Admin to assign administrator privileges to the roles, groups, or users specified in the policy. Administrators can edit or delete the policy, and can also create child policies based on the original policy.

- You can use the Plus (+) symbol to add additional conditions. Conditions are evaluated in the order listed in the policy. The condition at the top of the list is applied first, then the second, then the third, and so on.
- You can use Deny All Other Accesses to deny access to all other users, groups, and roles other than those specified in the allow conditions for the policy.
- Click Add.

Related Information

[Wildcards and variables in resource-based policies](#)

Configure a resource-based policy: HDFS

How to add a new policy to an existing HDFS service.

About this task

Through configuration, Apache Ranger enables both Ranger policies and HDFS permissions to be checked for a user request. When the NameNode receives a user request, the Ranger plugin checks for policies set through the Ranger Service Manager. If there are no policies, the Ranger plugin checks for permissions set in HDFS.

We recommend that permissions be created at the Ranger Service Manager, and to have restrictive permissions at the HDFS level.

Procedure

- On the Service Manager page, select an existing HDFS service.

The List of Policies page appears.

- Click Add New Policy.
The Create Policy page appears.

The screenshot shows the Ranger 'Create Policy' page. The page is titled 'Create Policy' and is part of the 'cm_hdfs Policies' section. The 'Policy Details' section includes the following fields and controls:

- Policy Type:** Access (selected)
- Policy Name:** A text input field with a lock icon and a toggle switch for 'enabled' (selected) and 'normal'.
- Policy Label:** A text input field with the placeholder 'Policy Label'.
- Resource Path:** A text input field with a toggle switch for 'recursive' (selected).
- Description:** A text area.
- Audit Logging:** A toggle switch for 'YES' (selected).
- add/edit permissions:** A dropdown menu showing options: Read (selected), Write, Execute, and Select/Deselect All.

The 'Allow Conditions' section includes the following controls:

- Select Role:** A dropdown menu with the placeholder 'Select Roles'.
- Select Group:** A dropdown menu with the placeholder 'Select Groups'.
- Select User:** A dropdown menu with the placeholder 'Select Users'.
- Add Permissions:** A button with a plus sign.
- Delegate Admin:** A checkbox.

- Complete the Create Policy page as follows:

Table 25: Policy Details

Field	Description
Policy Name	Enter a unique name for this policy. The name cannot be duplicated anywhere in the system.
normal/override	Enables you to specify an override policy. When override is selected, the access permissions in the policy override the access permissions in existing policies. This feature can be used with Add Validity Period to create temporary access policies that override existing policies.
Resource Path	Define the resource path for the policy folder/file. The default recursive setting specifies that the resource path is recursive; you can also specify a non-recursive path.
Description	(Optional) Describe the purpose of the policy.
Audit Logging	Specify whether this policy is audited. (De-select to disable auditing).
Policy Label	Specify a label for this policy. You can search reports and filter policies based on these labels.

Field	Description
Add Validity Period	Specify a start and end time for the policy.

Table 26: Allow Conditions

Label	Description
Select Role	Specify the roles to which this policy applies. To designate a role as an Administrator, select the Delegate Admin check box. Administrators can edit or delete the policy, and can also create child policies based on the original policy.
Select Group	Specify the groups to which this policy applies. To designate a group as an Administrator, select the Delegate Admin check box. Administrators can edit or delete the policy, and can also create child policies based on the original policy. The public group contains all users, so granting access to the public group grants access to all users.
Select User	Specify the users to which this policy applies. To designate a user as an Administrator, select the Delegate Admin check box. Administrators can edit or delete the policy, and can also create child policies based on the original policy.
Permissions	Add or edit permissions: Read, Write, Execute, Select/Deselect All.
Delegate Admin	You can use Delegate Admin to assign administrator privileges to the roles, groups, or users specified in the policy. Administrators can edit or delete the policy, and can also create child policies based on the original policy.

- You can use the Plus (+) symbol to add additional conditions. Conditions are evaluated in the order listed in the policy. The condition at the top of the list is applied first, then the second, then the third, and so on.
- You can use Deny All Other Accesses to deny access to all other users, groups, and roles other than those specified in the allow conditions for the policy.
- Click Add.

Related Information

[Wildcards and variables in resource-based policies](#)

Configure a resource-based policy: Hive

How to add a new policy to an existing Hive service.

Procedure

- On the Service Manager page, select an existing Hive service.
The List of Policies page appears.

2. Click Add New Policy.

The Create Policy page appears.

The screenshot shows the Ranger 'Create Policy' page. The page has a dark blue header with 'Ranger' and navigation links for 'Access Manager', 'Audit', 'Security Zone', and 'Settings'. The user 'admin' is logged in. The breadcrumb trail is 'Service Manager > cm_hive Policies > Create Policy'. The main section is 'Create Policy' with a sub-section 'Policy Details :'. The 'Policy Type' is 'Access'. There is a button 'Add Validity Period'. The 'Policy Name *' field is empty, with a 'normal' override policy selected. The 'Policy Label' is 'Policy Label'. There are three 'include' toggle switches for 'database', 'table', and 'Hive Column *'. The 'Description' field is empty. 'Audit Logging' is set to 'YES'. A dropdown menu 'add/edit permissions' is open, showing a list of permissions: select, update, Create, Drop, Alter, Index, Lock, All, Read, Write, Repl/Admin, Service Admin, Temporary UDF Admin, Refresh, and Select/Deselect All. At the bottom, there are sections for 'Allow Conditions :'. There are three dropdowns: 'Select Role', 'Select Group', and 'Select User'. There is a 'Delegate Admin' checkbox and a 'Add Permissions +' button.

3. Complete the Create Policy page as follows:

Table 27: Policy Details

Field	Description
Policy Name	Enter an appropriate policy name. This name cannot be duplicated across the system. This field is mandatory. The policy is enabled by default.
normal/override	Enables you to specify an override policy. When override is selected, the access permissions in the policy override the access permissions in existing policies. This feature can be used with Add Validity Period to create temporary access policies that override existing policies.
Database	Type in the applicable database name. The autocomplete feature displays available databases based on the entered text. Include is selected by default to allow access. Select Exclude to deny access..
table/udf	Specifies a table-based or UDF-based policy. Select table or udf, then type in the applicable table or UDF name. The autocomplete feature displays available tables based on the entered text. Include is selected by default to allow access. Select Exclude to deny access.

Field	Description
Hive Column	Type in the applicable Hive column name. The autocomplete feature displays available columns based on the entered text. Include is selected by default to allow access. Select Exclude to deny access.
URL	Specify the cloud storage path (for example s3a://dev-admin/demo/campaigns.txt) where the end-user permission is needed to read/write the Hive data from/to a cloud storage path. Permissions: READ operation on the URL permits the user to perform HiveServer2 operations which use S3 as data source for Hive tables. WRITE operation on the URL permits the user to perform HiveServer2 operations which write data to the specified S3 location. This feature is a Technical Preview: it is not ready for production deployment.
URI	Hive INSERT OVERWRITE queries require a Ranger URI policy to allow write operations, even if the user has write privilege granted through HDFS policy. Failure to specify this field will result in the following error: Error while compiling statement: FAILED: HiveAccessControlException Permission denied: user [jdoe] does not have [WRITE] privilege on [/tmp/*] (state=42000,code=40000) Example value: /tmp/*
Description	(Optional) Describe the purpose of the policy.
Hive Service Name	hiveservice is used only in conjunction with Permissions=Service Admin. Enables a user who has Service Admin permission in Ranger to run the kill query API: kill query <queryID> . Supported value: *. (Required)
Audit Logging	Specify whether this policy is audited. (De-select to disable auditing).
Policy Label	Specify a label for this policy. You can search reports and filter policies based on these labels.
Add Validity Period	Specify a start and end time for the policy.

Table 28: Allow Conditions

Label	Description
Select Role	Specify the roles to which this policy applies. To designate a role as an Administrator, select the Delegate Admin check box. Administrators can edit or delete the policy, and can also create child policies based on the original policy.
Select Group	Specify the groups to which this policy applies. To designate a group as an Administrator, select the Delegate Admin check box. Administrators can edit or delete the policy, and can also create child policies based on the original policy. The public group contains all users, so granting access to the public group grants access to all users.
Select User	Specify the users to which this policy applies. To designate a user as an Administrator, select the Delegate Admin check box. Administrators can edit or delete the policy, and can also create child policies based on the original policy.

Label	Description
Permissions	Add or edit permissions: Select, Update, Create, Drop, Alter, Index, Lock, All, ReplAdmin, Service Admin, Select/Deselect All. Service Admin is used in conjunction with Hive Service Name and the kill query API: kill query <queryID> .
Delegate Admin	You can use Delegate Admin to assign administrator privileges to the roles, groups, or users specified in the policy. Administrators can edit or delete the policy, and can also create child policies based on the original policy.

- You can use the Plus (+) symbol to add additional conditions. Conditions are evaluated in the order listed in the policy. The condition at the top of the list is applied first, then the second, then the third, and so on.
- You can use Deny All Other Accesses to deny access to all other users, groups, and roles other than those specified in the allow conditions for the policy.
- Click Add.

What to do next

Provide User Access to Hive Database Tables from the Command Line

Hive provides the means to manage user access to Hive database tables directly from the command line. The most commonly-used commands are:

- GRANT

Syntax:

```
grant <permissions> on table <table> to user <user or group>;
```

For example, to create a policy that grants user1 SELECT permission on the table default-hivesmoke22074, the command would be:

```
grant select on table default.hivesmoke22074 to user user1;
```

The syntax is the same for granting UPDATE, CREATE, DROP, ALTER, INDEX, LOCK, ALL, and ADMIN rights.

- REVOKE

Syntax:

```
revoke <permissions> on table <table> from user <user or group>;
```

For example, to revoke the SELECT rights of user1 to the table default.hivesmoke22074, the command would be:

```
revoke select on table default.hivesmoke22074 from user user1;
```

The syntax is the same for revoking UPDATE, CREATE, DROP, ALTER, INDEX, LOCK, ALL, and ADMIN rights.

Related Information

[Wildcards and variables in resource-based policies](#)

Configure a resource-based policy: Kafka

How to add a new policy to an existing Kafka service.

Procedure

1. On the Service Manager page, select an existing Kafka service.
The List of Policies page appears.
2. Click Add New Policy.
The Create Policy page appears.

The screenshot shows the 'Create Policy' page in Cloudera Ranger. The page has a dark blue header with 'Ranger' and navigation links for 'Access Manager', 'Audit', 'Security Zone', and 'Settings'. The user is logged in as 'admin'. The breadcrumb trail is 'Service Manager > cm_kafka Policies > Create Policy'. The main content area is titled 'Create Policy' and contains a 'Policy Details' section. This section includes a 'Policy Type' dropdown set to 'Access', a 'Policy Name' text field, a 'Policy Label' text field, and an 'Audit Logging' toggle set to 'YES'. There are also 'enabled' and 'normal' toggle buttons, and an 'include' toggle. A 'Policy Conditions' section is visible with a '+ Add Validity Period' button and a 'No Conditions' message. Below this is an 'Allow Conditions' section with a 'hide' link and a table with columns: 'Select Role', 'Select Group', 'Select User', 'Policy Conditions', 'Permissions', 'Delegate Admin', and a delete button. The table is currently empty.

3. Complete the Create Policy page as follows:

Table 29: Policy Details

Field	Description
Policy Name	Enter an appropriate policy name. This name cannot be duplicated across the system. This field is mandatory.
normal/override	Enables you to specify an override policy. When override is selected, the access permissions in the policy override the access permissions in existing policies. This feature can be used with Add Validity Period to create temporary access policies that override existing policies.
Policy Label	Specify a label for this policy. You can search reports and filter policies based on these labels.
Topic	Kafka resource type. A topic is a category or feed name to which messages are published.
Transactional ID	Kafka resource type, uniquely identifies producers in a persistent way.
Cluster	Kafka resource type.
Delegation Token	Kafka resource type for authentication.
Description	(Optional) Describe the purpose of the policy.

Field	Description
Audit Logging	Specify whether this policy is audited. (De-select to disable auditing).
Add Validity Period	Specify a start and end time for the policy.
Policy Conditions (applied at the policy level)	Click the + icon, then specify an IP address range.

Table 30: Allow Conditions

Label	Description
Select Role	Specify the roles to which this policy applies. To designate a role as an Administrator, select the Delegate Admin check box. Administrators can edit or delete the policy, and can also create child policies based on the original policy.
Select Group	Specify the groups to which this policy applies. To designate a group as an Administrator, select the Delegate Admin check box. Administrators can edit or delete the policy, and can also create child policies based on the original policy. The public group contains all users, so granting access to the public group grants access to all users.
Select User	Specify the users to which this policy applies. To designate a user as an Administrator, select the Delegate Admin check box. Administrators can edit or delete the policy, and can also create child policies based on the original policy.
Policy Conditions (applied at the item level)	Specify an IP address range.
Permissions	Add or edit permissions: Publish, Consume, Configure, Describe, Create, Delete, Describe Configs, Alter Configs, Select/Deselect All.
Delegate Admin	You can use Delegate Admin to assign administrator privileges to the roles, groups, or users specified in the policy. Administrators can edit or delete the policy, and can also create child policies based on the original policy.

4. You can use the Plus (+) symbol to add additional conditions. Conditions are evaluated in the order listed in the policy. The condition at the top of the list is applied first, then the second, then the third, and so on.
5. You can use Deny All Other Accesses to deny access to all other users, groups, and roles other than those specified in the allow conditions for the policy.
6. Click Add.

Related Information

[Wildcards and variables in resource-based policies](#)

Configure a resource-based policy: Knox

How to add a new policy to an existing Knox service.

Procedure

1. On the Service Manager page, select an existing Knox service.
The List of Policies page appears.

- Click Add New Policy.
The Create Policy page appears.

Ranger Access Manager Audit Security Zone Settings admin

Service Manager > cm_knox Policies > Create Policy

Create Policy

Policy Details :

Policy Type: **Access** Add Validity Period

Policy Name * enabled normal

Policy Label: Policy Conditions:

Knox Topology * include

Knox Service * include

Description:

Audit Logging: **YES**

Allow Conditions : hide

Select Role	Select Group	Select User	Policy Conditions	Permissions	Delegate Admin	
<input type="text" value="Select Roles"/>	<input type="text" value="Select Groups"/>	<input type="text" value="Select Users"/>	Add Conditions <input type="text"/>	Add Permissions <input type="text"/>	<input type="checkbox"/>	<input type="button" value="x"/>
			<input type="button" value="+"/>	<input type="button" value="+"/>		

- Complete the Create Policy page as follows:

Table 31: Policy Details

Field	Description
Policy Name	Enter an appropriate policy name. This name cannot be duplicated across the system. This field is mandatory.
normal/override	Enables you to specify an override policy. When override is selected, the access permissions in the policy override the access permissions in existing policies. This feature can be used with Add Validity Period to create temporary access policies that override existing policies.
Knox Topology	Enter an appropriate Topology Name.
Knox Service	Enter an appropriate Service Name.
Description	(Optional) Describe the purpose of the policy.
Audit Logging	Specify whether this policy is audited. (De-select to disable auditing).
Policy Label	Specify a label for this policy. You can search reports and filter policies based on these labels.
Add Validity Period	Specify a start and end time for the policy.

Field	Description
Policy Conditions (applied at the policy level)	Click the + icon, then specify an IP address range.

Table 32: Allow Conditions

Label	Description
Select Role	Specify the roles to which this policy applies. To designate a role as an Administrator, select the Delegate Admin check box. Administrators can edit or delete the policy, and can also create child policies based on the original policy.
Select Group	Specify the groups to which this policy applies. To designate a group as an Administrator, select the Delegate Admin check box. Administrators can edit or delete the policy, and can also create child policies based on the original policy. The public group contains all users, so granting access to the public group grants access to all users.
Select User	Specify the users to which this policy applies. To designate a user as an Administrator, select the Delegate Admin check box. Administrators can edit or delete the policy, and can also create child policies based on the original policy.
Policy Conditions (applied at the item level)	Specify an IP address range.
Permissions	Add or edit permissions: Allow
Delegate Admin	You can use Delegate Admin to assign administrator privileges to the roles, groups, or users specified in the policy. Administrators can edit or delete the policy, and can also create child policies based on the original policy.

Since Knox does not provide a command line methodology for assigning privileges or roles to users, the User and Group Permissions portion of the Knox Create Policy form is especially important.

4. You can use the Plus (+) symbol to add additional conditions. Conditions are evaluated in the order listed in the policy. The condition at the top of the list is applied first, then the second, then the third, and so on.
5. You can use Deny All Other Accesses to deny access to all other users, groups, and roles other than those specified in the allow conditions for the policy.
6. Click Add.

Related Information

[Wildcards and variables in resource-based policies](#)

Configure a resource-based policy: NiFi

How to add a new policy to an existing Atlas service.

Procedure

1. On the Service Manager page, select an existing NiFi service.
The List of Policies page appears.

- Click Add New Policy.
The Create Policy page appears.

The screenshot shows the 'Create Policy' page in the Ranger interface. The page is titled 'Create Policy' and is part of the 'Service Manager' > 'cm_nifi Policies' > 'Create Policy' navigation path. The user is logged in as 'admin'.

Policy Details :

- Policy Type: **Access** (with a dropdown arrow)
- Policy Name *: (with a dropdown arrow)
- Policy Label:
- NiFi Resource Identifier *:
- Description:
- Audit Logging: **YES** (with a dropdown arrow)
- Buttons: **enabled** (selected), **normal** (disabled), **Add Validity Period**

Allow Conditions :

Select Role	Select Group	Select User	Permissions	Delegate Admin	
<input type="text" value="Select Roles"/>	<input type="text" value="Select Groups"/>	<input type="text" value="Select Users"/>	Add Permissions +	<input type="checkbox"/>	x

- Complete the Create Policy page as follows:

Table 33: Policy Details

Field	Description
Policy Name	Enter an appropriate policy name. This name cannot be duplicated across the system. This field is mandatory.
normal/override	Enables you to specify an override policy. When override is selected, the access permissions in the policy override the access permissions in existing policies. This feature can be used with Add Validity Period to create temporary access policies that override existing policies.
NiFi Resource Identifier	In a NiFi cluster, all nodes must be granted the ability to view and modify component data in order for user to list or empty queues in processor component outbound connections. With Ranger this can be accomplished by using a wildcard to grant all of the NiFi nodes read and write access to the /data/* NiFi resource.
Description	(Optional) Describe the purpose of the policy.
Audit Logging	Specify whether this policy is audited. (De-select to disable auditing).
Policy Label	Specify a label for this policy. You can search reports and filter policies based on these labels.

Field	Description
Add Validity Period	Specify a start and end time for the policy.

Table 34: Allow Conditions

Label	Description
Select Role	Specify the roles to which this policy applies. To designate a role as an Administrator, select the Delegate Admin check box. Administrators can edit or delete the policy, and can also create child policies based on the original policy.
Select Group	Specify the groups to which this policy applies. To designate a group as an Administrator, select the Delegate Admin check box. Administrators can edit or delete the policy, and can also create child policies based on the original policy. The public group contains all users, so granting access to the public group grants access to all users.
Select User	Specify the users to which this policy applies. To designate a user as an Administrator, select the Delegate Admin check box. Administrators can edit or delete the policy, and can also create child policies based on the original policy.
Permissions	Add or edit permissions: Read, Write, Select/Deselect All.
Delegate Admin	You can use Delegate Admin to assign administrator privileges to the roles, groups, or users specified in the policy. Administrators can edit or delete the policy, and can also create child policies based on the original policy.

- You can use the Plus (+) symbol to add additional conditions. Conditions are evaluated in the order listed in the policy. The condition at the top of the list is applied first, then the second, then the third, and so on.
- You can use Deny All Other Accesses to deny access to all other users, groups, and roles other than those specified in the allow conditions for the policy.
- Click Add.

Configure a resource-based policy: NiFi Registry

How to add a new policy to an existing Atlas service.

Procedure

- On the Service Manager page, select an existing NiFi Registry service.
The List of Policies page appears.

- Click Add New Policy.
The Create Policy page appears.

- Complete the Create Policy page as follows:

Table 35: Policy Details

Field	Description
Policy Name	Enter an appropriate policy name. This name cannot be duplicated across the system. This field is mandatory.
normal/override	Enables you to specify an override policy. When override is selected, the access permissions in the policy override the access permissions in existing policies. This feature can be used with Add Validity Period to create temporary access policies that override existing policies.
NiFi Registry Resource Identifier	In a NiFi cluster, all nodes must be granted the ability to view and modify component data in order for user to list or empty queues in processor component outbound connections. With Ranger this can be accomplished by using a wildcard to grant all of the NiFi nodes read and write access to the /data/* NiFi resource.
Description	(Optional) Describe the purpose of the policy.
Audit Logging	Specify whether this policy is audited. (De-select to disable auditing).
Policy Label	Specify a label for this policy. You can search reports and filter policies based on these labels.

Field	Description
Add Validity Period	Specify a start and end time for the policy.

Table 36: Allow Conditions

Label	Description
Select Role	Specify the roles to which this policy applies. To designate a role as an Administrator, select the Delegate Admin check box. Administrators can edit or delete the policy, and can also create child policies based on the original policy.
Select Group	Specify the groups to which this policy applies. To designate a group as an Administrator, select the Delegate Admin check box. Administrators can edit or delete the policy, and can also create child policies based on the original policy. The public group contains all users, so granting access to the public group grants access to all users.
Select User	Specify the users to which this policy applies. To designate a user as an Administrator, select the Delegate Admin check box. Administrators can edit or delete the policy, and can also create child policies based on the original policy.
Permissions	Add or edit permissions: Read, Write, Delete, Select/Deselect All.
Delegate Admin	You can use Delegate Admin to assign administrator privileges to the roles, groups, or users specified in the policy. Administrators can edit or delete the policy, and can also create child policies based on the original policy.

- You can use the Plus (+) symbol to add additional conditions. Conditions are evaluated in the order listed in the policy. The condition at the top of the list is applied first, then the second, then the third, and so on.
- You can use Deny All Other Accesses to deny access to all other users, groups, and roles other than those specified in the allow conditions for the policy.
- Click Add.

Related Information

[SQL Standard Based Hive Authorization](#)

Configure a resource-based policy: Solr

How to add a new policy to an existing Solr service.

Procedure

- On the Service Manager page, select an existing Solr service.
The List of Policies page appears.

- Click Add New Policy.
The Create Policy page appears.

Ranger Access Manager Audit Security Zone Settings admin

Service Manager > cm_solr Policies > Create Policy

Create Policy

Policy Details :

Policy Type: **Access** Add Validity Period

Policy Name * enabled normal

Policy Label:

Solr Collection * include

Description:

Audit Logging: **YES**

Policy Conditions +

No Conditions

Allow Conditions : hide ^

Select Role	Select Group	Select User	Policy Conditions	Permissions	Delegate Admin	
<input type="text" value="Select Roles"/>	<input type="text" value="Select Groups"/>	<input type="text" value="Select Users"/>	Add Conditions +	Add Permissions +	<input type="checkbox"/>	<input checked="" type="checkbox"/>

+

- Complete the Create Policy page as follows:

Table 37: Policy Details

Field	Description
Policy Name	Enter an appropriate policy name. This name cannot be duplicated across the system. This field is mandatory.
normal/override	Enables you to specify an override policy. When override is selected, the access permissions in the policy override the access permissions in existing policies. This feature can be used with Add Validity Period to create temporary access policies that override existing policies.
Solr Collection	http:host_ip:8983/solr
Description	(Optional) Describe the purpose of the policy.
Audit Logging	Specify whether this policy is audited. (De-select to disable auditing).
Policy Label	Specify a label for this policy. You can search reports and filter policies based on these labels.
Add Validity Period	Specify a start and end time for the policy.

Field	Description
Policy Conditions (applied at the policy level)	Click the + icon, then specify an IP address range.

Table 38: Allow Conditions

Label	Description
Select Role	Specify the roles to which this policy applies. To designate a role as an Administrator, select the Delegate Admin check box. Administrators can edit or delete the policy, and can also create child policies based on the original policy.
Select Group	Specify the groups to which this policy applies. To designate a group as an Administrator, select the Delegate Admin check box. Administrators can edit or delete the policy, and can also create child policies based on the original policy. The public group contains all users, so granting access to the public group grants access to all users.
Select User	Specify the users to which this policy applies. To designate a user as an Administrator, select the Delegate Admin check box. Administrators can edit or delete the policy, and can also create child policies based on the original policy.
Policy Conditions (applied at the item level)	Specify an IP address range.
Permissions	Add or edit permissions: Query, Update, Others, Solr Admin, Select/Deselect All.
Delegate Admin	You can use Delegate Admin to assign administrator privileges to the roles, groups, or users specified in the policy. Administrators can edit or delete the policy, and can also create child policies based on the original policy.

- You can use the Plus (+) symbol to add additional conditions. Conditions are evaluated in the order listed in the policy. The condition at the top of the list is applied first, then the second, then the third, and so on.
- You can use Deny All Other Accesses to deny access to all other users, groups, and roles other than those specified in the allow conditions for the policy.
- Click Add.

Related Information

[Wildcards and variables in resource-based policies](#)

Configure a resource-based policy: YARN

How to add a new policy to an existing YARN service.

Procedure

- On the Service Manager page, select an existing YARN service.
The List of Policies page appears.

- Click Add New Policy.
The Create Policy page appears.

The screenshot shows the Ranger 'Create Policy' page. The top navigation bar includes 'Ranger', 'Access Manager', 'Audit', 'Security Zone', and 'Settings'. The breadcrumb trail is 'Service Manager > cm_yarn Policies > Create Policy'. The page title is 'Create Policy'. The 'Policy Details' section contains the following fields and controls:

- Policy Type:** Set to 'Access'. An 'Add Validity Period' button is visible.
- Policy Name:** A text input field with a lock icon. A toggle switch is set to 'enabled' (overriding the 'normal' label).
- Policy Label:** A text input field containing 'Policy Label'.
- Queue:** A text input field. A toggle switch is set to 'recursive'.
- Description:** A text area.
- Audit Logging:** A toggle switch set to 'YES'.

The 'Allow Conditions' section features a table with the following columns and controls:

Select Role	Select Group	Select User	Permissions	Delegate Admin	
Select Roles	Select Groups	Select Users	Add Permissions +	<input type="checkbox"/>	x

- Complete the Create Policy page as follows:

Table 39: Policy Details

Field	Description
Policy Name	Enter an appropriate policy name. This name cannot be duplicated across the system. This field is mandatory.
normal/override	Enables you to specify an override policy. When override is selected, the access permissions in the policy override the access permissions in existing policies. This feature can be used with Add Validity Period to create temporary access policies that override existing policies.
Queue	The YARN queue to which the policy applies.
Recursive	The default recursive setting specifies that the policy will also be applied to all sub-queues; you can also specify a non-recursive path.
Description	(Optional) Describe the purpose of the policy.
Audit Logging	Specify whether this policy is audited. (De-select to disable auditing).
Policy Label	Specify a label for this policy. You can search reports and filter policies based on these labels.

Field	Description
Add Validity Period	Specify a start and end time for the policy.

Table 40: Allow Conditions

Label	Description
Select Role	Specify the roles to which this policy applies. To designate a role as an Administrator, select the Delegate Admin check box. Administrators can edit or delete the policy, and can also create child policies based on the original policy.
Select Group	Specify the groups to which this policy applies. To designate a group as an Administrator, select the Delegate Admin check box. Administrators can edit or delete the policy, and can also create child policies based on the original policy. The public group contains all users, so granting access to the public group grants access to all users.
Select User	Specify the users to which this policy applies. To designate a user as an Administrator, select the Delegate Admin check box. Administrators can edit or delete the policy, and can also create child policies based on the original policy.
Permissions	Add or edit permissions: submit-app, admin-queue, Select/Deselect All.
Delegate Admin	You can use Delegate Admin to assign administrator privileges to the roles, groups, or users specified in the policy. Administrators can edit or delete the policy, and can also create child policies based on the original policy.

- You can use the Plus (+) symbol to add additional conditions. Conditions are evaluated in the order listed in the policy. The condition at the top of the list is applied first, then the second, then the third, and so on.
- You can use Deny All Other Accesses to deny access to all other users, groups, and roles other than those specified in the allow conditions for the policy.
- Click Add.

Related Information

[Wildcard and variables in resource-based policies](#)

Wildcard and variables in resource-based policies

Reference for wildcards and variables in resource-based policies.

Ranger Authorization Resource Policy Wildcard Characters

Wildcard characters can be included in the resource path, the database name, the table name, or the column name:

- * indicates zero or more occurrences of characters
- ? indicates a single character

Ranger Authorization Resource Policy {USER} Variable

The variable {USER} can be used to autofill the accessing user, for example:

In Select User, choose {USER}.

In Resource Path, enter data_{USER}.

Ranger Authorization Resource Policy {USER} Variable Recommended Practices and Customizability

Ranger requires that string '{USER}' is used to represent accessing user as the user in the policy-item in a Ranger policy. However, Ranger provides flexible way of customizing the string that is used as shorthand to represent the

accessing user's name in the policy resource specification. By default, Ranger policy resource specification expects characters '{' and '}' as delimiters for string 'USER', however, ranger supports customizable way of specifying delimiter characters, escaping those delimiters, and the string 'USER' itself by prefixing it with another, user-specified string on a per resource-level basis in the service definition of each component supported by Ranger.

For example, if for a certain HDFS installation, if the path names may contain '{' or '}' as valid characters, but not '%' character, then the service-definition for HDFS can be specified as:

```
"resources": [
  {
    "itemId": 1,
    "name": "path",
    "type": "path",
    "level": 10,
    "parent": "",
    "mandatory": true,
    "lookupSupported": true,
    "recursiveSupported": true,
    "excludesSupported": false,
    "matcher": "org.apache.ranger.plugin.resourcematcher.RangerPathResourceMatcher",
    "matcherOptions": {"wildcard": true, "ignoreCase": false}, "replaceTokens": true, "tokenDelimiterStart": "%", "tokenDelimiterEnd": "%", "tokenDelimiterPrefix": "rangerToken:"
    "validationRegex": "",
    "validationMessage": "",
    "uiHint": "",
    "label": "Resource Path",
    "description": "HDFS file or directory"
  }
]
```

Corresponding ranger policy for the use case for HDFS will be written as follow:

```
resource: path=/home/%rangerToken:USER%
user: {USER}
permissions: all, delegateAdmin=true
```


The following customizable matcherOptions are available for this feature:

- `replaceTokens`: true if short-hand for user in resource-spec needs to be replaced at run-time with current-user's name; false if the resource-spec needs to be interpreted as it is. Default value: true.
- `tokenDelimiterStart`: Identifies start character of short-hand for current-user in resource specification. Default value: {.
- `tokenDelimiterEnd`: Identifies end character of short-hand for current-user in resource specification. Default value: }.
- `tokenDelimiterEscape`: Identifies escape character for escaping `tokenDelimiterStart` or `tokenDelimiterEnd` values in resource specification. Default value: \.
- `tokenDelimiterPrefix`: Identifies special prefix which together with string 'USER' makes up short-hand for current-user's name in the resource specification. Default value: .


Preloaded resource-based services and policies

Apache Ranger includes preloaded resource-based services and policies.

- The preloaded resource-based services appear on the Service Manager page for resource-based policies, and are prefixed with "cm_".



- To view the policies for each preloaded service, click the service name. To view policy details, click the applicable edit icon or policy ID number.



cm_atlas

all - entity-type, entity-classification, entity

This is a default policy of type "entity" that gives access to all entities and their classifications for the following users and groups, with the specified permissions:

- admin, rangerlookup – Read, Create, Update, Delete entity & Add, Update, Remove classification
- rangertagsync – Read entity
- public group – Read entity

all - relationship-type, end-one-entity-type, end-one-entity-classification, end-one-entity, end-two-entity-type, end-two-entity-classification, end-two-entity

This is a default policy of type "relationship" that gives access to all to all Entity-Relationships between End1-Entity-Type, End1-Entity-Classification, End1-Entity-ID and End2-Entity-Type, End2-Entity-Classification, End2-Entity-ID for the following users and groups, with the specified permissions:

- admin, rangerlookup – Add, Update, and Remove relationship
- public group – Add, Update, and Remove relationship

all - atlas-service

This is a default policy of type "atlas-service" that gives access to all atlas-services [export, import, server] for the following users, with the specified permissions:

- admin, rangerlookup – Admin Export & Admin Import

all - type-category, type

This is a default policy of type "type-category" that gives access to all type categories [ENUM, ENTITY, CLASSIFICATION, RELATIONSHIP, STRUCT] and type names for the following users, with the specified permissions:

- admin, rangerlookup – Create, Update, and Delete type

Allow users to manage favorite searches

This is a default policy of type "entity-type" that gives access to __AtlasUserProfile & __AtlasUserSavedSearch resources which are internal types for favorite search. This policy provides Read, Create, Update, and Delete Entity permissions to users who create a favorite search.

cm_hbase

all - table, column-family, column

Provides access to all HBase tables, column-families, and columns to the following users, with the specified permissions:

- hbase, rangerlookup – Read, Write, Create, Admin

ATLAS_HBASE_TABLES

Provides access to all HBase column-families and columns in the atlas_janus and ATLAS_ENTITY_AUDIT_EVENTS HBase tables, to the following user, with the specified permissions:

- atlas – Read, Write, Create, Admin

cm_hdfs

all - path

Provides access to all HDFS resource paths to the following users, with the specified permissions:

- hdfs, rangerlookup – Read, Write, Execute

kms-audit-path

Provides access to the /ranger/audit/kms resource path to the following user, with the specified permissions:

- keyadmin – Read, Write, Execute

cm_hive

all - global

Provides global access to the following users, with the specified permissions:

- hive, rangerlookup, impala – Select, Update, Create, Drop, Alter, Index, Lock, All, Read, Write, ReplAdmin, Service Admin, Temporary UDF Admin, Refresh

all - database, table, column

Provides access to all databases, tables, and columns to the following users, with the specified permissions:

- hive, rangerlookup, impala – Select, Update, Create, Drop, Alter, Index, Lock, All, Read, Write, ReplAdmin, Service Admin, Temporary UDF Admin, Refresh
- {OWNER} – All

all - database, table

Provides access to all databases and tables to the following users, with the specified permissions:

- hive, rangerlookup, impala – Select, Update, Create, Drop, Alter, Index, Lock, All, Read, Write, ReplAdmin, Service Admin, Temporary UDF Admin, Refresh
- {OWNER} – All

all - database

Provides access to all databases to the following users, with the specified permissions:

- hive, rangerlookup, impala – Select, Update, Create, Drop, Alter, Index, Lock, All, Read, Write, ReplAdmin, Service Admin, Temporary UDF Admin, Refresh
- {OWNER} – All

Also provides access to all databases to the following group, with the specified permissions:

- public – Create

all - hiveservice

Provides hiveservice access to the following users, with the specified permissions:

- hive, rangerlookup, impala – Select, Update, Create, Drop, Alter, Index, Lock, All, Read, Write, ReplAdmin, Service Admin, Temporary UDF Admin, Refresh

all - database, udf

Provides database and udf access to the following users, with the specified permissions:

- hive, rangerlookup, impala – Select, Update, Create, Drop, Alter, Index, Lock, All, Read, Write, ReplAdmin, Service Admin, Temporary UDF Admin, Refresh
- {OWNER} – All

all - url

Provides url access to the following users, with the specified permissions:

- hive, rangerlookup, impala – Select, Update, Create, Drop, Alter, Index, Lock, All, Read, Write, ReplAdmin, Service Admin, Temporary UDF Admin, Refresh

default database tables columns

Provides access to all tables and columns in the default database to the following user, with the specified permissions:

- impala – Create

Also provides access to all tables and columns in the default database to the following group, with the specified permissions:

- public – Create

information_schema database tables columns

Provides access to all tables and columns in the information_schema database to the following user, with the specified permissions:

- impala – Select

Also provides access to all tables and columns in the information_schema database to the following group, with the specified permissions:

- public – Select

cm_kafka

all - topic

Provides access to all topics to the following users, with the specified permissions:

- kafka, rangerlookup, streamsmgmr, streamsrepmgr – Publish, Consume, Configure, Describe, Create, Delete, Describe Configs, Alter Configs

all - cluster

Provides access to all clusters to the following users, with the specified permissions:

- kafka, rangerlookup, streamsmgmr, streamsrepmgr – Configure, Describe, Create, Kafka Admin, Idempotent Write, Describe Configs, Alter Configs

all - transactionalid

Provides transactionalid access to the following users, with the specified permissions:

- kafka, rangerlookup, streamsmgmr, streamsrepmgr – Publish, Describe

all - delegationtoken

Provides delegationtoken access to the following users, with the specified permissions:

- kafka, rangerlookup, streamsmgmr, streamsrepmgr – Describe

ATLAS_HOOK

Provides ATLAS_HOOK topic access to the following users, with the specified permissions:

- hbase, hive, impala, mlgov – Publish
- atlas – Create, Configure, and Consume

ATLAS_ENTITIES

Provides ATLAS_ENTITIES topic access to the following users, with the specified permissions:

- atlas – Create, Configure, and Publish
- rangertagsync – Consume

ATLAS_SPARK_HOOK

Provides ATLAS_SPARK_HOOK topic access to the following user, with the specified permissions:

- atlas – Create, Configure, and Consume

Also provides ATLAS_SPARK_HOOK topic access to the following group, with the specified permissions:

- public – Publish

cm_knox

all - topology, service

Provides access to all Knox topologies and services to the following users, with the specified permissions:

- admin, rangerlookup – Allow

cm_nifi**all - nifi-resource**

Provides access to all NiFi resource identifiers to the following user, with the specified permissions:

- rangerlookup – Read, Write

cm_solr**all - collection**

Provides access to all Solr collections to the following users, with the specified permissions:

- solr, rangerlookup, ranger, atlas – Query, Update, Others, Solr Admin

RANGER_AUDITS_COLLECTION

Provides access to the RANGER_AUDITS_COLLECTION Solr collection to the following users, with the specified permissions:

- atlas, hbase, hdfs, hive, impala, kafka, Knox, nifi, ranger, storm, yarn – Query, Update, Others
- ranger – Query, Update, Others, Solr Admin

cm_yarn**all - queue**

Provides access to all YARN queues to the following users, with the specified permissions:


- yarn, rangerlookup – submit-app, admin-queue

Importing and exporting resource-based policies

You can export and import policies from the Ranger Admin UI for cluster resiliency (backups), during recovery operations, or when moving policies from test clusters to production clusters. You can export/import a specific subset of policies (such as those that pertain to specific resources or user/groups) or clone the entire repository (or multiple repositories) via Ranger Admin UI.

Interfaces

You can import and export policies from the Service Manager page:



You can also export policies from the Reports page:




Table 41: Export Policy Options

	Service Manager Page	Reports Page
Formats	JSON	JSON Excel CSV
Filtering Supported	No	Yes
Specific Service Export	Yes	Via filtering

Filtering

When exporting from the Reports page, you can apply filters before saving the file.

Export Formats

You can export policies in the following formats:

- Excel
- JSON
- CSV

Note: CSV format is not supported for importing policies.

When you export policies from the Service Manager page, the policies are automatically downloaded in JSON format. If you wish to export in Excel or CSV format, export the policies from the Reports page dropdown menu.

Required User Roles

The Ranger admin user can import and export only Resource & Tag based policies. The credentials for this user are set in Ranger Configs > Advanced ranger-env in the fields labeled admin_username (default: admin/admin).

The Ranger KMS keyadmin user can import and export only KMS policies. The default credentials for this user are keyadmin/keyadmin.

Limitations

To successfully import policies, use the following database versions:

- MariaDB: 10.1.16+
- MySQL: 5.6.x+
- Oracle: 11gR2+
- PostgreSQL: 8.4+
- MS SQL: 2008 R2+

Partial import is not supported.

Related Information

[Importing and exporting tag-based policies](#)

Import resource-based policies for a specific service

How to import resource-based policies for a specific service (HBase, YARN, etc.).

Procedure

1. On the Service Manager page, click the Import icon for the service:



The Import Policy page appears.


2. Select the file to import.

You can only import policies in JSON format.


Security Zone : Select

Import Policy ✕

Select File :

Select file  Override Policy :

Ranger_Policies_20190717_190622.json ✕

 All services gets listed on service destination when Zone destination is blank. When zone is selected at destination, then only services associated with that zone will be listed.

Specify Zone Mapping :

Source	To	Destination
<input type="text"/>	To	<input type="text" value="No zone selected"/>

Specify Service Mapping :

Source	To	Destination
<input type="text" value="cm_hdfs"/>	To	<input type="text" value="Select service name"/>

3. (Optional) Configure the import operation:

- a) The Override Policy option deletes all policies of the destination repositories.
- b) Zone Mapping – when no destination is selected, all services are imported. When a destination is selected, only the services associated with that security zone are imported.
- c) Service Mapping maps the downloaded file repository, i.e. source repository to destination repository. You can use the red x symbols to remove services from the import. Scroll down to view all service mappings.

Import Policy [Close]

Specify Zone Mapping :

Source: [Empty] To Destination: [No zone selected]

Specify Service Mapping :

Source	To	Destination	Action
cm_hdfs	To	cm_hdfs	✗
cm_hbase	To	cm_hbase	✗
cm_yarn	To	cm_yarn	✗
cm_hive	To	cm_hive	✗
cm_knox	To	cm_knox	✗
cm_storm	To	cm_storm	✗

[Cancel] [Import]

4. Click Import.

A confirmation message appears after the file is imported.

Related Information


[Import resource-based policies for all services](#)

Import resource-based policies for all services

How to import policies for all services.

Procedure


1. On the Service Manager page, click Import.



The Import Policy page appears.

Import Policy ✕

Select File :

Select file  Override Policy :

Ranger_Policies_20190717_190622.json ✕

i All services gets listed on service destination when Zone destination is blank. When zone is selected at destination, then only services associated with that zone will be listed.

Specify Zone Mapping :

Source		Destination
<input type="text"/>	To	<input type="text" value="No zone selected"/>

Specify Service Mapping :

Source		Destination
<input type="text" value="cm_hdfs"/>	To	<input type="text" value="cm_hdfs"/>

2. Select the file to import.
You can only import policies in JSON format.

3. (Optional) Configure the import operation:
 - a) The Override Policy option deletes all policies of the destination repositories.
 - b) Zone Mapping – when no destination is selected, all services are imported. When a destination is selected, only the services associated with that security zone are imported.
 - c) Service Mapping maps the downloaded file repository, i.e. source repository to destination repository. You can use the red x symbols to remove services from the import. Scroll down to view all service mappings.

Import Policy

Specify Zone Mapping :

Source: To Destination:

Specify Service Mapping :

Source	To	Destination
cm_hdfs	To	cm_hdfs
cm_hbase	To	cm_hbase
cm_yarn	To	cm_yarn
cm_hive	To	cm_hive
cm_knox	To	cm_knox
cm_storm	To	cm_storm

Buttons: Cancel, Import

4. Click Import.
A confirmation message appears after the file is imported.

Related Information

[Import resource-based policies for a specific service](#)

Export resource-based policies for a specific service


How to export the policies for a specific service (HBase, YARN, etc).

About this task

If you would like to export in Excel or CSV format, export the policies from the Reports page dropdown menu.


Procedure

1. On the Service Manager page, click the Export icon for the service:



The Export Policy page appears.

2. Click Export.



The file downloads in your browser as a JSON file.

Related Information

[Export all resource-based policies for all services](#)

Export all resource-based policies for all services

How to export the policies for all service.

About this task

If you would like to export in Excel or CSV format, export the policies from the Reports page drop-down menu.

Procedure

- From the Service Manager page:
 - a) Click Export.
The Export Policy page appears.
 - b) Remove components or specific services, then click Export.

Export Policy [Close]

Service Type :

x hdfs x hbase x hive x yarn x Knox x storm x solr x kafka
x nifi x nifi-registry x atlas

Select Service Name *

x cm_hdfs x cm_hbase x cm_hive x cm_yarn x cm_knox x cm_storm
x cm_solr x cm_kafka x cm_nifi x cm_nifi_registry x cm_atlas

Cancel Export

The file downloads in your browser as a JSON file.

- From the Reports page:
 - Apply filters before exporting the file.
 - Open the Export drop-down menu:

The screenshot shows the Ranger Reports page. At the top, there are navigation tabs: Ranger, Access Manager, Audit, Security Zone, and Settings. The user is logged in as 'admin'. The main section is titled 'User Access Report' and 'Reports'. Below this is a 'Search Criteria' section with several input fields: Policy Name (text), Policy Type (dropdown set to 'Access'), Component (text), Resource (text), Policy Label (dropdown), Zone Name (dropdown), and Search By (dropdown set to 'Group'). A 'Search' button is at the bottom of this section. Below the search criteria is a table of reports for 'HDFS'. The table has columns: Policy ID, Policy Name, Policy Labels, Resources, Policy Type, Status, Zone Name, Allow Conditions, Allow Exclude, Deny Conditions, and De. Two rows are visible: Policy 1 (all - path) and Policy 2 (kms-audit-path). Below the HDFS table is a section for 'HBASE' with a similar table. One row is visible: Policy 3 (all - table, column-family, col...). An 'Export' dropdown menu is open on the right side of the HDFS table, showing options: Excel file, CSV file, and JSON file.

- Select the file format.
The file downloads in your browser.

Related Information

[Export resource-based policies for a specific service](#)

Row-level filtering and column masking in Hive

You can use Apache Ranger row-level filters to set access policies for rows in Hive tables. You can also use Ranger column masking to set policies that mask data in Hive columns, for example to show only the first or last four characters of column data.



Note: To prevent possible data loss, row filtering and masking policies must exclude users that run compaction. For more information about excluding compaction users from Ranger policies, see [Compaction prerequisites in Managing Apache Hive](#).

Related Information

[Compaction prerequisites](#)

Row-level filtering in Hive with Ranger policies

Row-level filtering helps simplify Hive queries. By moving the access restriction logic down into the Hive layer, Hive applies the access restrictions every time data access is attempted. This helps simplify authoring of the Hive query, and provides seamless behind-the-scenes enforcement of row-level segmentation without having to add this logic to the predicate of the query.

About this task

Row-level filtering also improves the reliability and robustness of Hadoop. By providing row-level security to Hive tables and reducing the security surface area, Hive data access can be restricted to specific rows based on user characteristics (such as group membership) and the runtime context in which this request is issued.

Typical use cases where row-level filtering can be beneficial include:

- A hospital can create a security policy that allows doctors to view data rows only for their own patients, and that allows insurance claims administrators to view only specific rows for their specific site.
- A bank can create a policy to restrict access to rows of financial data based on the employee's business division, locale, or based on the employee's role (for example: only employees in the finance department are allowed to see customer invoices, payments, and accrual data; only European HR employees can see European employee data).
- A multi-tenant application can create logical separation of each tenant's data so that each tenant can see only their own data rows.

You can use Apache Ranger row-level filters to set access policies for rows in Hive tables. Row-level filter policies are similar to other Ranger access policies. You can set filters for specific users, groups, and conditions.

The following conditions apply when using row-level filters:

- The filter expression must be a valid WHERE clause for the table or view.
- Each table or view should have its own row-level filter policy.
- Wildcard matching is not supported on database or table names.
- Filters are evaluated in the order listed in the policy.
- An audit log entry is generated each time a row-level filter is applied to a table or view.

Procedure

1. On the Service Manager page, select an existing Hive Service.

2. Select the Row Level Filter tab, then click Add New Policy.

Ranger

Access Management

Service Manager

cm_hive Policies

Access

Masking

List of Policies : cm_hive

Search for your policy...

Policy ID	Policy Name
-----------	-------------

- On the Create Policy page, add the following information for the row-level filter:

Table 42: Policy Details

Field	Description
Policy Name (required)	Enter an appropriate policy name. This name cannot be duplicated across the system. The policy is enabled by default.
normal/override	Enables you to specify an override policy. When override is selected, the access permissions in the policy override the access permissions in existing policies. This feature can be used with Add Validity Period to create temporary access policies that override existing policies.
Hive Database (required)	Type in the applicable database name. The auto-complete feature displays available databases based on the entered text.
Hive Table (required)	Type in the applicable table name. The auto-complete feature displays available tables based on the entered text.
Audit Logging	Audit Logging is set to Yes by default. Select No to turn off audit logging.
Description	Enter an optional description for the policy.
Add Validity Period	Specify a start and end time for the policy.

Table 43: Row Filter Conditions

Label	Description
Select Role	Specify the roles to which this policy applies.
Select Group	Specify the groups to which this policy applies. The public group contains all users, so granting access to the public group grants access to all users.
Select User	Specify one or more users to which this policy applies.
Access Types	Currently select is the only available access type. This will be used in conjunction with the WHERE clause specified in the Row Level Filter field.

Label	Description
Add Row Filter	<ul style="list-style-type: none">• To create a row filter for the specified users, groups, and roles, Click Add Row Filter, then type a valid WHERE clause in the Enter filter expression box.• To allow Select access for the specified users and groups without row-level restrictions, do not add a row filter (leave the setting as "Add Row Filter").• Filters are evaluated in the order listed in the policy. The filter at the top of the Row Filter Conditions list is applied first, then the second, then the third, and so on.

Service Manager

cm_hive Policies

Create Policy

Create Policy

i Please ensure that users/groups listed in this policy have access to the

Policy Details :

Policy Type

Row Level Filter

Policy Name *



Policy Label

Policy Label

Hive Database *

Hive Table *

Description

Audit Logging

Row Filter Conditions :

4. To move a condition in the Row Filter Conditions list (and therefore change the order in which it is evaluated), click the dotted rows icon at the left of the condition row, then drag the condition to a new position in the list.

Ranger

Access Management

Service Manager

cm_hive Policy

Create Policy



Please ensure that users/gr

Policy Details :

Policy Type

Ro

Policy Name *

Policy Label

Pol

5. Click Add to add the new row-level filter policy.

Dynamic resource-based column masking in Hive with Ranger policies

You can use Apache Ranger dynamic resource-based column masking capabilities to protect sensitive data in Hive in near real-time. You can set policies that mask or anonymize sensitive data columns (such as PII, PCI, and PHI) dynamically from Hive query output. For example, you can mask sensitive data within a column to show only the first or last four characters.

About this task

Dynamic column masking policies are similar to other Ranger access policies for Hive. You can set filters for specific users, groups, and conditions. With dynamic column-level masking, sensitive information never leaves Hive, and no changes are required at the consuming application or the Hive layer. There is also no need to produce additional protected duplicate versions of datasets.

The following conditions apply when using Ranger column masking policies to mask data returned in Hive query results:

- A variety of masking types are available, such as show last 4 characters, show first 4 characters, Hash, Nullify, and date masks (show only year).
- You can specify a masking type for specific users, groups, and conditions.
- Wildcard matching is not supported.
- Each column should have its own masking policy.
- Masks are evaluated in the order listed in the policy.
- An audit log entry is generated each time a masking policy is applied to a column.

Procedure

1. On the Service Manager page, select an existing Hive Service.

2. Select the Masking tab, then click Add New Policy.

Ranger

Access Management

Service Manager

cm_hive Policies

Access

Masking

List of Policies : cm_hive

Search for your policy...

Policy ID	Policy Name
-----------	-------------

- On the Create Policy page, add the following information for the column-masking filter:

Table 44: Policy Details

Field	Description
Policy Name (required)	Enter an appropriate policy name. This name cannot be duplicated across the system. The policy is enabled by default.
normal/override	Enables you to specify an override policy. When override is selected, the access permissions in the policy override the access permissions in existing policies. This feature can be used with Add Validity Period to create temporary access policies that override existing policies.
Hive Database (required)	Type in the applicable database name. The auto-complete feature displays available databases based on the entered text.
Hive Table (required)	Type in the applicable table name. The auto-complete feature displays available tables based on the entered text.
Hive Column (required)	Type in the applicable column name. The auto-complete feature displays available columns based on the entered text.
Audit Logging	Audit Logging is set to Yes by default. Select No to turn off audit logging.
Description	Enter an optional description for the policy.
Add Validity Period	Specify a start and end time for the policy.

Table 45: Mask Conditions

Label	Description
Select Role	Specify the roles to which this policy applies.
Select Group	Specify the groups to which this policy applies. The public group contains all users, so granting access to the public group grants access to all users.
Select User	Specify one or more users to which this policy applies.
Access Types	Currently select is the only available access type.

Label	Description
Select Masking Type	<p>To create a row filter for the specified users, groups, and roles, click Select Masking Option, then select a masking type:</p> <ul style="list-style-type: none">• Redact – mask all alphabetic characters with "x" and all numeric characters with "n".• Partial mask: show last 4 – Show only the last four characters.• Partial mask: show first 4 – Show only the first four characters.• Hash – Replace all characters with a hash of entire cell value.• Nullify – Replace all characters with a NULL value.• Unmasked (retain original value) – No masking is applied.• Date: show only year – Show only the year portion of a date string and default the month and day to 01/01• Custom – Specify a custom masked value or expression. Custom masking can use any valid Hive UDF (Hive that returns the same data type as the data type in the column being masked). <p>Masking conditions are evaluated in the order listed in the policy. The condition at the top of the Masking Conditions list is applied first, then the second, then the third, and so on.</p>

Service Manager

cm_hive Policies

Create Policy

Create Policy

i Please ensure that users/groups listed in this policy have access to the

Policy Details :

Policy Type **Masking**

Policy Name * **i**

Policy Label

Hive Database *

Hive Table *

Hive Column *

Description

Audit Logging **YES**

4. To move a condition in the Mask Conditions list (and therefore change the order in which it is evaluated), click the dotted rows icon at the left of the condition row, then drag the condition to a new position in the list.

Ranger

Access Management

Service Manager

cm_hive Policy

Policy Details :

Policy Type

Ma

Policy Name *

Policy Label

Polic

Hive Database *

Hive Table *

5. Click Add to add the new column masking filter policy.

Dynamic tag-based column masking in Hive with Ranger policies

Where Ranger resource-based masking policy for Hive anonymizes data from a Hive column identified by the database, table, and column, tag-based masking policy anonymizes Hive column data based on tags and tag attribute values associated with Hive column (usually specified as metadata classification in Atlas).

About this task

The following conditions apply when using Ranger column masking policies to mask data returned in Hive query results:

- A variety of masking types are available, such as show last 4 characters, show first 4 characters, Hash, Nullify, and date masks (show only year).
- You can specify a masking type for specific users, groups, and conditions.
- Wildcard matching is not supported.
- If there are multiple tag masking policies applied to the same Hive column, the masking policy with the lexicographically smallest policy-name is chosen for enforcement, E.G., policy "a" is enforced before policy "aa".
- Masks are evaluated in the order listed in the policy.
- An audit log entry is generated each time a masking policy is applied to a column.

Procedure

1. Select Access Manager > Tag Based Policies, then select a tag-based service.

2. Select the Masking tab, then click Add New Policy.

Ranger

Access Management

Service Manager

cm_tag Policies

Access

Masking

List of Policies : cm_tag

Search for your policy...

Policy ID

Policy Name

3. On the Create Policy page, add the following information for the column-masking filter:

Table 46: Policy Details

Field	Description
Policy Type (required)	Set to Masking by default.
Policy Name (required)	Enter an appropriate policy name. This name cannot be duplicated across the system. The policy is enabled by default.
normal/override	Enables you to specify an override policy. When override is selected, the access permissions in the policy override the access permissions in existing policies. This feature can be used with Add Validity Period to create temporary access policies that override existing policies.
TAG (required)	Enter the applicable tag name, E.G., MASK.
Audit Logging	Audit Logging is set to Yes by default. Select No to turn off audit logging.
Description	Enter an optional description for the policy.
Add Validity Period	Specify a start and end time for the policy.
Policy Conditions (applied at the policy level)	<p>Click the + icon to add policy conditions. Currently "Accessed after expiry_date? (yes/no)" is the only available policy condition.</p> <p>"Accessed after expiry_date (yes/no)": To set this condition, type yes in the text box, then click the check mark button to add the condition.</p> <p>Enter boolean expression: Available for allow or deny conditions on tag-based policies. For examples and details, see "Using Tag Attributes and Values in Ranger Tag-Based Policy Conditions".</p> <p>Click Save to save the policy condition.</p>

Table 47: Mask Conditions

Label	Description
Select Role	Specify the roles to which this policy applies.
Select Group	Specify the groups to which this policy applies. The public group contains all users, so granting access to the public group grants access to all users.
Select User	Specify one or more users to which this policy applies.
Policy Conditions (applied at the item level)	<p>Click Add Conditions to add policy conditions. Currently "Accessed after expiry_date? (yes/no)" is the only available policy condition.</p> <p>"Accessed after expiry_date (yes/no)": To set this condition, type yes in the text box, then click the check mark button to add the condition.</p> <p>Enter boolean expression: Available for allow or deny conditions on tag-based policies. For examples and details, see "Using Tag Attributes and Values in Ranger Tag-Based Policy Conditions".</p>
Access Types	Currently select is the only available access type for the hive component.

Label	Description
Select Masking Option	<p>To create a row filter for the specified users, groups, and roles, click Select Masking Option, then select a masking type:</p> <ul style="list-style-type: none">• Redact – mask all alphabetic characters with "x" and all numeric characters with "n".• Partial mask: show last 4 – Show only the last four characters.• Partial mask: show first 4 – Show only the first four characters.• Hash – Replace all characters with a hash of entire cell value.• Nullify – Replace all characters with a NULL value.• Unmasked (retain original value) – No masking is applied.• Date: show only year – Show only the year portion of a date string and default the month and day to 01/01• Custom – Specify a custom masked value or expression. Custom masking can use any valid Hive UDF (Hive that returns the same data type as the data type in the column being masked). <p>Masking conditions are evaluated in the order listed in the policy. The condition at the top of the Masking Conditions list is applied first, then the second, then the third, and so on.</p>

Service Manager

tag_service1 Policies

Create Policy

Create Policy

i Please ensure that users/groups listed in this policy have access to the

Policy Details :

Policy Type **Masking**

Policy Name * **i**

Policy Label

TAG *

Description

Audit Logging **YES**

Mask Conditions :

4. You can use the Plus (+) symbols to add additional conditions. Conditions are evaluated in the order listed in the policy. The condition at the top of the list is applied first, then the second, then the third, and so on.
5. Click Add to add the new policy.

Related Information

[Using tag attributes and values in Ranger tag-based policy conditions](#)

Tag-based Services and Policies

Ranger enables you to create tag-based services and add access policies to those services.


Adding a tag-based service

How to add a tag-based service to Ranger.

About this task

You can use the Service Manager for Tag-Based Policies page to create tag-based services and add tag-based access policies that can be applied to Hadoop resources. Using tag-based policies enables you to control access to resources across multiple Hadoop components without creating separate services and policies in each component. You can also use Ranger TagSync to synchronize the Ranger tag store with an external metadata service such as Apache Atlas.

Procedure


1. Select Access Manager > Tag Based Policies, then click the Add icon () in the TAG box on the Service Manager page.

Ranger

Access Management

Service Manager

Service Manager

 **TAG**

cm_tag

cm_nifi_tag

2. On the Create Service page, type in a service name and an optional description. The service is enabled by default, but you can disable it by selecting Disabled. To add the service, click Add.

Service Manager

Create Service

Create Service

Service Details :

Service Name *

tag_service1

Description

Active Status

Enabled Disabled

Config Properties :

Add New Configurations

	N



Test Connection

Add

Cancel


3. The new tag service appears on the Service Manager page.

Ranger

Access Management

Service Manager

Service Manager

 **TAG**

- cm_tag
- cm_nifi_tag
- tag_service1

Adding tag-based policies

Tag-based policies enable you to control access to resources across multiple Hadoop components without creating separate services and policies in each component. You can also use Ranger TagSync to synchronize the Ranger tag store with an external metadata service such as Apache Atlas.

Procedure

1. Select Access Manager > Tag Based Policies, then select a tag-based service.

2. The List of Policies page appears with the Access tab selected by default. Click Add New Policy.

Ranger

Access Management

Service Manager

tag_service1

Access


Masking

List of Policies : tag_service1

Search for your policy...

Policy ID	Policy Name
38	EXPIRES_ON

The Create Policy page appears:



3. Enter information on the Create Policy page as follows:

Table 48: Policy Details

Field	Description
Policy Type	Set to Access by default.
Policy Name	Enter a unique policy name. This name cannot be duplicated across the system. This field is mandatory.
normal/override	Enables you to specify an override policy. When override is selected, the access permissions in the policy override the access permissions in existing policies. This feature can be used with Add Validity Period to create temporary access policies that override existing policies.
TAG	Enter the applicable tag name.
Description	(Optional) Describe the purpose of the policy.
Audit Logging	Specify whether this policy is audited. (De-select to disable auditing).
Policy Label	Specify a label for this policy. You can search reports and filter policies based on these labels.
Add Validity Period	Specify a start and end time for the policy.
Policy Conditions (applied at the policy level)	<p>Click the + icon to add policy conditions. Currently "Accessed after expiry_date? (yes/no)" is the only available policy condition.</p> <p>"Accessed after expiry_date (yes/no)": To set this condition, type yes in the text box, then click the check mark button to add the condition.</p> <p>Enter boolean expression: Available for allow or deny conditions on tag-based policies. For examples and details, see "Using Tag Attributes and Values in Ranger Tag-Based Policy Conditions".</p> <p>Click Save to save the policy condition.</p>

Table 49: Allow, Exclude from Allow, Deny, and Exclude from Deny Conditions

Label	Description
Select Role	Specify the roles to which this policy applies.
Select Group	<p>Specify the group to which this policy applies. To designate the group as an Administrator for the chosen resource, specify Admin permissions. (Administrators can create child policies based on existing policies).</p> <p>The public group contains all users, so setting a condition for the public group applies to all users.</p>
Select User	Specify a particular user to which this policy applies (outside of an already-specified group) OR designate a particular user as Admin for this policy. (Administrators can create child policies based on existing policies).
Policy Conditions (applied at the item level)	<p>Click Add Conditions to add policy conditions. Currently "Accessed after expiry_date? (yes/no)" is the only available policy condition.</p> <p>"Accessed after expiry_date (yes/no)": To set this condition, type yes in the text box, then click the check mark button to add the condition.</p> <p>Enter boolean expression: Available for allow or deny conditions on tag-based policies. For examples and details, see "Using Tag Attributes and Values in Ranger Tag-Based Policy Conditions".</p>

Label	Description
Component Permissions	Click Add Permissions to add or edit component conditions. To add component permissions, enter the component name in the text box, then use the check boxes to specify component permissions. Click the check mark button to add the chosen component conditions to the policy.

4. You can use the Plus (+) symbols to add additional conditions. Conditions are evaluated in the order listed in the policy. The condition at the top of the list is applied first, then the second, then the third, and so on.
5. You can use Deny All Other Accesses to deny access to all other users, groups, and roles other than those specified in the allow conditions for the policy.
6. Click Add to add the new policy.

Related Information

[Using tag attributes and values in Ranger tag-based policy conditions](#)

Using tag attributes and values in Ranger tag-based policy conditions

Enter boolean expression allows Ranger to use tag attributes and values when configuring tag-based policy Allow or Deny conditions. It allows admins to provide boolean expression(s) using tag attributes.

The policy condition is introduced in the tag service definition:

```
{
  "itemId":2,
  "name":"expression",
  "evaluator": "org.apache.ranger.plugin.conditionevaluator.RangerScriptConditionEvaluator",
  "evaluatorOptions" : {"engineName":"JavaScript", "ui.isMultiline":"true"},
  "label":"Enter boolean expression",
  "description": "Boolean expression"
}
```

The following variables can be referenced in the boolean expression:

- ctx: Context handler containing APIs to access metadata information from the request.
- tag: Information about the current tag.
- tagAttr: Map containing all the current tag attributes and corresponding values.

The following APIs available from the request:

- getUser(): Returns a string.
- getUserGroups(): Returns a set of strings containing groups.
- getClientIPAddress(): Returns a string containing client IP address.
- getAction(): Returns a string containing information about the action being requested.

For two scenarios:

- User “sam” needs to be denied a policy based on the IP address of the machine from where the resources are accessed.

Set the deny condition for user sam with the following boolean expression:

```
if ( tagAttr.get('ipAddr').equals(ctx.getClientIPAddress()) ) {
  ctx.result = true;
}
```

- Deny one particular user, “bob” from a group, “users”, only when this user is accessing resources from a particular IP defined as an tag attribute in Atlas.

Set the deny condition for group users with the following boolean expression:

```
if (tagAttr.get('ipAddr').equals(ctx.getClientIPAddress()) && ctx.getUser().equals("bob")) {
  ctx.result=true;
}
```

The screenshot shows the "Deny Conditions" configuration interface. It features a table with columns for "Select Group", "Select User", "Policy Conditions", and "Component Permissions". Two rows are visible, each with a "deny" button. Red callouts highlight the JavaScript expressions for the "Policy Conditions" column:

- Top callout: `(tagAttr.get('ipAddr').equals(ctx.getClientIPAddress())) { ctx.result = true;}`
- Bottom callout: `(tagAttr.get('ipAddr').equals(ctx.getClientIPAddress()) && ctx.getUser().equals("bob")) { ctx.result=true;}`

Adding a tag-based PII policy

Example of how to add a PII tag-based policy. In this example we create a tag-based policy for objects tagged "PII" in Atlas. Access to objects tagged "PII" is allowed for members of the "audit" group. All other users (the "public" group) are denied access.

Procedure

1. Select Access Manager > Tag Based Policies, then select a tag-based service.

2. On the List of Policies page, click Add New Policy.

Ranger

Access Management

Service Manager

tag_service1

Access


Masking

List of Policies : tag_service1

Search for your policy...

Policy ID	Policy Name
38	EXPIRES_ON

The Create Policy page appears:



3. Enter the following information on the Create Policy page:

Table 50: Policy Details

Field	Description
Policy Type	Set to Access by default.
Policy Name	PII
TAG	PII
Audit Logging	YES
Description	Restrict access to resources with the PII tag.

Table 51: Allow Conditions

Label	Description
Select Group	audit
Select User	<none>
Policy Conditions	<none>
Component Permissions	hive (select all permissions)

Table 52: Deny Conditions

Label	Description
Select Group	public
Select User	<none>
Policy Conditions	<none>
Component Permissions	hive (select all permissions)

Table 53: Exclude from Deny Conditions

Label	Description
Select Group	audit
Select User	<none>
Policy Conditions	<none>

Label	Description
Component Permissions	hive (select all permissions)

Ranger

Access Manager

Service Manager

cm_tag Policies

Create Policy

Policy Details :

Policy Type

Access

Policy Name *

PII

Policy Label

Policy La

TAG *

× PII

In this example we used Allow Conditions to grant access to the "audit" group, and then used Deny Conditions to deny access to the "public" group. Because the "public" group includes all users, we then used Exclude from Deny Conditions to exclude the "audit" group, in effect reinstating the "audit" group's original Allow access condition.

4. Click Add to add the new policy.

Default EXPIRES ON tag policy

An EXPIRES_ON tag-based policy is created automatically when a tag service instance created. This default policy denies access to objects tagged with EXPIRES_ON after the expiry date specified in the Atlas tag attribute. You can use the following steps to review the default EXPIRES_ON policy.

Procedure

1. Select Access Manager > Tag Based Policies, then select a tag-based service.

2. On the List of Policies page, click the Edit icon for the default EXIRES_ON policy.

Ranger

Access Management

Service Manager

tag_service1

Access

Masking

List of Policies : tag_service1

Search for your policy...

Policy ID	Policy Name
38	EXPIRES_ON

The Edit Policy page appears:

Service Manager

tag_service1 Policies

Edit Policy

Edit Policy

Policy Details :

Policy Type **Access**

Policy ID **38**

Policy Name *

enabled

Policy Label

TAG *

Description

Audit Logging **YES**

Allow Conditions :

Select Role	Select Group
<input type="text" value="Select Roles"/>	<input type="text" value="Select Groups"/>




3. We can see that the default EXPIRES_ON policy denies access to all users, and for all components, after the expiry date specified in the Atlas tag attribute.

Importing and exporting tag-based policies

You can export and import policies from the Ranger Admin UI for cluster resiliency (backups), during recovery operations, or when moving policies from test clusters to production clusters. You can import or export a specific subset of policies (such as those that pertain to specific resources or user/groups) or clone the entire repository (or multiple repositories) via the Ranger Admin UI.

Interfaces

You can import and export policies from the Tag Based Policies page:



You can also export policies from the Reports page:




Table 54: Export Policy Options

	Service Manager Page	Reports Page
Formats	JSON	JSON Excel CSV
Filtering Supported	No	Yes
Specific Service Export	Yes	Via filtering

Filtering

When exporting from the Reports page, you can apply filters before saving the file.

Export Formats

You can export policies in the following formats:

- Excel
- JSON
- CSV

Note: CSV format is not supported for importing policies.

When you export policies from the Service Manager page, the policies are automatically downloaded in JSON format. If you wish to export in Excel or CSV format, export the policies from the Reports page dropdown menu.

Required User Roles

The Ranger admin user can import and export only Resource & Tag based policies. The credentials for this user are set in Ranger Configs > Advanced ranger-env in the fields labeled admin_username (default: admin/admin).

The Ranger KMS keyadmin user can import and export only KMS policies. The default credentials for this user are keyadmin/keyadmin.

Limitations

To successfully import policies, use the following database versions:

- MariaDB: 10.1.16+
- MySQL: 5.6.x+
- Oracle: 11gR2+
- PostgreSQL: 8.4+
- MS SQL: 2008 R2+

Partial policy import is not supported.

Related Information

[Importing and exporting resource-based policies](#)

Import tag-based policies

How to import tag-based policies.

Procedure




1. On the Tag Based Policies page, click one of the Import icons:

Ranger

Access Management

Service Management

Service Management

-  Resource Based
-  Tag Based Policies
-  Reports

TAG

cm_tag

cm_nifi_tag

The Import Policy page appears.

Import Policy

Select File :

Select file 

Ranger_Policies_20190717_190622.json

i All services gets listed on service c
When zone is selected at destination,
will be listed.

Specify Zone Mapping :

Source

2. Select the file to import.

You can only import policies in JSON format.

3. (Optional) Configure the import operation:

- a) The Override Policy option deletes all policies of the destination repositories.
- b) Zone Mapping – when no destination is selected, all services are imported. When a destination is selected, only the services associated with that security zone are imported.
- c) Service Mapping maps the downloaded file repository, i.e. source repository to destination repository. You can use the red x symbols to remove services from the import. Scroll down to view all service mappings.

Import Policy [Close]

Specify Zone Mapping :

Source	To	Destination
	To	No zone selected

Specify Service Mapping :

Source	To	Destination
cm_hdfs	To	cm_hdfs
cm_hbase	To	cm_hbase
cm_yarn	To	cm_yarn
cm_hive	To	cm_hive
cm_knox	To	cm_knox
cm_storm	To	cm_storm

Buttons: Cancel, Import

4. Click Import.

A confirmation message appears after the file is imported.

Related Information

[Export tag-based policies](#)

Export tag-based policies

How to export all tag-based policies.

About this task

You can only export policies in JSON format from the Tag-based policies page. If you would like to export in Excel or CSV format, export the policies from the Reports page drop-down menu.

Procedure

- From the Access Manager >Tag Based Policies page:
 - a) Click the Export button or icon:

Ranger

Access Mana

Service Manager

Service Manager



TAG

cm_tag


cm_nifi_tag

tag_service1

tag_tag

The Export Policy page appears.

- b) Remove components or specific services, then click Export.



- c) The file downloads in your browser as a JSON file.
- From the Reports page:
 - a) Filter Component to tag and click Search.
 - b) (Optional) Apply filters before exporting the file.
 - c) Open the Export drop-down menu:

The screenshot shows the Ranger User Access Report interface. The 'Reports' section has search criteria for Policy Name, Policy Type (Access), Component (tag), Resource, Policy Label, Zone Name, and Search By (Group). Below is a table titled 'TAG' with columns for Policy ID, Policy Name, Policy Labels, Resources, Policy Type, Status, Zone Name, Allow Conditions, Allow Exclude, Deny Conditions, and De. An 'Export' dropdown menu is open, showing options for Excel file, CSV file, and JSON file.

Policy ID	Policy Name	Policy Labels	Resources	Policy Type	Status	Zone Name	Allow Conditions	Allow Exclude	Deny Conditions	De
27	EXPIRES_ON	--	tag:EXPIRES_ON	Access	Enabled	--	+	+	+	+
39	EXPIRES_ON	--	tag:EXPIRES_ON	Access	Enabled	--	+	+	+	+
5	EXPIRES_ON	--	tag:EXPIRES_ON	Access	Enabled	--	+	+	+	+
38	EXPIRES_ON	--	tag:EXPIRES_ON	Access	Enabled	--	+	+	+	+

- d) Select the file format.
The file downloads in your browser.

Create a time-bound policy

Ranger policy validity periods enable you to configure a policy to be effective for a specified time range. You can add a validity period to both resource-based and tag-based policies.

About this task

Time-bound policy use-case examples:

- To restrict access to sensitive financial information until the earnings release date.
- To block a certain user for a specific time period (e.g., a compromised user account being investigated needs to be put on "hold" from accessing resources in Hadoop services).
- To block a certain group for a specific time (e.g., excluding temporary employees from writing on resources during the holiday season).



Note: The following procedure shows how to create a time-bound resource-based policy. The procedure is essentially the same for a tag-based resource policy.

Procedure

1. On the Ranger Service Manger page, select a service, then click Add New Policy.
2. Complete the fields on the **Create Policy** page.
3. Click Add Validity Period.
4. On the **Policy Validity Period** pop-up, specify a start time, end time, and time zone. To add additional validity periods, click the + symbol. Click Save to save the specified validity periods.

The screenshot shows a "Policy Validity Period" dialog box overlaid on a "Create Policy" page. The dialog has a title bar with a close button (X). It contains three columns: "Start Time", "End Time", and "Time zone".

Start Time	End Time	Time zone
2019/07/22 09:00:15	2019/08/31 09:09:15	America/Los_Angel...
+		

At the bottom right of the dialog are "Cancel" and "Save" buttons. The background page shows breadcrumb navigation: "om_hbase Policies" > "Create Policy".

- If you would like the policy to override all other policies during its validity period, select override.

Ranger Access Manager Audit Security Zone Settings admin

Service Manager > cm_hbase Policies > Create Policy

Create Policy

Policy Details :

Policy Type: Access Add Validity Period

Policy Name * Temp Employees Override enabled **override**

Policy Label: Policy Label

HBase Table * sales include

HBase Column-family * include

HBase Column * include

Description:

Audit Logging: YES

Allow Conditions : hide

Select Role	Select Group	Select User	Permissions	Delegate Admin	
Select Roles	temp_employees	Select Users	Read	<input type="checkbox"/>	<input checked="" type="checkbox"/>

+ show

Exclude from Allow Conditions: show

Deny Conditions : show

Add Cancel

- Click Add.

Ranger Security Zones

Ranger security zones let you organize service resources into multiple security zones.

Overview

Ranger Security Zones overview.

What is a Security Zone?

Lets you organize resource and tag-based services and policies into separate security zones. You can assign one or more administrators for each security zone. Security zone administrators can then create and update policies for their security zone.

For example, let us consider two security zones: "finance" and "sales":

- Security zone "finance" includes all content in a "finance" Hive database.
- Security zone "sales" includes all content in a "sales" Hive database.
- Sets of users and groups are designated as administrators in each security zone.
- Users are allowed to set up policies only in security zones in which they are administrators.
- Policies defined in a security zone are applicable only for resources of that zone.
- A zone can be extended to include resources from multiple services such as HDFS, Hive, HBase, Kafka, etc., allowing administrators of a zone to set up policies for resources owned by their organization across multiple services.

```
Zone: finance
service: prod_hdfs; path=/finance/*, /taxes/*
service: prod_hive; database=finance
service: prod_kafka; topic=FIN_*
service: test_hadoop; path=/finance/*, /taxes/*
Zone: sales
service: prod_hdfs; path=/sales/*
service: prod_hive; database=sales
service: prod_kafka; topic=SALES_*
```

- As shown above, resources can be specified using wildcards (FIN_*, SALES_*).
- A resource is not mappable to more than one security zone. Ranger does not allow creation of security zones that specify resources that match resources in another zone. For example, an attempt to update the "finance" zone above with the HDFS path /sales/finance/* is not permitted, as this conflicts with the HDFS path /sales/* specified in the "sales" zone.
- A set of users and groups can be designated as administrators of a security zone. Administrators can create, update, and delete security policies for the resources in the security zone.
- A set of users and groups can be authorized to view audit logs of access to a security zone's resources. Other users are not allowed to view access-audit logs of the security zone resources.

Security Zone Administration

- Security zones can only be created, updated, or deleted by a user with the ROLE_SYS_ADMIN role in Ranger.
- Users can view, retrieve, and update policies only in security zones in which they have administrator privileges.

How are Security Zones Used in Authorization?

When a Ranger authorization plugin authorizes a resource access request, it first determines the zone in which the accessed resource resides. If the resource matches a security zone, only the policies of that security zone are used to authorize the access. If resource does not match any security zone, the policies in the default (unnamed) security zone are used to authorize the access.

Tag-based Policies in Security Zones

In a given service, each security zone can be configured to use tag-based policies from a specific security zone in a tag-service. This enables tag-based authorization policies to be used based on the security zone of the resource.

Audit Logs

Audit logs generated by Ranger include the name of the security zone in which the accessed resource resides. Only users who have been assigned as an Admin or Auditor for the security zone are allowed to view the audit logs.

Adding a Ranger security zone

How to add a new Ranger Security Zone.

Procedure

1. Click Security Zone in the top menu.

The Security Zone page appears.

2. On the Security Zone page, click the + icon.

Ranger

Access Management

Security Zone

Security Zones

Search

security-zone1

The Create Zone page appears.

Security Zone

Create Zone

Create Zone

Zone Details :

Zone Name *

security-zone2

Zone Description

Zone Administration :

Admin Users

× admin

Admin Usergroups

Select Group

Auditor Users

× auditor1

Auditor Usergroups

Select Group

Services :

Select Tag Services

× cm_tag

Select Resource Services *

× cm_hive

3. Complete the Create Zone page as follows:

Table 55: Zone Details

Field	Description
Zone Name	The security zone name.
Zone Description	An optional description.

Table 56: Zone Administration

Field	Description
Admin Users	The Admin users for the security zone.
Admin Usergroups	The Admin user groups for the security zone.
Auditor Users	The Auditor users for the security zone.
Auditor Usergroups	The Auditor user groups for the security zone.

Table 57: Services

Label	Description
Select Tag Services	Select tag-based services for the security zone.
Select Resource Services	Select resource-based services for the security zone.

4. Selected Services are listed in the Services table. To add resources for each selected service, click the + icon in the Resources column for the applicable service.

Ranger

Access Management

Security Zone

Create Zone

Create Zone

Zone Details :

Zone Name *

sec

Zone Description

Zone Administration :

Admin Users

5. Use the Add/Edit Resources pop-up to specify resources for the service, then click Save.

Ranger

Access Management

Security Zone

Create Zone

Create Zone

Zone Details :

Zone Name *

secu

Zone Description

Zone Administration :

Admin Users

x a

The resources are listed in the Resources column of the Services table.

6. Click Save at the bottom of the Create Zone page to save the new security zone.

Ranger

Access Management

Security Zone

Create Zone

Create Zone

Zone Details :

Zone Name *

sec

Zone Description

Zone Administration :

Admin Users



7. The new security zone is listed on the Security Zone page.

Security Zone

Security Zones



security-zone1

security-zone2



security-

Zone Administration

Admin Us

Admin Usergro

Auditor Us

Auditor Usergro

Zone Tag Services

cm_tag

Services

Service

cm_hive

8. To edit a security zone, click the security zone name in the Security Zones list, then click Edit.


9. After security zones have been created, you can use the Security Zone selection box on the Service Manager page to display the services assigned to the selected security zone. A Zone Name column appears in the table on the Audit > Access page, and also in the Access Manager > Reports tables.

Ranger


Access Management

Service Manager

Service Manager

 **HDFS**

cm_hdfs

 **YARN**

cm_yarn

 **SOLR**

Administering Ranger Users, Groups, Roles, and Permissions

To view a list of the users, groups, and roles that can access the Ranger portal or its services, select Settings > Users/Groups/Roles in the top menu.

The Users/Groups/Roles page lists:

- Internal users who can log in to the Ranger portal; created by the Ranger console Service Manager.
- External users who can access services controlled by the Ranger portal; created at other systems such as Active Directory, LDAP, or UNIX, and synched with those systems.
- Admin users who are the only users with permission to create users and services, run reports, and perform other administrative tasks. Admin users can also create child policies based on the original policy (base policy).
- On the Groups page, you can click the people icons in the Users column to view the members of the applicable group.

Users/Groups/Roles

Users

Groups

Roles

Group List

Search for your groups...

<input type="checkbox"/>	Group Name	
<input type="checkbox"/>	livy	Ex
<input type="checkbox"/>	chrony	Ex
<input type="checkbox"/>	druid	Ex
<input type="checkbox"/>	kafka	Ex
<input type="checkbox"/>	knoxui	Ex
<input type="checkbox"/>	hdfs	Ex
<input type="checkbox"/>	hue	Ex
<input type="checkbox"/>	sqoop	Ex
<input type="checkbox"/>	yarn	Ex
<input type="checkbox"/>	centos	Ex
<input type="checkbox"/>	adm	Ex
<input type="checkbox"/>	systemd-journal	Ex
<input type="checkbox"/>	knox	Ex
<input type="checkbox"/>	mapred	Ex
<input type="checkbox"/>	tez	Ex
<input type="checkbox"/>	audit	Im

Add a user

How to add a new Ranger user.

Procedure

1. Select Settings > Users/Groups/Roles.
The Users/Groups/Roles page appears.

Users/Groups/Roles

Users

Groups

Roles

User List

Search for your users...

<input type="checkbox"/>	User Name	Email Address	
<input type="checkbox"/>	admin		A
<input type="checkbox"/>	rangerusersync		A
<input type="checkbox"/>	rangertagsync		A
<input type="checkbox"/>	hive		U
<input type="checkbox"/>	cloudera-scm		U
<input type="checkbox"/>	httpfs		U
<input type="checkbox"/>	superset		U
<input type="checkbox"/>	atlas		U
<input type="checkbox"/>	ranger		U
<input type="checkbox"/>	kudu		U
<input type="checkbox"/>	kms		U
<input type="checkbox"/>	accumulo		U

2. Click Add New User .

The User Detail page appears.

Ranger

Access Manager Audit Security Zone

Users/Groups/Roles User Create

User Detail

User Name *	<input type="text" value="auditor1"/>	
New Password *	<input type="password" value="....."/>	
Password Confirm *	<input type="password" value="....."/>	
First Name *	<input type="text" value="Audrey"/>	
Last Name	<input type="text"/>	
Email Address	<input type="text"/>	
Select Role *	<input type="text" value="Auditor"/>	
Group	audit	

Save Cancel

3. Add the required user details, then click Save.
The user is immediately added to the list.

Edit a user

How to edit a user in Ranger.

Procedure

1. Select Settings > Users/Groups/Roles.

The Users/Groups page opens to the Users tab.

The screenshot shows the Ranger Access Manager interface. At the top, there is a dark blue navigation bar with the 'Ranger' logo and three menu items: 'Access Manager' (with a shield icon), 'Audit' (with a document icon), and 'Security Zones' (with a lightning bolt icon). Below this is a light gray sidebar with a blue arrow-shaped button labeled 'Users/Groups/Roles'. Underneath, there are three tabs: 'Users' (which is selected and underlined), 'Groups', and 'Roles'. The main content area is titled 'User List' and features a search bar with the placeholder text 'Search for your users...'. Below the search bar is a table with the following columns: a checkbox column, a 'User Name' column, an 'Email Address' column, and a partial column with blue 'A' and 'U' icons. The table lists several users, including 'admin', 'rangerusersync', 'rangertagsync', 'hive', 'cloudera-scm', 'httpfs', 'superset', 'atlas', 'ranger', 'kudu', 'kms', and 'accumulo'.

<input type="checkbox"/>	User Name	Email Address	
<input type="checkbox"/>	admin		A
<input type="checkbox"/>	rangerusersync		A
<input type="checkbox"/>	rangertagsync		A
<input type="checkbox"/>	hive		U
<input type="checkbox"/>	cloudera-scm		U
<input type="checkbox"/>	httpfs		U
<input type="checkbox"/>	superset		U
<input type="checkbox"/>	atlas		U
<input type="checkbox"/>	ranger		U
<input type="checkbox"/>	kudu		U
<input type="checkbox"/>	kms		U
<input type="checkbox"/>	accumulo		U

2. Select a user profile to edit. To edit your own profile, select your user name, then click Profile.

Ranger

Access Management

Users/Groups/Roles

Users

Groups

User List

Search for your users

<input type="checkbox"/>	User Name
<input type="checkbox"/>	admin
<input type="checkbox"/>	rangerusersync
<input type="checkbox"/>	rangertagsync

The User Detail page appears.

Ranger

Access Manager Audit Security Zone

Users/Groups/Roles User Edit

User Detail

Basic Info Change Password

User Name * ⓘ

First Name * ⓘ

Last Name ⓘ

Email Address ⓘ

Select Role * ⌵

Group *Please select* ⓘ

Save Cancel

**Note:**

You can only fully edit internal users. For external users, you can only edit the user role.

3. Edit the user details, then click Save.

Delete a user

How to delete a user in Ranger.

Before you begin

Only users with the "admin" role can delete a user.


Procedure


1. Select Settings > Users/Groups.
The Users/Groups page appears.

The screenshot shows the Ranger web interface. The top navigation bar includes 'Ranger', 'Access Manager', 'Audit', 'Security Zone', and 'Settings'. The user 'admin' is logged in. The 'Users/Groups/Roles' section is active, with 'Users' selected. Below this is a search bar and buttons for 'Add New User', 'Set Visibility', and a trash icon. The main content is a 'User List' table.

<input type="checkbox"/>	User Name	Email Address	Role	User Source	Groups	Visibility
<input type="checkbox"/>	admin		Admin	Internal	--	Visible
<input type="checkbox"/>	rangerusersync		Admin	Internal	--	Visible
<input type="checkbox"/>	rangertagsync		Admin	Internal	--	Visible
<input type="checkbox"/>	hive		User	External	hive	Visible
<input type="checkbox"/>	cloudera-scm		User	External	wheel cloudera-scm	Visible
<input type="checkbox"/>	httpfs		User	External	httpfs	Visible
<input type="checkbox"/>	superset		User	External	superset	Visible
<input type="checkbox"/>	atlas		User	External	hadoop atlas	Visible
<input type="checkbox"/>	ranger		User	External	hadoop ranger	Visible
<input type="checkbox"/>	kudu		User	External	kudu	Visible
<input type="checkbox"/>	kms		User	External	kms	Visible
<input type="checkbox"/>	accumulo		User	External	accumulo	Visible

2.

Select the check box of the user you want to delete, then click the Delete icon () at the right of the User List menu bar.



The screenshot shows the Ranger Admin console interface. At the top, there is a navigation bar with 'Ranger' and several menu items: 'Access Manager', 'Audit', 'Security Zone', and 'Settings'. The user 'admin' is logged in. Below the navigation bar, there are tabs for 'Users/Groups/Roles', 'Users', 'Groups', and 'Roles'. The 'Users' tab is active, and the 'User List' is displayed. A search bar is at the top of the list, and there are buttons for 'Add New User', 'Set Visibility', and a Delete icon (highlighted with a red box). The table below shows a list of users with columns for 'User Name', 'Email Address', 'Role', 'User Source', 'Groups', and 'Visibility'. The user 'rangertagsync' is selected, and its checkbox is also highlighted with a red box.

<input type="checkbox"/>	User Name	Email Address	Role	User Source	Groups	Visibility
<input type="checkbox"/>	admin		Admin	Internal	--	Visible
<input type="checkbox"/>	rangerusersync		Admin	Internal	--	Visible
<input checked="" type="checkbox"/>	rangertagsync		Admin	Internal	--	Visible
<input type="checkbox"/>	hive		User	External	hive	Visible
<input type="checkbox"/>	cloudera-scm		User	External	wheel cloudera-scm	Visible
<input type="checkbox"/>	https		User	External	https	Visible
<input type="checkbox"/>	superset		User	External	superset	Visible
<input type="checkbox"/>	atlas		User	External	hadoop atlas	Visible
<input type="checkbox"/>	ranger		User	External	hadoop ranger	Visible
<input type="checkbox"/>	kudu		User	External	kudu	Visible

3. Click OK on the confirmation pop-up.

Add a group

How to add a group in Ranger.

Procedure

1. Select Settings > Users/Groups/Roles, then click the Groups tab.

The Groups page appears.

Ranger Access Manager Audit Security Zones

Users/Groups/Roles

Users Groups Roles

Group List

Search for your groups...

<input type="checkbox"/>	Group Name
<input type="checkbox"/>	livy
<input type="checkbox"/>	chrony
<input type="checkbox"/>	druid
<input type="checkbox"/>	kafka
<input type="checkbox"/>	KnoxUI
<input type="checkbox"/>	hdfs
<input type="checkbox"/>	hue
<input type="checkbox"/>	sqoop
<input type="checkbox"/>	yarn
<input type="checkbox"/>	centos
<input type="checkbox"/>	adm
<input type="checkbox"/>	systemd-journal
<input type="checkbox"/>	Knox
<input type="checkbox"/>	mapred
<input type="checkbox"/>	tez
<input type="checkbox"/>	...

2. Click Add New Group.

The Group Create page appears.

Ranger

Access Management

Users/Groups/Roles

Group Creation

Group Detail

Group Name *

Description

Save

3. Enter a unique name for the group and an optional description, then click Save.

Edit a group

How to edit a group in Ranger.

Procedure

1. Select Settings > Users/Groups/Roles, then click the Groups tab.

The Groups page appears.

Ranger Access Manager Audit Security Zones

Users/Groups/Roles

Users Groups Roles

Group List

Search for your groups...

<input type="checkbox"/>	Group Name
<input type="checkbox"/>	livy
<input type="checkbox"/>	chrony
<input type="checkbox"/>	druid
<input type="checkbox"/>	kafka
<input type="checkbox"/>	KnoxUI
<input type="checkbox"/>	hdfs
<input type="checkbox"/>	hue
<input type="checkbox"/>	sqoop
<input type="checkbox"/>	yarn
<input type="checkbox"/>	centos
<input type="checkbox"/>	adm
<input type="checkbox"/>	systemd-journal
<input type="checkbox"/>	Knox
<input type="checkbox"/>	mapred
<input type="checkbox"/>	tez

2. Select a group name to edit.

Ranger

Access Management

Users/Groups/Roles

Users

Groups

Group List

Search for your groups...

<input type="checkbox"/>	
<input type="checkbox"/>	public
<input type="checkbox"/>	hive
<input type="checkbox"/>	cloudera-scm

3. The Group Edit page appears.

Ranger

Access Management

Users/Groups/Roles

Group Edit

Group Detail

Group Name *

pub

Description

pub

Save

4. Edit the group details, then click Save.

Delete a group

How to delete a group in Ranger.

Before you begin

Only users with the "admin" role can delete a group.

Procedure

1. Select Settings > Users/Groups/Roles, then click the Groups tab.

The Groups page appears.

Ranger Access Manager Audit Security Zones

Users/Groups/Roles


Users Groups Roles


Group List

Search for your groups...











<input type="checkbox"/>	Group Name
<input type="checkbox"/>	livy
<input type="checkbox"/>	chrony
<input type="checkbox"/>	druid
<input type="checkbox"/>	kafka
<input type="checkbox"/>	KnoxUI
<input type="checkbox"/>	hdfs
<input type="checkbox"/>	hue
<input type="checkbox"/>	sqoop
<input type="checkbox"/>	yarn
<input type="checkbox"/>	centos
<input type="checkbox"/>	adm
<input type="checkbox"/>	systemd-journal
<input type="checkbox"/>	Knox
<input type="checkbox"/>	mapred
<input type="checkbox"/>	tez

2.

Select the check box of the group you want to delete, then click the Delete icon () at the right of the Group List menu bar.



The screenshot shows the Ranger Admin console interface. At the top, there is a navigation bar with 'Ranger' and 'Access Manager', 'Audit', 'Security Zone', and 'Settings'. The user 'admin' is logged in. Below the navigation bar, there are tabs for 'Users', 'Groups', and 'Roles'. The 'Groups' tab is active, and the 'Group List' section is displayed. A search bar is at the top of the list. Below the search bar, there are buttons for 'Add New Group', 'Set Visibility', and a 'Delete' icon (a trash can) which is highlighted with a red box. The table below shows a list of groups with columns for 'Group Name', 'Group Source', 'Visibility', and 'Users'. The 'wheel' group is selected, and its checkbox is also highlighted with a red box.

<input type="checkbox"/>	Group Name	Group Source	Visibility	Users
<input type="checkbox"/>	public	Internal	Visible	
<input type="checkbox"/>	hive	External	Visible	
<input type="checkbox"/>	cloudera-scm	External	Visible	
<input checked="" type="checkbox"/>	wheel	External	Visible	
<input type="checkbox"/>	https	External	Visible	
<input type="checkbox"/>	superset	External	Visible	
<input type="checkbox"/>	atlas	External	Visible	
<input type="checkbox"/>	hadoop	External	Visible	
<input type="checkbox"/>	ranger	External	Visible	
<input type="checkbox"/>	kudu	External	Visible	

3. Click OK on the confirmation pop-up.

What to do next

Users in a deleted group will be reassigned to no group. You can edit these users and reassign them to other groups.

Related Information

[Edit a user](#)

Add or edit permissions


How to add or edit user or group permissions in Ranger.

Procedure

1. Select Settings > Permissions.
The Permissions page appears.

The screenshot shows the Ranger interface with the 'Permissions' page selected. The 'Settings' menu is open, and 'Permissions' is highlighted. The main content area displays a table of permissions.

Modules	Groups	Users	Action
Resource Based Policies		admin rangerusersync keyadmin rangertagsync + More..	
Users/Groups		admin rangerusersync rangertagsync keyadmin + More..	
Reports		admin rangerusersync keyadmin rangertagsync + More..	
Audit		admin rangerusersync rangertagsync keyadmin + More..	
Key Manager		keyadmin	
Tag Based Policies		admin rangerusersync rangertagsync auditor1	
Security Zone		admin rangerusersync rangertagsync hive + More..	

2. Click the Edit icon () for the permission you would like to edit.
The Edit Permission page appears.

The screenshot shows the 'Edit Permission' page in Ranger. The 'Module Name' is 'Users/Groups'. The 'User and Group Permissions' section is active, showing a list of users: admin, rangerusersync, rangertagsync, keyadmin, and auditor1. There are 'x' icons next to each user name, and a '+' icon to add more users.

3. Edit the permission settings, then click Save.
You can select multiple users and groups using the + icons.

Administering Ranger Reports

You can use the Reports page to help manage policies more efficiently as the number of policies increases. This page lists all resource-based and tag-based policies.

Ranger

Access Manager

Audit

Security Zone

User Access R

Reports

- Resource Based Policies
- Tag Based Policies
- Reports**

Search Criteria

Policy Name

Policy

Component

Res

Policy Label

Zone

Search By

Q Search

HDFS

Policy ID	Policy Name	Policy Labels	Resources
1	all - path	--	path:/*


Allow Conditions

Groups

View Ranger reports

How to view reports for Ranger policies.

To view reports for one or more policies, select Access Manager > Reports.

- To view Allow Condition details for each policy, click the  icon in the Allow Conditions column. You can use the same method to view details for other policy conditions (Allow Exclude, Deny Conditions, etc.).
- To edit a policy from the Reports page, click the Policy ID.

Ranger

Access Manager

Audit

Security Zone

User Access R

Reports

- Resource Based Policies
- Tag Based Policies
- Reports**

Search Criteria

Policy Name

Policy

Component

Res

Policy Label

Zone

Search By

Q Search

HDFS

Policy ID	Policy Name	Policy Labels	Resources
1	all - path 187	--	path:/*
Allow Conditions		Groups	

Search Ranger reports

Reference information for searching Ranger reports on one or more policies.

You can search based on:

- Policy Name – The policy name.
- Policy Type – The policy type (Access, Masking, or Row Level Filter).
- Policy Label – The policy label.
- Component – The policy resource or tag component.
- Resource – The resource path used when creating the policy.
- Zone Name – The security zone name.
- Group, Username – The group or user name assigned to the policy.

Ranger

Access Manager

Audit

Security Zone

User Access R

Reports

- Resource Based Policies
- Tag Based Policies
- Reports**

Search Criteria

Policy Name

Policy

Component

Res

Policy Label

Zone

Search By

Group ▾

Q Search

HDFS

Policy ID	Policy Name	Policy Labels	Resources
1	all - path	--	path:/*

Allow Conditions

Groups

Export Ranger reports

Reference information for exporting Ranger reports on one or more policies.

You can export a list of reports in three file formats:

- CSV file
- Excel file
- JSON

Ranger

Access Manag

User Access Report

Reports

Search Criteria

Policy Name

Component

Policy Label

Related Information

[Export tag-based policies](#)

[Export resource-based policies for a specific service](#)

[Export all resource-based policies for all services](#)